



erwin Data Intelligence Suite

Mapping Management Guide

Release v10.2

Legal Notices

This Documentation, which includes embedded help systems and electronically distributed materials (hereinafter referred to as the “Documentation”), is for your informational purposes only and is subject to change or withdrawal by erwin Inc. at any time. This Documentation is proprietary information of erwin Inc. and may not be copied, transferred, reproduced, disclosed, modified or duplicated, in whole or in part, without the prior written consent of erwin Inc.

If you are a licensed user of the software product(s) addressed in the Documentation, you may print or otherwise make available a reasonable number of copies of the Documentation for internal use by you and your employees in connection with that software, provided that all erwin Inc. copyright notices and legends are affixed to each reproduced copy.

The right to print or otherwise make available copies of the Documentation is limited to the period during which the applicable license for such software remains in full force and effect. Should the license terminate for any reason, it is your responsibility to certify in writing to erwin Inc. that all copies and partial copies of the Documentation have been returned to erwin Inc. or destroyed.

TO THE EXTENT PERMITTED BY APPLICABLE LAW, ERWIN INC. PROVIDES THIS DOCUMENTATION “AS IS” WITHOUT WARRANTY OF ANY KIND, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NONINFRINGEMENT. IN NO EVENT WILL ERWIN INC. BE LIABLE TO YOU OR ANY THIRD PARTY FOR ANY LOSS OR DAMAGE, DIRECT OR INDIRECT, FROM THE USE OF THIS DOCUMENTATION, INCLUDING WITHOUT LIMITATION, LOST PROFITS, LOST INVESTMENT, BUSINESS INTERRUPTION, GOODWILL, OR LOST DATA, EVEN IF ERWIN INC. IS EXPRESSLY ADVISED IN ADVANCE OF THE POSSIBILITY OF SUCH LOSS OR DAMAGE.

The use of any software product referenced in the Documentation is governed by the applicable license agreement and such license agreement is not modified in any way by the terms of this notice.

The manufacturer of this Documentation is erwin Inc.

Provided with “Restricted Rights.” Use, duplication or disclosure by the United States Government is subject to the restrictions set forth in FAR Sections 12.212, 52.227-14, and

52.227-19(c)(1) - (2) and DFARS Section 252.227-7014(b)(3), as applicable, or their successors.

Copyright © 2020 erwin Inc. All rights reserved. All trademarks, trade names, service marks, and logos referenced herein belong to their respective companies.

Contact erwin

Understanding your Support

Review [support maintenance programs and offerings](#).

Registering for Support

Access the [erwin support](#) site and click Sign in to register for product support.

Accessing Technical Support

For your convenience, erwin provides easy access to "One Stop" support for [erwin Data Intelligence Suite \(DI Suite\)](#), and includes the following:

- Online and telephone contact information for technical assistance and customer services
- Information about user communities and forums
- Product and documentation downloads
- erwin Support policies and guidelines
- Other helpful resources appropriate for your product

For information about other erwin products, visit <http://erwin.com/>.

Provide Feedback

If you have comments or questions, or feedback about erwin product documentation, you can send a message to distechpubs@erwin.com.

erwin Data Modeler News and Events

Visit www.erwin.com to get up-to-date news, announcements, and events. View video demos and read up on customer success stories and articles by industry experts.

Contents

Legal Notices	2
Contents	5
Managing Mappings	11
Using Mapping Manager	12
Creating and Managing Mapping Specifications	14
Creating Projects	15
Adding Documents	18
Assigning Users	21
Assigning Roles	23
Configuring Extended Properties	26
Default Connector	29
Reference Data Manager	34
Importing from Excel	38
Setting Up Collaborations	40
Managing Topics	42
Creating Subject Areas	45
Subject Areas	45
Nested Subject Areas	46
Managing Subject Areas	49
Managing Projects	50
Defining Transformations	53
Configuring Transformation Library	56

Uploading Transformations	59
Downloading Templates	60
Managing Transformations	61
Creating Maps	64
Drag and Drop	69
Creating Mapping Specifications	69
Setting Target Update Strategy	70
Graphical	73
Creating Mapping Specifications	73
Setting Target Update Strategy	76
Auto-Map	78
Creating Mapping Specifications	78
Setting Target Update Strategy	81
Adding Transformations	82
One to Many and Many to Many Mapping Specifications	85
Creating Mapping Specifications	85
Setting Target Update Strategy	86
Adding Transformation and Lookup Details	89
Adding Transformation Details	89
Adding Lookup Details	94
Graphical Designer	96
Adding Transformation Details	96
Adding Lookup Details	100

Updating Mapping Specifications Manually	102
Uploading Mapping Specifications in XML	105
Specifying XPath in Mapping Specifications	108
Setting Column Order and Visibility	111
Column Order	111
Column Visibility	111
Updating Additional Mapping Information	113
Updating Map Spec Overview	116
Updating Source Extract SQL	119
Setting Target Update Strategy	121
Updating Testing Notes	123
Adding Mapping Specification Documents	125
Assigning Mapping Specifications to Users	127
Linking Additional Specification Artifacts	130
Recording Level of Effort	132
Viewing Change Logs	134
Viewing Release Information	135
Setting Up Collaborations	136
Configuring Extended Properties	138
Default Connector	141
Reference Data Manager	146
Importing from Excel	150
Branching and Merging Maps	152

Branching Maps	153
Merging Changes into Parent Maps	156
Deleting Maps	159
Viewing Workflow Logs	161
Analyzing Mappings	163
Generating Virtual Preview of Targets	164
Previewing Data	166
Performing Table Gap Analysis	169
Performing Column Gap Analysis	173
Running Impact Analysis	177
Running Lineage Analysis	182
System	183
Viewing Lineage	183
Working on Lineage	186
Environment	191
Viewing Lineage	191
Working on Lineage	194
Table	200
Viewing Lineage	200
Working on Lineage	203
Column	210
Viewing Lineage	210
Working on Lineage	213

Running End to End Lineage	220
Opening Business View	224
Viewing Mapping Statistics	229
Associating Mappings	231
Associating Code Maps with Data Item Mappings	232
Publishing Code Maps	232
Associating Code Maps	234
Associating Reference Tables with Mappings	237
Linking Requirements to Mappings	239
Publishing and Creating Versions of Mappings	241
Creating Versions of Maps	242
Base-lining Projects	245
Comparing Two Different Mapping Versions	247
Publishing Mappings	249
Publishing Mappings	249
Updating Publishing Details	252
Restoring Archived Maps As Active	254
Exporting Mapping Specifications	257
Proprietary XML Format	258
ETL Jobs	261
Creating and Managing Test Cases for Mappings	264
Creating Test Cases	265
Creating Project-Level Test Cases	265

Creating Map-Level Test Cases	267
Adding Validation Steps	270
Adding Validation Steps to Project-Level Test Cases	270
Adding Validation Steps to Map-Level Test Cases	272
Adding Documents	276
Adding Documents to Project-Level Test Cases	276
Adding Documents to Map-Level Test Cases	278
Managing Test Cases	282
Managing Project-Level Test Cases	282
Managing Map-Level Test Cases	283
Viewing Mapping Manager Dashboard	286
Statistics	288
Mapping Summary	288
Mapping Status	290
Proactive Impact Analysis - Truncation Impacts	292
Project Overview	294
Mapping Classification	295
Mapping Assignments	297
Sources/Targets Not Mapped	298
Test Case Status	300
Project Test Cases	302
User Test Cases	303

Managing Mappings

This section walks you through managing source to target mappings in the Mapping Manager.

Mapping Manager is the core of erwin Data Intelligence Suite (DI Suite), where you do the following:


- Source to target mappings using the Metadata Catalogue
- Associate crosswalks to mappings using the Code Mapping Catalogue
- Associate reference data to mappings using the Reference Table Catalogue
- Associate requirements to mappings using the Specification Artifact Catalogue
- Create new mapping versions
- Specify test cases

Once mappings are approved for coding, ETL developers can export them as coding requirements. They can also export the mappings to XML and automatically generate ETL/ELT jobs for ETL tools, such as Informatica PowerCenter, IBM DataStage, Microsoft SQL Server SSIS, and so on.

For further information on accessing and using the Mapping Manager, refer to the [Using Mapping Manager](#) topic.

Using Mapping Manager

To access the Mapping Manager, go to **Application Menu > Data Catalog > Mapping Manager**. The Mapping Manager dashboard appears:



UI Section	Function
1-Workspace Mappings	Use this pane to browse and work on projects and mappings.
2-Central Pane	Based on your selection in the browser pane, use this pane to view or work on the data.
3-Mapping Manager Dashboard	Use this pane to view statistics related to mappings and projects.
4-Published Mappings	Use this pane to view and export details of published mappings.

Managing mappings involves the following:

- [Creating and managing mapping specifications](#)
- [Analyzing mappings](#)
- [Associating mappings](#)
- [Publishing and creating mapping versions](#)

- [Exporting mapping specifications](#)
- [Creating and managing test cases for mappings](#)
- [Viewing mapping manager dashboard](#)

Creating and Managing Mapping Specifications

After defining systems and uploading metadata in the Metadata Manager, you can create mapping specifications. The Mapping Manager offers multiple ways to create mapping specifications. This section walks you through building metadata driven source to target mapping specifications and enterprise standards to manage them.

Creating and managing mapping specifications involves:


- [Creating projects](#)
- [Defining transformations](#)
- [Creating maps](#)
- [Adding transformations and lookup details](#)
- [Updating mapping specifications manually](#)
- [Uploading mapping specifications in XML format](#)
- [Specifying XPath in mapping specifications](#)
- [Setting column order and column visibility](#)
- [Updating additional mapping information](#)
- [Branching and merging maps](#)
- [Deleting maps](#)
- [Viewing workflow logs](#)

Creating Projects

Projects store and group maps in a hierarchy, Projects > Mappings. You can create an ETL tool-specific project and specify its details, such as project description, project manager, business sponsor, cost center, and IT sponsor.

To create projects, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, right-click the **Projects** node.



Workspace Mappings		Project Summary	
		#	Project Name
Mappings			
Transformations			
Projects			<input type="text"/>
Ac		1	ERP
Al		2	EDW
BE		3	Sales Data Mart
BF			
Curator (7)			
Data Lake Migration (3)			
EDW (2)			

3. Click **Create Project**.

The Create Project page appears.

The screenshot shows the 'Create Project' dialog box with the 'Project Details' tab selected. The form contains the following fields and controls:

- Project Name***: A text input field.
- Cost Center**: A text input field.
- Description**: A rich text editor with a toolbar containing icons for bold, italic, underline, text color, background color, bulleted list, numbered list, indent, and outdent.
- Project Manager Name**: A text input field.
- IT Sponsor Name**: A text input field.
- Business Sponsor Name**: A text input field.
- Project ETL**: A dropdown menu currently showing 'SSIS Pseudocode'.
- Enable display of Transformation without pseudocode**: A toggle switch currently set to 'NO'.

At the top right, there are three buttons: 'Save & Continue', 'Save & Exit', and 'Cancel'. The 'Project Details' tab is highlighted in orange.

4. Enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.

Field Name	Description
Project Name	Specifies the name of the project. For example, Data Lake Migration. For more information on naming conventions, refer to the Best Practices section.
Description	Specifies the description of the project. For example: The project contains the mapping specifications for the sales data migration.
Project Manager Name	Specifies the project manager's name. For example, John Doe.
Business Sponsor Name	Specifies the business sponsor of the project. For example, ABC Consulting Services.
Project ETL	Specifies the ETL tool assigned to the project. For example, Informatica Pseudocode.
Cost Center	Specifies the cost center of the project.

Field Name	Description
	For example, Finance and Accounting.
IT Sponsor Name	Specifies the IT sponsor of the project. For example, XYZ IT Services.
Enable display of Transformation without pseudocode	Specifies whether the transformation is displayed without pseudocode. Switch Enable display of Transformation without pseudocode on (<input checked="" type="radio"/>) to display transformation without pseudocode.

5. Click **Save and Exit**.

A new project is created and added to the project tree.

Once a project is created, you can enrich it further by:

- [Adding supporting project documents](#)
- [Assigning users to the project](#)
- [Configuring extended properties](#)
- [Setting up collaborations](#)
- [Creating subject areas](#)
- [Creating maps](#)

You can also manage a project by using the options available on right-clicking the project.

[Managing projects](#) involves:

- Uploading legacy maps
- Exporting maps
- Exporting change logs
- Viewing reports
- Sharing links
- Deleting projects
- Viewing workflows


Adding Documents

You can add supporting documents, such as text files, audio files, video files, document links, and so on to a project.

To add documents to projects, follow these steps:

1. In the **Workspace Mappings** pane, click a project.
2. Click the **Project Documents** tab.

The following page appears.



3. Click .

The Add Project Document page appears.

The screenshot shows the 'Add Project Document' form. It includes input fields for Document Name, Document Reference, Reference Number, Document Link, and Document Owner. There is also a text area for Description with a rich text editor toolbar and a checkbox for Approval Required Flag.

Document Name* Document Owner

Document Reference Document Object

Reference Number Drag-n-Drop files here or click to select files for upload. 

Document Link

Description 


Approval Required Flag

4. Enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.

Option	Description
Document Name	Specifies the name of the physical document being attached to the project. For example, Project Details.
Document Reference	Specifies the name of the reference document. For example, Wikipedia pages.
Reference Number	Specifies the reference number of the reference document. For example, KB_230145.
Document Owner	Specifies the document owner's name. For example, John Doe.
Document Object	Drag and drop or use  to browse and select the document.
Document Link	Specifies the URL of the document. For example, https://drive.google.com/file/d/2sC2_SZlYeFKI70On-b5YkMBq4ptA7jhg5/view
Description	Specifies the description of the document. For example: The document is to keep a record of description and data dictionary of the system.
Approval Required Flag	Specifies whether the document requires approval or not. Select the Approval Required Flag check box to select the document status.
Document Status	Specifies the status of the document. For example, In Progress. Select the status of the document from the drop down. This field is available only when the Approval Required Flag check box is selected.

5. Click .

The project document is saved in the Project Documents Grid.



Once a supporting document is added, use the following options:

Information (i)

Use this option to view the document information.

Download (↓)

Use this option to download the document.

Edit (✎)

Use this option to update the document details.

Delete (✕)

Use this option to delete the document that is not required.


Assigning Users

You can assign one or more members of your team to a project. Team members assigned to a project have write access to all mappings under it. Ensure that the roles assigned to the users have the required permissions.

To assign users, follow these steps:

1. In the **Workspace Mappings** pane, click a project.
2. Click the **Project Users** tab.

The Project Users page appears.



#	User ID	User Full Name	Assigned Role	Email ID	Manager Name
1	esimpson	Erica Simpson	Data Owner_GER	e.simpson@xyz.	
2	jadams	Joey Adams	Tech Data Steward_GER	jadams@xyz.com	
3	janedoe	Jane Doe	Mapping Designer	jane.doe@edufir	K.Sridhar

3. Click .

The Assign Project Users page appears.



4. Select user IDs under User ID list-box and move them to Assigned Users list-box using the arrows ( or ). Similarly, to change existing user assignment, select user IDs

under Assigned Users list-box and move them back to User ID list-box using the arrows ( or ).



You cannot assign users with Administrator role to projects.

5. Click .

The selected users are assigned to the project.

Project Users						
#	User ID	User Full Name	Assigned Role	Email ID	Manager Name	View Edit Delete
1	esimpson	Erica Simpson	Data Owner_GER	e.simpson@xyz.		  
2	jadams	Joey Adams	Tech Data Steward_GER	jadams@xyz.coi		  
3	janedoe	Jane Doe	Mapping Designer	jane.doe@edufir	K.Sridhar	  
4	jwilson	Joey Wilson	Tech Data Steward_RO	jwilson@xyz.coi		  

Use the following options to work on the project users list:

Information ()

Use this option to view project user details, such as telephone number, company, and the assigned responsibility.

Edit ()

Use this option to update project user details, such as assigned role and assigned responsibility.

Delete ()

Use this option to remove a user from the project users list.


Assigning Roles

You can assign one or more roles to a project. Users assigned to these roles get write access to all the mappings in the project. Ensure that the roles have the required permissions to access the Mapping Manager.

To assign roles, follow these steps:

1. In the **Workspace Mappings** pane, click a project.
2. Click the **Project Roles** tab.

The Project Roles page appears.



#	Role Name	Role Description	Role Users
1	Data Owner_RO	This role is accountable for who has access to information assets within their functional areas ft	View
2	Data Steward_RO	This role is responsible for utilizing Romania's data governance processes to ensure fitness	View
3	Mapping Admin	Administers Mapping Manager module to define, edit or delete any mapping in any project irres	View

3. Click .

The Assign/Unassign Roles page appears.

Assign/Unassign Roles				
#	Select Role	Role Name	Role Description	Role Users
	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	
1	<input checked="" type="checkbox"/>	Data Owner_RO	This role is accountable for who has access to information assets within their functional areas for Romania. It may decide to review and authorize each access request individually or may define a set of rules that determine who is eligible for access based on business function, support role, etc.	View
2	<input checked="" type="checkbox"/>	Data Steward_RO	This role is responsible for utilizing Romania's data governance processes to ensure fitness of data elements - both the content and metadata.	View
3	<input checked="" type="checkbox"/>	Mapping Admin	Administers Mapping Manager module to define, edit or delete any mapping in any project irrespective to project assignment	View
4	<input type="checkbox"/>	Mapping_Tester		View
5	<input type="checkbox"/>	Tech Data Steward_UK	This role is responsible to answer how data is created, transformed, stored, and moved in technical systems for UK.	View

4. Select the required roles.

5. Click .

The selected roles are assigned to the project.

Project Roles			
#	Role Name	Role Description	Role Users
1	Data Owner_RO	This role is accountable for who has access to information assets within their functional areas fr	View
2	Data Steward_RO	This role is responsible for utilizing Romania's data governance processes to ensure fitness	View
3	Mapping Admin	Administers Mapping Manager module to define, edit or delete any mapping in any project irres	View
4	Tech Data Steward_UK	This role is responsible to answer how data is created, transformed, stored, and moved in technr	View

You can view the users assigned to roles. To view Role Users, click **View**.

For example, the following Role Users page displays the users assigned to the Data Owner_RO role.


Role Users	
User ID	User Full Name
1 ksridhar	Kartik Sridhar
2 srahim	Syed Rahim

Configuring Extended Properties


You can configure user-defined project properties under the Extended Properties tab. First, you need to set up a form and then use it to configure the user-defined extended properties.

To configure extended properties of projects, follow these steps:

1. In the **Workspace Mappings** pane, click a project.
2. Click the **Extended Properties** tab.




3. Click **Configure**.



The **Extended Properties Configuration** page contains the following sections:

- **Field Controls:** Use this pane to get the required UI elements.
- **Configure Form:** Use this pane to design forms using the UI elements available in the **Field Controls** pane.
- **Properties:** Use this pane to view the properties of the UI element selected in the **Configure Form** pane.

- Click **Edit**. Then, double-click or drag and drop the required UI elements from the **Field Controls** pane to the **Configure Form** pane.
- Select UI elements, one at a time, and configure their properties in the **Properties** pane.



 The available properties differ based on the type of UI element.

Refer to the following table for property descriptions:

Property	Description
Published	Switch Published to ON to publish the field.
Field	Specifies the field label. To change the field labels, double-click the corresponding Value cell. For example, Project Approved On.
Type	Specifies the type of the field. To select field types, double-click the corresponding Value cell. For example, Date Picker.
Dependencies	Defines the pick list that can be used as controlling fields. It works

Property	Description
	<p>only with the Reference Data Manager connector.</p> <p>To define pick list, select the fields from the drop down option.</p>
Configure Values	<p>Specifies the connectors for the field.</p> <p>To enter option values, click Configure Values.</p> <p>Use the following options:</p> <ul style="list-style-type: none"> ▪ Default connector: Use this option to enter option values manually or using an MS Excel file. ▪ Reference Data Manager: Use this option to pull option values from reference tables in the Reference Data Manager.
Mandatory	Specifies whether the field is mandatory.
Description	<p>Specifies the field description.</p> <p>To enter field descriptions, double-click the corresponding Value cell.</p>
Visible in Extended Properties	Switch Visible in Extended Properties to ON to make it visible on the Extended Properties tab.
Order	<p>Specifies the order of the field on the Extended Properties tab.</p> <p>To enter the order number, double-click the corresponding Value cell.</p> <p>You can also drag and move fields in the Configure Form pane to change their order.</p>

6. Click **Save**.

The form is saved, and is available on the **Extended Properties** tab.

You can download extended properties in the XLSX format and use it as a template to [import extended properties](#). To download extended properties, on the **Extended Properties** tab, click **Export To Excel**.

Default Connector

When you configure extended properties using UI elements, such as combo box, radio button, and list, you also need to configure their option values. You can use the default connector to import option values from an MS Excel file or enter them manually.


To configure option values using the default connector, follow these steps:

1. In the **Configure Form** section, click the required UI element.

Ensure that you are in edit mode.


2. In the **Properties** section, click **Configure**.

The Connectors page appears.



3. On the **Connectors** page, ensure that the Default Connector option is selected. Then, click **Next**.

The <UI_Element> Options page appears. For example, if the UI element is Combo Box, the Combo Box Options page appears.



4. Use the following options:

Add

Use this option to enter text and value manually.

Import Excel


Use this option to import options from MS Excel files.

5. After configuring option values, click **Save**.

To add option values manually, follow these steps:


1. Click **Add**.
2. Enter values to the Text and Value fields.

The Text corresponds to options whereas the Value corresponds to underlying value of an option. You can add as many values as needed.



3. Click **Save**.


The option values appear in the UI element under the Configure Form section.



To import option values from MS Excel files, follow these steps:

1. Click **Import Excel**.

The Upload Excel page appears.



2. Click **Choose File** and select the required MS Excel file.

The Upload Excel page appears. It displays the data in the MS Excel file.

#	GROUP NAME	ROLE NAME	USER ID
#	Select Column To Import	Select Column To Import	Select Column To Import
1	Data Stewards	Data Steward_GER	mmannigan
2	Data Stewards	Data Steward_GER	mmenza
3	Data Stewards	Data Steward_GER	mmannigan

3. Double-click the **Select Column To Import** cell in the required column.

The available options appear.

#	GROUP NAME	ROLE NAME	USER ID
#	Select Column To Import	Select Column To Import	Select Column To Import
1	Data Stewards	Data Steward_GER	mmannigan


Dropdown menu options:
 Select Column To Import
 FIELD
 VALUE
 Clear Selection

4. Select the appropriate option.

Field corresponds to options and Value corresponds to value of an option. You can import multiple columns. Use Clear Selection to undo the selection.


5. Click .

The <UI_Element> Options page appears. It displays the imported columns. You can delete a row that is not required. To delete rows, click a row and then click **Delete**.



6. Click **Save**.

The option values appear in the UI element under the Configure Form section.



Reference Data Manager

When you configure extended properties using UI elements, such as combo box, radio button, and list, you also need to configure their option values. You can use the Reference Data Manager connector to import option values from tables in the Reference Data Manager.


To configure option values using reference data manager connector, follow these steps:

1. In the **Configure Form** section, click the required UI element.

Ensure that you are in edit mode.


2. In the **Properties** section, click **Configure**.

The Connectors page appears.




3. On the **Connectors** page, click **Reference Data Manager** and then click **Next**.


The Reference Data Manager page appears. It displays the reference folders in the Connector View pane.



4. In the **Connector View** pane, expand a reference folder and select a reference table. The Parameters pane displays the columns in the reference table. You can also click Preview to view the data in the reference table.




5. In the **Parameters** pane, click the radio button next to the required column.
 You can select the controlling field from the drop down option. Ensure that you define the required dependencies in the Properties pane and that the option values for controlling field are configured using the same reference column.
6. Click **Finish**.
 The Extended Properties Configuration page appears.



7. Under the **Properties** section, switch **Load on Startup** to **ON**.
8. Click **Save**.

The option values are configured. For example, in the following form the List of Cities is the controlling field for Selected City. Both the fields get their option values from the same reference column.




Importing from Excel

You can import user-defined project properties from an XLSX file. You can either use an existing XLSX file or download an extended properties file from a project. Ensure that the XLSX file follows the correct template.

To import extended properties from XLSX files, follow these steps:


1. On the **Extended Properties** tab, click **Import From Excel**.

The Upload Excel page appears.



2. Click **Choose File**.
3. Browse and select the XLSX file.
4. Click .

The Upload Excel page appears. It displays the data in the XLSX file.



#	FIELD	VALUE	TYPE	PARENTFIELD	CREATED_BY	CREATED_DATE_TIME
#	Select Column To Import					
1	Data Stewards		Combo Box			
2	Data Steward_UK	Data Steward_UK	Text Box	/Data Stewards	Administrator	10/20/2020 06:42:38
3	Data Steward_GER	Data Steward_GER	Text Box	/Data Stewards		
4	Data Owners	Data Owner_GER	Text Box		Administrator	10/20/2020 06:42:38

5. Double-click the **Select Column To Import** cell in the required column.

The available options appear.

Upload Excel

#	FIELD	VALUE	TYPE	PARENTFIELD
#	Select Column To Import			
1	FIELD		Combo Box	
2	Data Steward_UK	Data Steward_UK	Text Box	/Data Stewards
3	Data Steward_GER	Data Steward_GER	Text Box	/Data Stewards

6. Select an appropriate option.

For example, if you select Field, then the selected column is imported as Field.

Similarly, you can also select the Value, Type, and Parentfield columns. Ensure that you at least select a Field column.

7. Click .

The extended properties are imported.

Configure Edit Delete Import From Excel Export To Excel

Form Values

Data Stewards

Data Owners

Technical Data Steward

Compliance Officer

Self Help

Setting Up Collaborations

You can start discussions on mapping projects or a relevant topic with your team using the Collaboration Center. This enables you and your team to work together.


To set up collaborations, follow these steps:

1. In the **Workspace Mappings** pane, click a project.

The Mapping Summary page appears.


#	Project Name	Subject Hierarchy	Map Name	Lock Status	Locked By	Locked Date	Mapping State	Mapping Description
1	erwinDIS		BugTrial	🔒			In Progress	Testing for a bug logged by QA
2	erwinDIS		Data Integration	🔒	Administrator	05/25/2020 12:05:21	In Progress	
3	erwinDIS		erwinSalesIntegration	🔒			In Progress	
4	erwinDIS		SalesforceIntegration	🔒			In Progress	
5	erwinDIS		TechPubsBugTrial	🔒			In Progress	TechPubsBugTrial

2. Click the **Collaboration Center** tab.



3. Click **+**.

The Add Topic page appears.



4. Enter the **Topic Name** and **Description**.

5. Click .

The topic is saved and added to the list of topics on the Collaboration Center tab.

You can manage a topic using the options available under Topic Options (). [Managing a topic](#) involves:

- Viewing, editing, or deleting a topic
- Assigning users
- Managing notifications
- Saving topic conversations
- Sharing a topic

Managing Topics


Managing topics involves:

- Viewing, editing, or deleting a topic
- Assigning users
- Managing notifications
- Saving topic conversations
- Sharing a topic

To manage topics, follow these steps:

1. Click the **Collaboration Center** tab.
2. In the list of topics, on the topic you want to manage, click .


Topic options appear.



3. Use the following options:

View Topic Details

Use this option to view topic details, such as creator, the creation date and time, and the modification date and time.



Edit Topic Details

Use this option to edit the topic name and description to enrich it further.

Assign Users

Use this option to assign multiple users to collaborate with you and contribute to the topic.


To assign users, click **Assign Users**.

The User Assignment page appears.



Select users and click .

The assigned users can chat and collaborate with each other.



Disable Notification

Use this option to choose whether you are notified whenever the topic is updated.

Save Conversation as Text

Use this option to save topic conversations to a text file. This option downloads a text file with the conversation, authors, and time stamp.

Send Topic as Email

Use this option to send the topic and its conversations in an email. Clicking **Send Topic as Email** opens an email recipient list, where you can select one or multiple recipients. Click  to send an email to the selected recipients.

Delete Topic

Use this option to delete a topic that is no longer required.


Creating Subject Areas

Subject areas provide one more level of grouping for mapping specifications. You can create a subject area within a project or within another subject area. Ensure that the subject area names are unique under each project.

Subject Areas


To create subject areas, follow these steps:

1. In the **Workspace Mappings** pane, right-click a project.



2. Click **New Subject Area**.

The Add Subject page appears.



3. Enter the **Subject Name** and **Subject Description**.

For example:

- **Subject Name:** Members.
- **Subject Description:** This subject area is created to arrange the mappings logically.

You can use additional fields and define UI labels in [Language Settings](#).

4. Click .


The subject area is saved and added to the project.

Nested Subject Areas

You can create subject areas within another subject area. These subject areas are called nested subject areas.


To create nested subject areas, follow these steps:

1. In the **Workspace Mappings** pane, right-click a subject area.



2. Click **New Subject Area**.

The Add Subject page appears.



3. Enter the **Subject Name** and **Subject Description**.

You can use additional fields and define UI labels in [Language Settings](#).

4. Click .

A subject area is created under the subject area.


Managing Subject Areas

Managing subject areas involves:

- Deleting
- Reordering

To manage subject areas, follow these steps:

1. In the **Workspace Mappings** pane, right-click a subject area.



2. Use the following options:

Delete Subject Area

Use this option to delete subject areas that are not required.

Reorder Subject Areas

Use this option to reorder subject areas. To reorder subject areas, click **Reorder Subject Areas**.

The Subject for <Project_Name> page appears.

#	Subject Name	Current Order	New Order	Parent Hierarchy	Created By	Created Date	Modified By	Modified Date
1	L_Name[0]	1	1	A_Project	Administrator	2019-10-30 11:45:11.917	Administrator	2019-10-30 11:45:11.917
2	P_Name[0]	2	2	A_Project	Administrator	2019-10-30 11:44:51.983	Administrator	2019-10-30 11:44:51.983
3	S_Name[0]	3	3	A_Project	Administrator	2019-10-30 11:35:42.867	Administrator	2019-10-30 11:35:42.867

To order subject areas, from the **Order By** list, select one of the following options:

- **Ascending Order:** Select this option to order in ascending alphabetical order.
- **Descending Order:** Select this option to order in descending alphabetical order.
- **Custom Order:** Select this option to order in custom order.

To sort subject areas, from the **Sort Subjects By** list, select one of the following options:

- **Subject Name:** Select this option to sort by subject name.
- **Created By:** Select this option to sort by the users who created subject areas.
- **Created Date:** Select this option to sort by created date.
- **Modified By:** Select this option to sort by the users who modified subject areas.
- **Modified Date:** Select this to sort by the modified date.

Managing Projects

Managing projects involves:


- Uploading legacy maps
- Exporting maps
- Exporting change logs
- Viewing reports

- Sharing links
- Deleting projects
- Viewing workflows

To manage projects, follow these steps:

1. In the **Workspace Mappings** pane, right-click a project.

The available options appear.



2. Use the following options:

Upload Legacy Maps

Use this option to upload legacy maps in the XLSX format. Ensure that you use the correct template.

Export All

Use this option to download the required maps in a project.

Export Change Log

Use this option to download change logs of all the maps in a project.

Reports

Use this option to download reports related to a project.

Share Link

Use this option to share link to a project with your team members.

Delete Project

Use this option to delete a project.

View Workflow

Use this option to view workflow status of a project.


Defining Transformations

Transformations specify rules that derive values from source columns to get the required values in target columns. You can define enterprise-level and project-level transformations. These transformations can be used as business rules and extended business rule transformations in mapping specifications. Ensure that you define transformations for the same ETL option as that of your mapping project.

To define transformations, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, click any one of the following:
 - **Transformations node**: Click this option to define enterprise-level transformations.
 - **Transformations node under a project**: Click this option to define project-level transformations.


For example, if you click the Transformations node, then the Transformation Details page appears.



#	Transformation Name	SSIS Pseudocode	Informatica Pseudocode	Intended Use
1	1-DataGov(HighDate:12/31/9999)		To_date(mm/dd/yyyy,12/31/9999)	DataGovernance r...
2	2-DataGov(LowDate01/01/0001)		To_date(mm/dd/yyyy, 01/01/0001)	DataGovernance r...
3	3-DataGov(AverageChurn)		Count(active customers)/(Count of Cancelled Customers for current month)	DataGovernance r. Churn KPIs are used.

3. Click .

The Transformation Rule Editor page appears.



4. Enter or select appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.

Field Name	Description
Published	Switch Published on () to publish the transformation.
Transformation Name	Specifies a unique name of the transformation. For example, ASCII.
Scope	Specifies the projects to which the transformation can be applied. For example, All Projects.
ETL Option	Specifies the ETL option. For example, Informatica Pseudocode. You can configure ETL option list and add or remove an ETL option from the list.

Field Name	Description
Replace Transformation Name with Pseudocode	Switch Replace Transformation Name with Pseudocode on () to replace the transformation name with pseudocode.
Pseudocode	Specifies the pseudocode for the transformation. Enter a pseudocode or use Ctrl + Space keys to select a pseudocode. For example, To_date(mm/dd/yyyy,1231,9999).
Intended Use	Specifies the objective of the transformation. For example: Data governance rule - use on projects.

5. Click .

A new transformation is added on the Transformations Details page.

You can upload transformations in bulk [using an MS Excel file](#).

Once a transformation is defined, you can manage it using the options available on right-clicking the transformation. [Managing Transformations](#) involves:

- Editing transformations
- Running impact analysis
- Viewing history

Configuring Transformation Library

You can create transformations for the following ETL options:


- DataStage Pseudocode
- BODS Pseudocode
- SSIS Pseudocode
- Informatica Pseudocode
- ODI Pseudocode
- Talend Pseudocode

This ETL options list forms the Transformation Library and is configurable. You can add or remove an ETL option from the ETL options list.

To configure transformation library, follow these steps:

1. In the **Workspace Mappings** pane, click the **Transformations** node.


The Transformation Details page appears.



#	Transformation Name	BODS Pseudocode	SSIS Pseudocode	Informatica Pseudocode	ODI Pseudocode	Talend Pseudocode
1	1-DataGov(HighDate:12/31/9999)			To_date(mm/dd/yyyy,12/31/9999)		
2	2-DataGov(LowDate01/01/0001)			To_date(mm/dd/yyyy, 01/01/0001)		
3	3-DataGov(AverageChurn)			Count(active customers)/(Count of Cancelled Customers for current month)		

2. Click .

The ETL Settings page appears.



3. Switch an **<ETL_Option>** key to **ON** to add the corresponding ETL option to the Transformation Library.

For example, switch **BODS Pseudocode** to **ON** to add BODS Pseudocode to the Transformation Library.

4. Click **Save**.

ETL options are added to the ETL Option list.

Transformation Rule Editor

Published OFF

Transformation Name*

Scope

ETL Option

Pseudocode

- BODS Pseudocode
- SSIS Pseudocode
- Informatica Pseudocode
- ODI Pseudocode
- Talend Pseudocode

Note: Press 'Ctrl + Space' to select Transformations

Intended Use

Uploading Transformations

You can upload transformations in bulk using an MS Excel file. You can either use an existing MS Excel file or a template to upload transformations. Ensure that the MS Excel file follows the correct template.

To upload transformations, follow these steps:


1. In the **Workspace Mappings** pane, click the **Transformations** node.

The Transformation Details page appears.

#	Transformation Name	Informatica Pseudocode	Intended Use	Scope
1	1-DataGov(HighDate:12/31/9999)	Ta_date(mm/dd/yyyy,12/31/9999)	DataGovernance rule - use on all projects	All Projects
2	2-DataGov(LowDate01/01/0001)	Ta_date(mm/dd/yyyy,01/01/0001)	DataGovernance rule - use on all projects	All Projects

2. Click .

The Upload Transformations page appears.



3. Drag and drop or use  to browse and select the MS Excel file.

You can use a template to upload transformations. For more information on downloading templates, refer to the [Downloading Templates](#) section.


4. Click .

The file is uploaded, and transformations are added to the Transformation Details page.

Downloading Templates

To download templates, follow these steps:

1. In the **Workspace Mappings** pane, right-click the **Transformations** node.



2. Click **Download Template**.

The template is downloaded in the XLSX format. You can update the MS Excel file with the required transformations.

Managing Transformations


Managing transformations involves:

- Editing transformations
- Deleting transformations
- Running impact analysis
- Viewing history

To manage transformations, follow these steps:

1. In the **Workspace Mappings** pane, click the **Transformations** node.

The Transformation Details page appears.




#	Transformation Name	BODS Pseudocode	SSIS Pseudocode	Informatica Pseudocode	ODI Pseudocode	Talend Pseudocode
1	1-DataGov(HighDate:12/31/9999)			To_date(mm/dd/yyyy,12/31/9999)		
2	2-DataGov(LowDate01/01/0001)			To_date(mm/dd/yyyy, 01/01/0001)		
3	3-DataGov(AverageChurn)			Count(active customers)/(Count of Cancelled Customers for current month)		

2. Select the required row and right-click it.

The available options appear.

Transformation Details			
#	Transformation Name	BODS Pseudocode	SSIS Pseudocode
	<input type="text"/>	<input type="text"/>	<input type="text"/>
31	EXT		
32	FIRST		
33	FLOOR		
34	FV		
35	GET_DATE_PART		



3. Use the following options:

Edit Transformation Details

Use this option to edit transformation details, such as transformation name and its scope.

Delete

Use this option to delete the selected transformation.



If a transformation is already used in a Mapping Specification, it is still visible under it. However, it is not available for future use.

Impact Analysis Report

Hover over **Impact Analysis Report** and use the following options to view impact analysis of transformations:

Default Search: Use this option to view the impact analysis report of the selected transformation.

Advanced Search: Use this option to select multiple transformations and view their impact analysis report.

For example, the following image displays the impact analysis of a transformation.

Advanced Search

Business Rule: LOWER

Impact Analysis Report

#	Project Name	Mapping Name	Map Specification Version	Business Rule
1	TestData_Map	HeteroMultiSrc_Lookup_BR_He	1.0	LOWER(#1)
2	TestData_Map	HeteroMultiSrc_Lookup_BR_Hc	1.0	LOWER(#1)
3	TestData_Map	HomoMultiSrc_Lookup_BR_He	1.0	LOWER(#1)
4	TestData_Map	HomoMultiSrc_Lookup_BR_Ho	1.0	LOWER(#1)
5	TestData_Map	MultiSource_Lookup_BusRule_S	1.0	LOWER(#1)
6	TestData_Map	SingleSource_Lookup_BusRule	1.0	LOWER(#1)

History

Use this option to view activity logs of a transformation.

For example, the following image displays the history of a transformation.

History

#	Transformation Name	Pseudocode	Intended Use	Created By	Created Date Time	Last Modified By	Last Modified Date Time
1	FLOOR		ETL Built-In Transformation: Record handling and processing rule for all projects. Returns the largest integer less than or equal to the numeric value you pass to this function. For example, if you pass 3.14 to FLOOR, the function returns 3. If you pass 3.98 to FLOOR, the function returns 3. Likewise, if you pass -3.17 to FLOOR, the function returns -4.	Administrator	2018-09-14 10:39:48.937	Administrator	2020-01-13 16:23:56.38


Creating Maps

You can create maps under a project or subject area. You can perform source to target mappings and create mapping specifications in maps. These mapping specifications facilitate your data integration project.

To create maps, follow these steps:


1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, right-click a project or subject area.

For example, when you right-click a project the available options appear.



3. Click **New Map**.

The New Mapping Wizard page appears.




4. Enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.

Field Name	Description
Mapping Name	Specifies the mapping specification name. For example, EDW_PROD_IDS_Benefits_Detail. For more information on naming conventions, refer to the Best Practices section.
Mapping Version	Specifies the version of the mapping specification. This field is autopopulated. For example, 1.00. For more information on configuring version display of maps, refer to the Configuring Version Display topic.
Sync Source Metadata	Specifies whether source metadata syncs with the mapping. Switch Sync Source Metadata to ON to sync source metadata with the mapping.
Sync Target Metadata	Specifies whether target metadata syncs with the mapping. Switch Sync Target Metadata to ON to sync target metadata with the

Field Name	Description
	mapping.
Mapping Description	<p>Specifies the description of the mapping.</p> <p>For example: This is a map between EDW source and IDS target systems.</p>
Mail Comments	<p>Specifies the mail comments, which can be sent to the project users through an email notification.</p> <p>For example: Source and target have identical columns, hence they can be mapped using auto-map technique.</p> <p>For more information on configuring notifications, refer to the Configuring Notifications topic.</p>

5. Click **Finish** or **Proceed with Auto Map**.

When you click Finish, a map is created and saved in the mappings tree. You can create a mapping specification under the map using [drag and drop method](#) or [graphical design](#).



When you click Proceed with Auto Map, you can [create mapping specification using auto-map technique](#).

Create New Mapping Wizard

2. Auto Map Source & Target Objects

Mapping Groups

Add Group Delete Group

View All

Group 1

Target Object(s)

Source Object(s)

Auto Mapping Preview Grid

#	Target System	Target Environmen	Target Object	Target Attribute	Source Attribute	Source Object	Source Environmen	Source System

Total Rows: 0 | Target Tables: 0 | Source Tables: 0 | Targets Not Mapped: 0 | Sources Not Mapped: 0

Create a distinct Mapping for every Group

Back Finish Cancel

- Metadata
 - 3rd Party Flat Files
 - 3rd Party Flat Files
 - A_System
 - A_Environment
 - AdventureWorks
 - AdventureWorks_Staging
 - AdventureWorks
 - AMERISURE
 - FDBSample
 - Atlas Sales System
 - Atlas Sales System
 - BI
 - Microstrategy
 - BO Reports
 - BO Reports
 - Customer Excellence Report
 - Customer Order Entry
 - COE
 - Data Lake
 - Cloudera HDFS
 - Twitter Feeds
 - Data Models
 - DMLDW

Drag and Drop


You can map source metadata with target metadata and create mapping specifications using the drag and drop method. This method is useful even when source column names are different from target column names. After mapping source to target, you can set the target update strategy and enter a description about the strategy.

Creating Mapping Specifications

To create mapping specifications using drag and drop method, follow these steps:

1. In the **Workspace Mappings** pane, click a map.

By default, the Mapping Specification tab opens.



The screenshot shows the 'Mapping Specification' tab in a software application. The interface includes a toolbar with icons for integration, profiles, and settings. A dropdown menu shows 'Profile_ABC'. Below the toolbar is a table with the following columns:

#	Target System Name	Target Environment Name	Target Table Name	Target Column Name	Target Column Data Type	Target Column Length	Target Column Precision	Target Colour Scale

2. Click .


You can now edit the Mapping Specification grid.

3. Drag source table or column from the **Metadata Catalogue** pane and drop in the **Mapping Specification** grid.

Ensure that you drop source tables or columns under the respective columns.



You cannot drop source systems or environments in the Mapping Specification grid.



4. Drag target table or column from the **Metadata Catalogue** pane and drop in the **Mapping Specification** grid.

Ensure that you drop target tables or columns under the respective columns.



You cannot drop target systems or environments in the Mapping Specification grid.

5. Click .

The mapping specification is saved.


Setting Target Update Strategy

To set the target update strategy, follow these steps:

1. Expand the **Additional Mapping Information** pane.

This pane is available at bottom of the central pane when you click a map in the Workspace Mappings pane.

2. Click the **Target Update Strategy** tab.



3. Click .

4. Click the required strategy, enter **Update Strategy Description**, and click .

The target update strategy is set.

You can enrich a mapping specification by:

- [Adding transformation and lookup details](#)
- [Associating code cross walks \(code mappings\)](#)
- [Associating reference tables](#)
- [Linking requirements](#)

After creating a mapping specification, you can analyze a mapping specification. [Analyzing mapping specifications](#) involves:

- Generating virtual preview of target
- Previewing data
- Performing table gap analysis
- Performing column gap analysis
- Running impact analysis
- Running lineage analysis
- Running end to end lineage

- Opening business view
- Viewing mapping statistics

Graphical

You can use the Graphical Designer tab to map source metadata with target metadata and create mapping specifications. This method is useful even when source column names are different from target column names.


After mapping source to target, you can set the target update strategy and enter a description about the strategy.

Creating Mapping Specifications

To create mapping specifications graphically, follow these steps:


1. In the **Workspace Mappings** pane, click a map.

By default, the Mapping Specification tab opens.




2. Click the **Graphical Designer** tab.

The following page appears.




3. Click .

4. Drag source table from the **Metadata Catalogue** pane and drop on the **Graphical Designer** tab.
5. On the **Graphical Designer** tab, click the source table and specify it **As Source**.




6. Drag target table from the **Metadata Catalogue** pane and drop on the **Graphical Designer** tab.
7. On the **Graphical Designer** tab, click the target table and specify it **As Target**.



8. Use the following options to map source with target:


- If the source and target have same column names, click **Auto Map**.

The source and target columns are mapped.



- If the source and target have different column names, then drag your mouse from a source column to the required target column.

The source and target columns are mapped.



9. Click .

The mapping specification is saved.


Setting Target Update Strategy

To set the target update strategy, follow these steps:

1. Expand the **Additional Mapping Information** pane.

This pane is available at bottom of the central pane when you click a map in the Work-space Mappings pane.

2. Click the **Target Update Strategy** tab.



3. Click .

4. Click the required strategy, enter **Update Strategy Description**, and click .

The target update strategy is set for the mapping specification.

You can enrich a mapping specification by:

- [Adding transformation and lookup details](#)
- [Associating code cross walks \(code mappings\)](#)
- [Associating reference tables](#)
- [Linking requirements](#)

After creating a mapping specification, you can analyze a mapping specification. [Analyzing mapping specifications](#) involves:

- Generating virtual preview of target
- Previewing data

- Performing table gap analysis
- Performing column gap analysis
- Running impact analysis
- Running lineage analysis
- Running end to end lineage
- Opening business view
- Viewing mapping statistics

Auto-Map


You can create a map and proceed with auto-map to create a mapping specification when source column names and target column names are same. For more information about creating maps, refer to the [Creating Maps](#) topic.

After creating a mapping specification, you can set the target update strategy and enter a description about the strategy.


Creating Mapping Specifications

To create mapping specifications using auto-map, follow these steps:

1. On the **Creating New Mapping Wizard** page, drag the target table from the **Metadata** pane and drop it in the **Target Object(s)** box.




2. Drag source table from the **Metadata** pane and drop it in the **Source Object(s)** box.



3. Click .

The source columns are mapped with the target columns under a mapping group with the target table name. The mappings can be previewed in the Auto Mapping Preview Grid, which gives information about the target and source tables.



Use the following options to manage the auto-map:

Maximize (🔍)

Use this option to maximize or minimize the Auto Mapping Preview Grid.

Delete Orphan Sources (👉)

Use this option to delete source attributes that are not mapped.

Delete Orphan Targets (👉)

Use this option to delete target attributes that are not mapped.

Add Transformations (🔗)

Use this option to [add transformations](#) for the auto map. You can add business rule, extended business rule transformation, look up reference column, lookup on, and trans look up condition.

Add Group

Use this option to add a mapping group to perform other mappings.

Rename Mapping Group (🔁)

Use this option to rename a mapping group.

Delete Group

Use this option to delete a mapping group. To delete a mapping group, click the mapping group and then click **Delete Group**.

Create a distinct Mapping for every Group

Use this option to create distinct mapping for every group.

4. Click Finish.

A new map is created and saved under the Mappings tree. All the auto-maps in the multiple mapping groups appear in the same sequence in the Mapping Specification grid.

#	Source System Name	Source Environment Name	Source Table Name	Source Column Name	Source Column Data Type	Source Column Length	Business Rule
1	Erwin_Sales_Target	Integration_Target	dbo.RM_RESOURCE	RESOURCENAME_New	varchar	100	TRUNC
2	Erwin_Sales_Target	Integration_Target	dbo.RM_RESOURCE	RESOURCEID_New	int	4	TRUNC
3	Erwin_Sales_Target	Integration_Target	dbo.RM_RESOURCE	RESOURCEEMAIL_New	varchar	50	TRUNC
4	Erwin_Sales_Target	Integration_Target	dbo.RM_RESOURCE	RESOURCECELLPHONE_New	varchar	15	TRUNC
5	Erwin_Sales_Target	Integration_Target	dbo.RM_RESOURCE	RESOURCEDESC_New	varchar	150	TRUNC

Setting Target Update Strategy

To specify target update strategy, follow these steps:

1. Expand the **Additional Mapping Information** pane.

This pane is available at bottom of the central pane when you click a map in the Workspace Mappings pane.

2. Click the **Target Update Strategy** tab.

The screenshot shows the 'Additional Mapping Information' pane expanded at the bottom of the Mapping Specification window. The 'Target Update Strategy' tab is selected, and the 'Update Strategy Description' field is visible. The list of update strategies includes:

- Unspecified
- Insert else Update
- Update else Insert
- Insert

3. Click .

4. Click the required strategy, enter **Update Strategy Description**, and click .

The target update strategy is set.


Adding Transformations

You can add transformations to an auto-map and specify whether it is applicable to exact match, orphan source, orphan target, or all the rows.

To add transformations in auto-maps, follow these steps:

1. Under the **Auto Mapping Preview Grid** section, click .

The Auto Map Transformation page appears.




2. Click .

A row is added to the grid.

3. Double-click the cell under the **Key** column and select the required transformation.
4. Double-click the cell under the **Value** column and select the value.



You can use transformations created under the Transformations node only for Business Rule. For other transformations, enter the required value.



5. Use the following options:

Exact Match

Use this option to apply the transformation on the exactly matched rows in the Auto Mapping Preview Grid.

Orphan Source

Use this option to apply the transformation on the orphan source rows in the Auto Mapping Preview Grid.

Orphan Target

Use this option to apply the transformation on the orphan target rows in the Auto Mapping Preview Grid.

All

Use this option to apply the transformation on every row in the Auto Mapping Preview Grid.

6. Click .

The transformations are added to the auto map.

You can enrich a mapping specification by:

- [Adding transformation and lookup details](#)
- [Associating code cross walks \(code mappings\)](#)
- [Associating reference tables](#)
- [Linking requirements](#)

After creating a mapping specification, you can analyze a mapping specification. [Analyzing mapping specifications](#) involves:

- Generating virtual preview of target
- Previewing data
- Performing table gap analysis
- Performing column gap analysis
- Running impact analysis
- Running lineage analysis

- Running end to end lineage
- Opening business view
- Viewing mapping statistics

One to Many and Many to Many Mapping Specifications


You can map multiple source columns to a single or multiple target columns to create a mapping specification. After creating the mapping specification, you can set the target update strategy and enter a description about the strategy.

Creating Mapping Specifications

To create one to many or many to many mapping specifications, follow these steps:

1. In the **Workspace Mappings** pane, click a map.

By default, the Mapping Specification tab opens.




2. Click .

3. Switch  to **ON**.

The append mode is enabled. You can now drop multiple columns from the Metadata Catalogue pane in one row of the Mapping Specification grid.

4. Drag one or multiple source columns from the **Metadata Catalogue** pane in the **Mapping Specification** grid under the **Source Columns Name** column.


You can use Ctrl key to select multiple columns in the Metadata Catalogue pane.



5. Drag single or multiple target columns from **Metadata Catalogue** in **Mapping Specification** under the **Target Columns Name**.
6. Click .

The mapping specification is saved.


You can view the mapping specification on the **Graphical Designer** tab to view the graphical representation of the many to one mappings.



Setting Target Update Strategy

To set target update strategy, follow these steps:

1. Expand the **Additional Mapping Information** pane and click the **Target Update Strategy** tab.
2. On the **Target Update Strategy** tab, click .



3. Click the required strategy, enter **Update Strategy Description**, and click .

4. Click .

The source to target mapping is saved.

You can enrich a mapping specification by:

- [Adding transformation and lookup details](#)
- [Associating code cross walks \(code mappings\)](#)
- [Associating reference tables](#)
- [Linking requirements](#)

After creating a mapping specification, you can analyze a mapping specification. [Analyzing mapping specifications](#) involves:

- Generating virtual preview of target
- Previewing data
- Performing table gap analysis
- Performing column gap analysis
- Running impact analysis

- Running lineage analysis
- Running end to end lineage
- Opening business view
- Viewing mapping statistics

Adding Transformation and Lookup Details

You can add transformation and lookup details to a mapping specification in the Mapping Specification grid.

Adding transformation details involves setting up:

- Business rule
- Extended business rule transformation

Ensure that you define business rules under the Transformations node for the same ETL Option as the Project ETL. For more information on defining business rules, refer to the [Defining Transformations](#) section.

Adding lookup details involves setting up:

- Trans lookup condition
- Lookup reference column
- Lookup on

Ensure that you scan the required table in the Metadata Manager to set trans lookup condition.

Adding Transformation Details

To add business rules to mapping specifications, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, click a map.

By default, it opens the Mapping Specification tab.

#	Target System Name	Target Environment Name	Target Table Name	Target Column Name	Target Column Data Type	Target Column Length	Target Column Precision	Target Colour Scale
1	Erwin_Sales_Targe	Integration_Targe	dbo.RM_RESOURC	RESOURCEID_New	int	4	10	0
2	Erwin_Sales_Targe	Integration_Targe	dbo.RM_RESOURC	RESOURCENAME	varchar	100	0	0
3	Erwin_Sales_Targe	Integration_Targe	dbo.RM_RESOURC	RESOURCEDESC_N	varchar	150	0	0

3. Right-click the header menu of the **Mapping Specification** grid.

#	Source System Name	Source Environment Name	Source Table Name	Source Column Name	Source Column Data Type	Source Column Length	Business Rule
1	Erwin_Sales	Integration	dbo.RM_RESOURC	RESOURCEID	int	4	
2	Erwin_Sales	Integration	dbo.RM_RESOURC	RESOURCENAME	varchar	100	
3	Erwin_Sales	Integration	dbo.RM_RESOURC	RESOURCEDESC	varchar	150	

4. Select the **Business Rule** check box.

The Business Rule column is now available in the Mapping Specification grid.

5. Click .

You can now edit the Mapping Specification grid.

6. Double-click the cell under the **Business rule** column for the required source column.

The available transformations appear.

Segment	Source Table Name	Source Column Name	Source Column Data Type	Source Column Length	Business Rule	Extended Business Rule Transformation
Function	dbo.RM_RESOURCE	RESOURCEID	int	4		
Function	dbo.RM_RESOURCE	RESOURCENAME	varchar	100	1-DataGov(HighDate:12/31/9999) 2-DataGov(LowDate01/01/0001) 3-DataGov(AverageChurn) ABORT ABS ADD_TO_DATE	
Function	dbo.RM_RESOURCE	RESOURCEDESC	varchar	150		
Function	dbo.RM_RESOURCE	RESOURCECELLPH	varchar	15		

7. Select a business rule.

You can add business rules for multiple source columns.

8. Click .

The business rules are added to the mapping specification.

To add extended business rule transformations, follow these steps:

1. Right-click the header menu of the **Mapping Specification** grid.

#	Source System Name	Source Environment Name	Source Table Name	Source Column Name	Source Column Data Type	Source Column Length	Business Rule
1	Erwin_Sales	Integration	dbo.RM_RESOURCE	RESOURCEID			
2	Erwin_Sales	Integration	dbo.RM_RESOURCE	RESOURCENAME			
3	Erwin_Sales	Integration	dbo.RM_RESOURCE	RESOURCEDESC	varchar	150	

2. Select the **Extended Business Rule Transformation** check box.


The Extended Business Rule Transformation column is now available in the Mapping Specification grid.

3. Click .

You can now edit the Mapping Specification grid.


4. Click .

The available options appear.




5. Select the **Extended Business Rule** check box.
6. In the **Mapping Specification** grid, double-click the cell under the **Extended Business rule Transformation** column for the required source column.

The Extended Transformation Rule Editor page appears.




7. Select a pseudocode based on the Project ETL.
For example, if the Project ETL is Informatica then select Informatica Pseudocode.



8. Press Ctrl + Space keys.

The available transformations appear.



If the required transformation is not available in the list, use  to create and update the transformations list.

9. Double-click the required transformation.

You can use  to replace the transformation name with the pseudocode.

10. Click .


The extended business rule transformation is added to the source column. You can add extended business rule transformation to multiple source columns. You can also

configure UI labels for user defined fields. For more information on configuring UI labels, refer to the [Configuring Language Settings](#) topic.


Adding Lookup Details

To add lookup details in mapping specifications, follow these steps:

1. Right-click the header menu of the mapping specification grid.
2. Select **Lookup Reference Column**, **Lookup On**, and **Trans Lookup Condition**.



3. Drag the required table from the **Metadata Catalogue** pane and drop it under the **Trans Lookup Condition** column for the required source column.



A SQL query populates.

Once trans lookup condition is set for the source column, you can add lookup reference column and lookup on.

To add lookup reference column, double-click the cell under the **Lookup Reference Column** column and select the required option.

The screenshot shows a table with the following columns: Created By, Created Date, Lookup Reference Column, Lookup On, Trans Lookup Condition, Last Modified By, and Last Modified Date. The 'Lookup Reference Column' dropdown menu is open, showing options: ID, SOURCE_OBJECT_ID, SOURCE_OBJECT_TYPE_ID, TARGET_OBJECT_ID, TARGET_OBJECT_TYPE_ID, and RELATIONSHIP_DETAIL_ID. The 'Trans Lookup Condition' column contains a SQL query: SELECT ID, SOURCE_OBJECT_ID, SOURCE_OBJECT_TYPE_ID, TARGET_OBJECT_ID, TARGET_OBJECT_TYPE_ID, RELATIONSHIP_DETAIL_ID FROM dbo.ADS_ASSOCIATION.

Created By	Created Date	Lookup Reference Column	Lookup On	Trans Lookup Condition	Last Modified By	Last Modified Date
Administrator	2020-01-12 20:40:27.5			SELECT ID, SOURCE_OBJECT_ID, SOURCE_OBJECT_TYPE_ID, TARGET_OBJECT_ID, TARGET_OBJECT_TYPE_ID, RELATIONSHIP_DETAIL_ID FROM dbo.ADS_ASSOCIATION	Administrator	2020-01-12 20:40:27.5
Administrator	2020-01-12 20:40:27.5	ID			Administrator	2020-01-12 20:40:27.5
Administrator	2020-01-12 20:40:27.5				Administrator	2020-01-12 20:40:27.5

To add lookup on, double-click the cell under the **Lookup On** column and select the required option.

The screenshot shows the same table as above, but now the 'Lookup On' dropdown menu is open, showing options: ID, SOURCE_OBJECT_ID, SOURCE_OBJECT_TYPE_ID, TARGET_OBJECT_ID, TARGET_OBJECT_TYPE_ID, and RELATIONSHIP_DETAIL_ID. The 'Lookup Reference Column' column now contains the value 'ID'.

Created By	Created Date	Lookup Reference Column	Lookup On	Trans Lookup Condition	Last Modified By	Last Modified Date
Administrator	2020-01-12 20:40:27.5	ID		SELECT ID, SOURCE_OBJECT_ID, SOURCE_OBJECT_TYPE_ID, TARGET_OBJECT_ID, TARGET_OBJECT_TYPE_ID, RELATIONSHIP_DETAIL_ID FROM dbo.ADS_ASSOCIATION	Administrator	2020-01-12 20:40:27.5
Administrator	2020-01-12 20:40:27.5		ID		Administrator	2020-01-12 20:40:27.5
Administrator	2020-01-12 20:40:27.5				Administrator	2020-01-12 20:40:27.5

4. Click .

The lookup details are added in the Mapping Specification. You can add lookup details for multiple source columns.

Alternately, you can add transformation and lookup details to a mapping specification graphically. For more information about adding transformation and lookup details graphically, refer to the [Graphical Designer](#) topic.

Graphical Designer

You can add transformation and lookup details to a mapping specification on the Graphical Designer tab.

Adding transformation details involves setting up:

- Business rule
- Extended business rule transformation

Ensure that you define business rules under the Transformations node for the same ETL Option as the Project ETL. For more information on defining business rules, refer to the [Defining Transformations](#) section.

Adding lookup details involves setting up:

- Trans lookup condition
- Lookup reference column
- Lookup on

Ensure that you scan the required table in the Metadata Manager to set trans lookup condition.


Adding Transformation Details

To add business rules graphically, follow these steps:

1. Click the **Graphical Designer** tab.
2. Click .

You can now edit the mapping specification graphically.

3. Click the mapping link of the required column and expand the **Properties** pane.
4. Expand the **Transformation Details** pane.



5. Double-click the **Value** cell for **Business Rule** and select the required value.


6. Click .

The business rule is added to the mapping link. You can add business rules for multiple mapping links.

To add extended business rule transformations graphically, follow these steps:


1. On the **Graphical Designer** tab, Click .

The available options appear.




2. Select the **Extended Business Rule** check box.

3. Click the mapping link of the required column and expand the **Transformation Details** pane.




4. Double-click the **Value** cell for **Extended Business Rule Transformation**.

The Extended Transformation Rule Editor page appears.




5. Select the pseudocode based on the Project ETL.

For example, if the Project ETL is Informatica then select Informatica Pseudocode.



6. Press Ctrl + Space keys.

The available transformations appear.



If the required transformation is not available in the list, use  to create and update the transformations list.

7. Double-click the required transformation.

You can use  to replace transformation name with pseudocode.


8. Click .

The extended business rule transformation is added to the mapping link. You can add extended business rule transformations to multiple mapping links.


Adding Lookup Details

To add lookup details graphically, follow these steps:

1. On the **Graphical Designer** tab, click the mapping link of the required column and expand the **Properties** pane.
2. Expand the **Lookup Details** pane.




3. Drag the required table from the **Metadata Catalogue** pane and drop it for **Trans Lookup Condition**.



Once trans lookup condition is set, you can add lookup reference column and lookup on.

To add lookup reference column, double-click the cell for **Lookup Reference Column** and select the required option.



To add lookup on, double-click the cell against **Lookup On** and select the required option.

4. Click .

The lookup details are added to the mapping specification. You can add lookup details for multiple mapping links.


Updating Mapping Specifications Manually

After creating a mapping specification, you can update the mapping specification manually. However, we recommend that you use the manual method case by case on exception basis.

To update mapping specifications manually, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, click a map.

By default, it opens the Mapping Specification tab.



The screenshot shows the 'Mapping Specification' tab in the software interface. On the left is a 'Workspace Mappings' tree view with a tree icon and a plus sign. The tree contains 'Mappings' (with a plus sign), 'Transformations' (with a plus sign), 'Projects' (with a plus sign), 'Carrefour (9)', 'Data Lake Migration (3)', 'EDW (3)', 'ERP (2)', 'Erwin_Project (4)', 'Erwin_Sales (1)', 'Transformations' (with a plus sign), 'Test Cases' (with a plus sign), 'Mappings' (with a plus sign), 'Integration' (with a plus sign), 'MappingTargets' (with a plus sign), 'Exeter (2)', and 'IQVIA (1)'. The 'Integration' folder is selected. The main area shows a table with the following data:

#	Target System Name	Target Environment Name	Target Table Name	Target Column Name	Target Column Data Type	Target Column Length	Target Column Precision	Target Colour Scale
1	Erwin_Sales_Target	Integration_Target	dbo.RM_RESOURCE	RESOURCEID_New	int	4	10	0
2	Erwin_Sales_Target	Integration_Target	dbo.RM_RESOURCE	RESOURCENAME_	varchar	100	0	0
3	Erwin_Sales_Target	Integration_Target	dbo.RM_RESOURCE	RESOURCEDESC_	varchar	150	0	0

3. Click .

You can now edit the Mapping Specification grid.

4. Select a row (use Ctrl key to select multiple rows) and right-click the cell.

#	Target System Name	Target Environment Name	Target Table Name	Target Column Name	Target Column Data Type	Target Column Length	Target Column Precision	Target Column Scale
1	Erwin_Sales_Targe	Integration_Targe	dbo.RM_RESOURC	RESOURCEID_New	int	4	10	0
2	Erwin_Sales_Targe	Integration_Targe	dbo.RM_RESOURC	RESOURCENAME_	varchar	100		
3	Erwin_Sales_Targe	Integration_Targe	dbo.RM_RESOURC	RESOURCEDESC_N	varchar	150		

5. Use the following options:

Check All Rows

Use this option to select the check boxes under the Status column for the selected rows.



Right-click the header menu of the mapping specification grid and select the **Status** check box, to make Status column visible in the mapping specification grid.

Uncheck All Rows

Use this option to unselect the check boxes under the Status column for the selected rows.

Clear Source Details

Use this option to clear source details in the mapping specification grid.

Clear Target Details

Use this option to clear target details in the mapping specification grid.

Clear Source & Target Details

Use this option to clear source and target details in the mapping specification grid.

Clear Cell

Use this option to clear the cell.

Delete Row(s)

Use this option to delete the selected rows.

Extended Properties

Use this option to configure Extended Properties.

Share Link

Use this option to copy or share the URL of the mapping specification.

To update cell values, double-click a cell and update its values.


#	Target System Name	Target Environment Name	Target Table Name	Target Column Name	Target Column Data Type	Target Column Length	Target Column Precision	Target Column Scale
1	Erwin_Sales_Targe	Integration_Targe	dbo.RM_RESOURCE	RESOURCEID_New	int	4	10	0
2	Erwin_Sales_Targe	Integration_Targe	dbo.RM_RESOURCE	RESOURCENAME	varchar	4		
3	Erwin_Sales_Targe	Integration_Targe	dbo.RM_RESOURCE	RESOURCEDESC	varchar			

Uploading Mapping Specifications in XML

You can upload a mapping specification to a project in the XML format. You can either use an existing XML file or export it from a suitable project. Ensure that the XML file follows the correct template. For more information on exporting a mapping specification in XML, refer to the [Proprietary XML Format](#) topic.


To upload mapping specifications in the XML format, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, right-click a project.




3. Click **Upload XML**.

The Upload Mapping Manager XML page appears.



4. Drag and drop or use  to browse and select the XML file.
The Upload Mapping Manager XML page appears.



5. Enter **Mail Comments** and click .

The Mapping Specification is uploaded successfully.

If you have enabled notifications, project users receive notification emails and mail comments from the administrator's email ID. For more information on configuring notifications, refer to the [Configuring Notifications](#) topic.


Specifying XPath in Mapping Specifications

Xpath is a potential path expression in XML documents. Hence, if you have imported source or target metadata from XSD files then it is important to specify Xpath. You can specify Xpath in a mapping specification for source and target columns.

To specify Xpath in mapping specifications, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, click a map.

By default, it opens the Mapping Specification tab.



Target System Name	Target Environment Name	Target Table Name	Target Column Name	Target Column Data Type	Target Column Length	Created By	Created Date	Last
ool_Integrator	Integration_Projec	class	section	NCName		Administrator	2020-01-30 19:43:18.087	Admi
ool_Integrator	Integration_Projec	class	name	NCName		Administrator	2020-01-30 19:43:18.087	Admi

3. Right-click the header menu and select the **Target XPath** and **Source XPath** check boxes.

Target System Name	Target Environment Name	Target Table Name	Target Column Name	Target Column Data Type	Target Column	Target Column	Created By	Created Date	Target
ool_Integrator	Integration_Projec	class	section	NCName				2020-01-30 19:43:18.087	./clas
ool_Integrator	Integration_Projec	class	name	NCName				2020-01-30 19:43:18.087	./clas
ool_Integrator	Integration_Projec	student	name	string			Administrator	2020-01-30 19:44:33.49	./stuc
ool_Integrator	Integration_Projec	student	age	integer			Administrator	2020-01-30 19:44:33.49	./stuc

The Target XPath and Source XPath columns are now visible in the Mapping Specification grid.

4. Click .
5. Double-click cells under the **Target XPath** and **Source XPath** columns to enter the required XPath.
6. Click .

The Xpath is specified in the Mapping Specification.

Mapping Specification							
Graphical Designer		Test Specification		Workflow Log			
[School]				Profiles: Default			
Target Column Length	Created By	Created Date	Target XPath	Source XPath	Last Modified By	Last Modified Date Time	Reference Table
	Administrator	2020-01-30 19:43:18.087	./class/section	./class/section	Administrator	2020-01-30 19:57:40.59	
	Administrator	2020-01-30 19:43:18.087	./class/@name	./class/@name	Administrator	2020-01-30 19:44:33.49	
	Administrator	2020-01-30 19:44:33.49	./student/name	./student/name	Administrator	2020-01-30 19:44:33.49	
	Administrator	2020-01-30 19:44:33.49	./student/age	./student/age	Administrator	2020-01-30 19:57:40.59	

Setting Column Order and Visibility


You can set the column order and visibility in Mapping Specifications and personalize the Mapping Specification grid. This helps you work efficiently.

Column Order

To set the column order in mapping specifications, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, click a map.

By default, the Mapping Specification tab opens.



#	Source System Name	Source Environment Name	Source Table Name	Source Column Name	Source Column Data Type	Source Column Length	Business Rule
1	erwinDIS	erwinDIS	dbo.ADS_ASSOCI	ID	bigint	8	ABS
2	erwinDIS	erwinDIS	dbo.ADS_ASSOCI	SOURCE_OBJECT_	bigint	8	ABS
3	erwinDIS	erwinDIS	dbo.ADS_ASSOCI	SOURCE_OBJECT_	bigint	8	ABS

3. Click the required column header, drag and drop the column at the required place.

The Mapping Specifications can be exported with the new column order.




Column ordering in Mapping Specifications are not saved and gets reset.

Column Visibility

To set the column visibility, follow these steps:

1. In the **Mapping Specification** grid, click .

The Header Menu page appears.



2. Expand the respective nodes.
3. Select the required columns.



4. Close the **Header Menu** page.

The selected columns are visible in the Mapping Specification grid.

To reset column ordering and visibility click .

Updating Additional Mapping Information

You can update additional mapping information in the Additional Mapping Information pane with respect to the following tabs:


Tab	Description
Map Spec Overview	Under this, you can update the following for a mapping specification: <ul style="list-style-type: none"> ▪ Specification name ▪ Version label ▪ State name and sub-state name ▪ Source and target metadata sync ▪ Job Name XRef
Source Extract SQL	Under this, you can update: <ul style="list-style-type: none"> ▪ SQL Query relevant to a mapping specification ▪ SQL Query Description
Target Update Strategy	Under this, you can set your target update strategy as per your data integration requirements.
Testing Notes	Under this, you can add relevant testing notes with respect to a mapping specification.
Map Specs Docs	Under this, you can upload relevant documents.
Assignment	Under this, you can assign a mapping specification to multiple users.
Specification Artifacts	Under this, you can link additional specification artifacts relevant to a mapping specification.
Level of Effort	Under this, you can record planned level of effort and actual level of effort in creating mapping and ETL process.
Change Log	This tab can be enabled in Mapping Manager Settings . Under this, you can capture change logs of a mapping specification.
Release Information	Under this, you can view release information of a mapping.
Collaboration	Under this, you can collaborate with other users on a topic.

Tab	Description
Center	
User Defined Tabs (1-5)	There are five user defined tabs that can be used by you with your own UI labels .
Extended Properties	Under this, you can extend properties of a mapping specification by creating custom forms.

To access the Additional Mapping Information pane, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, click a map.

The central pane displays the Mapping Specification grid. The Additional Mapping Information pane is available at the bottom of the central pane.



3. Click the **Additional Mapping Information** pane.

You can use ◀ or ▶ to navigate across the pane.

Mapping Specification Graphical Designer Test Specification Workflow Log

[Erwin_Map] Profiles: Default

Source System Source Table Source Column Source Column Source Column Business Rule

Records from 1 to 6 Page 1 100 rows per page

Additional Mapping Information

Map Spec Overview Source Extract SQL Target Update Strategy Testing Notes Map Spec Docs Assignment Specification

Map Id: 237 Workflow Status: Draft

Specification Name: Erwin_Map

Map Specification Version: 1.05

Version Label: Data_Migration

State Name: In Progress Sub State Name:

Sync Source Metadata: OFF Sync Target Metadata: OFF

Job Name XRef:

Mapping Description: mapping description

Updating Map Spec Overview

You can update the Map Spec Overview tab and update various aspects of a mapping specification that includes:

- Specification name and its description
- Version label
- Mapping states and sub-states
- Syncing metadata with a mapping specification
- Job name XRef

To update the Map Spec Overview tab, follow these steps:

1. In the **Additional Mapping Information** pane, on the **Map Spec Overview** tab, click



The screenshot shows the 'Additional Mapping Information' pane with the 'Map Spec Overview' tab selected. The form contains the following fields and controls:

- Map Id:** Text input field containing '72'.
- Workflow Status:** Text input field containing 'Preliminary Draft'.
- Specification Name:** Text input field containing 'erwinSalesIntegration'.
- Map Specification Version:** Text input field containing '1.00'.
- Version Label:** Text input field.
- State Name:** Dropdown menu with 'In Progress' selected.
- Sub State Name:** Dropdown menu with 'Select' selected.
- Sync Source Metadata:** Toggle switch set to 'ON'.
- Sync Target Metadata:** Toggle switch set to 'ON'.
- Job Name XRef:** Text input field.
- Mapping Description:** Rich text editor with a toolbar containing icons for Home, Bold, Italic, Underline, Bulleted List, Numbered List, Indent, Outdent, Link, Unlink, and Undo.
- Assigned To:** Text input field.

2. Select or enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.

Field Name	Description
Specification Name	Specifies the mapping specification name. For example, EDW_PROD_IDS_Benefits_Detail. For more information on naming conventions, refer to the Best Practices section.
Version Label	Specifies the version label of the mapping specification. For example, EDW_PROD_IDS_Benefits_Detail (Alpha). For more information on configuring version display of maps, refer to the Configuring Version Display topic.
State Name	Specifies the mapping state of the mapping specification. For example, In Progress. For more information on configuring mapping states, refer to the Configuring Mapping State Settings topic.
Sub State Name	Specifies the sub-state of the mapping specification. For example, Needs Approval. For more information on configuring mapping sub-states, refer to the Configuring Mapping State Settings topic.
Sync Source Metadata	Switch Sync Source Metadata to ON to sync source metadata with the mapping specification.
Sync Target Metadata	Switch Sync Target Metadata to ON to sync target metadata with the mapping specification.
Job Name XRef	Specifies the equivalent ETL mapping name. For example, ErwinDIS931.
Description	Specifies the description for the mapping specification. For example: This is a map between EDW source and IDS target systems.



You cannot edit Map Id, Workflow Status, and Map Specification Version.

For more information on workflow status, refer to the [Managing Mapping Manager Workflows](#) topic.

3. Click .

The fields on the Map Spec Overview tab are updated.


Updating Source Extract SQL

You can keep a record of multiple source extract SQL and its description. You can also update it as per your requirements.


To update source extract SQL, follow these steps:

1. In the **Additional Mapping Information** pane, click the **Source Extract SQL** tab.

The Source Extract SQL tab appears.



2. click .



3. Enter **SQL Query** and **SQL Query Description**.

For example:

- **SQL Query:** Select * from dbo.RM_Resource
- **SQL Query Description:** - The query extracts the data from dbo.RM_Resource table.

4. Click .


The Source Extract SQL is updated.

Setting Target Update Strategy


You can set the way target metadata is updated when you map source to target. You can update the strategy any time as per your requirement.

To set target update strategy, follow these steps:

1. In the **Additional Mapping Information** pane, click the **Target Update Strategy** tab.



2. Click .



3. Click the appropriate update strategy from the options and enter **Update Strategy Description**.

For example:

- **Update strategy:** Insert else Update
- **Update Strategy Description:** Insert the source column value to a blank target column else update the target column value with the source column value.

4. Click .

The Target Update Strategy is set.


Updating Testing Notes

You can keep a record of testing notes related to a mapping specification and specify test results as:


- Un-specified
- Pass
- Fail
- Needs analysis

To update testing notes, follow these steps:

1. In the **Additional Mapping Information** pane, click the **Testing Notes** tab.



2. Click .



3. Click the appropriate option for test results and enter **Testing Notes**.

For example:

- **Test results:** Pass
- **Testing Notes:** The mapping specification passed the testing and it is ready for the ETL process.

4. Click .


The Testing Notes are updated.

Adding Mapping Specification Documents


You can add supporting documents, such as text files, audio files, video files, document links, and so on to a mapping specification.

To upload mapping specification documents, follow these steps:

1. In the **Additional Mapping Information** pane, click the **Map Spec Docs** tab.



2. Click .



3. Enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.

Field Name	Description
Document Name	Specifies the name of the physical document being attached to the mapping specification. For example, Mapping Details.
Document Object	Drag and drop document files or use  to select and upload document files.
Document Owner	Specifies the document owner's name. For example, John Doe.
Document Link	Specifies the URL of the document. For example, https://drive.google.com/file/d/1/2sC2_SZlYeFKI700n-b5YkMBq4ptA7jhg5/view
Description	Specifies the description of the document. For example: The document has information about the mapping details.
Approval Required Flag	Specifies whether the document requires approval. Select the Approval Required Flag check box to select the document status.
Document Status	Specifies the status of the document. For example, In Progress. Select the status of the document from the drop down. This field is available only when the Approval Required Flag check box is selected.

4. Click .

The mapping specification document is added.

3. Enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.

Field Name	Description
Mapping Designer	Specifies the User Full Name and User ID of the Mapping Designer. For example, Jane Doe(janedoe).
Mapping Approver	Specifies the User Full Name and User ID of the Mapping Approver. For example, John Doe(jdoe).
Mapping ETL Developer	Specifies the User Full Name and User ID of the Mapping ETL Developer. For example, John Denver(jdenver).
Mapping Tester	Specifies the User Full Name and User ID of the Mapping Tester. For example, Michael Samuel(M.Samuel).
Status	Specifies the status of the user's task. For example, Pending Review.
Email	The Email check boxes populate as you select corresponding users. Select the check boxes to send email notifications to the corresponding users about the mapping assignment and change in map-

Field Name	Description
	ping status. For more information on configuring email notifications, refer to the Configuring Notifications topic.
Distribution/CC List	Enter a comma-separated list of email IDs that should receive the email notification about the assignment. For example, ab.dav@xyz.com, cal.kai@xyz.com The email notification is sent from the administrator's email ID .
Custom Notes	Specifies custom notes about the mapping assignment. For example: John Denver is the Mapping ETL Developer of the mapping specification.
Assignment Changes	Specifies the changes in the mapping assignment. The information in this field is system-generated. For example: User Administrator - Default System User(Administrator) has been assigned to the mapping on 2020-01-12 19:58:15.815.

4. Click .


The mapping specification is assigned to the users.

Linking Additional Specification Artifacts


The Requirements Manager captures functional requirements of a data integration project using Specification Artifacts. You can link these specification artifacts with mapping specifications.

To link specification artifacts with mapping specifications, follow these steps:


1. In the **Additional Information** pane, click the **Specification Artifacts** tab.



2. Click .



3. In the right pane, expand the **Specification Artifact Catalogue** pane and drag and drop the required specification under the **Specification Artifacts** tab.



4. Click .


The specification artifact is linked.

Recording Level of Effort

You can record and compare planned level of effort with the actual level effort spent on creating and managing mapping specifications.


To record the level of effort, follow these steps:

1. In the **Additional Mapping Information** pane, click the **Level of Effort** tab.



The screenshot shows the 'Additional Mapping Information' pane with the 'Level of Effort' tab selected. The pane is divided into two columns: 'Planned Level of Effort' and 'Actual Level of Effort'. Each column has input fields for 'Mapping Effort' and 'ETL Effort', both set to '0.0 Days'. Below the input fields are 'Notes' text areas. A pencil icon is visible in the top right corner of the 'Actual Level of Effort' section.

2. Click .



The screenshot shows the 'Additional Mapping Information' pane with the 'Level of Effort' tab selected. The pane is divided into two columns: 'Planned Level of Effort' and 'Actual Level of Effort'. Each column has input fields for 'Mapping Effort' and 'ETL Effort', both set to '0.0 Days'. Below the input fields are 'Notes' text areas with a rich text editor toolbar. A pencil icon is visible in the top right corner of the 'Actual Level of Effort' section.

3. Enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.

Field Name	Sub-Fields	Description
Planned Level of Effort	Mapping Effort	Specifies the planned mapping effort in days. For example, 11.5 days.
	ETL Effort	Specifies the planned ETL effort in days. For example, 10.5 days.
	Notes	Specifies notes about the planned level of effort. For example: Planned level of effort took all the project requirements into account.
Actual Level of Effort	Mapping Effort	Specifies the actual mapping effort in days. For example, 11.0 days.
	ETL Effort	Enter the actual ETL effort in days. For example, 9.5 days.
	Notes	Specifies the notes about the actual level. For example: Actual level of effort were lesser than the planned level of effort.

4. Click .

The level of effort tab is recorded.

Viewing Change Logs

A change log is a record of changes made in a Mapping Specification grid. You can view these changes on the Change Log tab. By default, this tab is disabled. You can enable it under Change Log Settings. For more information, refer to the [Configuring Change Log Settings](#) topic.

To view the change logs of the mapping specifications, in the **Additional Information** pane, click the **Change Log** tab.

The change logs of the mapping specification appears.

The screenshot shows the Erwin Mapping Specification interface. The left sidebar displays a tree view of workspace mappings, including 'Erwin_Map'. The main area is titled 'Mapping Specification' and shows the 'Change Log' tab selected. The 'Additional Mapping Information' pane is open, displaying a table of change logs for the selected mapping specification.

#	Log Id	Changed Log Description	Map Version	Last Modified By	Last Modified Date Time
1	20	Version Label Modified.	1.05	Administrator	2019-11-21 19:28:03.0
2	21	Changed the Version Label	1.05	Administrator	2019-11-21 18:10:06.0
3	22	Sync Source Metadata was made ON	1.05	Administrator	2019-11-21 16:45:37.0
4	23	Edited Mapping Specification Name.	1.05	Administrator	2019-11-21 15:59:27.0
5	24	Edited Specification Name.	1.05	Administrator	2019-11-21 15:58:11.0
6	25	Business rule was updated.	1.05	Administrator	2019-11-21 15:01:42.0

Viewing Release Information

The release, migration, and audit-related information of a mapping specification are available on the Release Information tab. For more information on releases, refer to the [Release Manager](#) section.

To view release information of mapping specifications, in the **Additional Mapping Information** pane, click the **Release Information** tab.

The release information of the mapping specification appears.


Additional Mapping Information							
Docs	Assignment	Specification Artifacts	Level of Effort	Change Log	Release Information	Collaboration Center	User Defined1
Release Details							
Release	Release_Name		Project	Project_Name			
Status	PENDING APPROVAL		Owner				
Migration Details							
From	DEV		To	TEST			
Live Date	11/29/2019 HH:MM AM/PM		Migration Date	11/29/2019 HH:MM AM/PM			
Audit Details							
Created By	Administrator		Created Date	11/29/2019			
Last Modified By	Administrator		Last Modified Date	11/29/2019			

Setting Up Collaborations

You can start discussions on mapping projects or a relevant topic with your team using the Collaboration Center. This enables you and your team to work together.


To set up collaborations, follow these steps:

1. In the **Additional Mapping Information** pane, click the **Collaboration Center** tab.



2. Click .

The Add Topic page appears.

A screenshot of a dialog box titled "Add Topic". The dialog has a title bar with a close button and a maximize button. Inside the dialog, there are two input fields: "Topic Name*" with an asterisk indicating it is required, and "Description:". The "Topic Name" field is a single-line text box, and the "Description" field is a larger multi-line text area. In the top right corner of the dialog, there are two icons: a right-pointing arrow and a save icon (a floppy disk).

3. Enter the **Topic Name** and **Description**.

4. Click .

The new topic is saved and added to the list of topics on the Collaboration Center tab.

You can manage a topic using the options available under Topic Options (). [Managing a topic](#) involves:

- Viewing, editing, or deleting a topic
- Assigning users
- Managing notifications
- Saving topic conversations
- Sharing a topic


Configuring Extended Properties

You can configure user-defined properties of a mapping specification under the **Extended Properties** tab.


First, you need to set up a form and then use it to configure the user-defined extended properties.

To configure extended properties of mapping specifications, follow these steps:

1. In the **Additional Mapping Information** pane, click the **Extended Properties** tab.




2. Click **Configure**.



The **Extended Properties Configuration** page contains the following sections:

- **Field Controls:** Use this pane to get the required UI elements.
- **Configure Form:** Use this pane to design forms using the UI elements available in the **Field Controls** pane.

- **Properties:** Use this pane to view the properties of the UI element selected in the **Configure Form** pane.
3. Click **Edit**. Then, double-click or drag and drop the required UI elements from the **Field Controls** pane to the **Configure Form** pane.
 4. Select UI elements, one at a time, and configure their properties in the **Properties** pane.



 The available properties differ based on the type of UI element.

Refer to the following table for property descriptions:

Property	Description
Published	Switch Published to ON to publish the field.
Field	Specifies the field label. To change the field labels, double-click the corresponding Value cell. For example, Mapping Specification Approved On.
Type	Specifies the type of the field. To select field types, double-click the corresponding Value cell.

Property	Description
	For example, Date Picker.
Dependencies	<p>Defines the pick list fields that can be used as controlling fields. It works only with the Reference Data Manager connector.</p> <p>To define pick list fields, select the fields from the drop down option.</p>
Configure Values	<p>Specifies the connectors for the field.</p> <p>To enter option values, click Configure Values.</p> <p>Use the following options:</p> <ul style="list-style-type: none"> ▪ Default connector: Use this option to enter option values manually or using an MS Excel file. ▪ Reference Data Manager: Use this option to pull option values from reference tables in the Reference Data Manager.
Mandatory	Specifies whether the field is mandatory.
Description	<p>Specifies the field description.</p> <p>To enter field descriptions, double-click the corresponding Value cell.</p>
Visible in Extended Properties	Switch Visible in Extended Properties to ON to make it visible on the Extended Properties tab.
Order	<p>Specifies the order of the field on the Extended Properties tab.</p> <p>To enter the order number, double-click the corresponding Value cell.</p> <p>You can also drag and move fields in the Configure Form pane to change its order.</p>

5. Click **Save**.

The form is saved and is available on the **Extended Properties** tab.

You can download extended properties in the XLSX format and use it as a template to [import extended properties](#). To download extended properties, on the **Extended Properties** tab, click **Export To Excel**.

Default Connector

When you configure extended properties using UI elements, such as combo box, radio button, and list, you also need to configure their option values. You can use the default connector to import option values from an MS Excel file or enter them manually.


To configure option values using the default connector, follow these steps:

1. In the **Configure Form** section, click the required UI element.

Ensure that you are in edit mode.


2. In the **Properties** section, click **Configure**.

The Connectors page appears.



3. On the **Connectors** page, ensure that the Default Connector option is selected. Then, click **Next**.

The <UI_Element> Options page appears. For example, if the UI element is Combo Box, the Combo Box Options page appears.



4. Use the following options:

Add

Use this option to enter text and value manually.

Import Excel


Use this option to import options from MS Excel files.

5. After configuring option values, click **Save**.

To add option values manually, follow these steps:


1. Click **Add**.
2. Enter values to the Text and Value fields.

The Text corresponds to options whereas the Value corresponds to underlying value of an option. You can add as many values as needed.



3. Click **Save**.


The option values appear in the UI element under the Configure Form section.



To import option values from MS Excel files, follow these steps:

1. Click **Import Excel**.

The Upload Excel page appears.



2. Click **Choose File** and select the required MS Excel file.

The Upload Excel page appears. It displays the data in the MS Excel file.

#	GROUP NAME	ROLE NAME	USER ID
#	Select Column To Import	Select Column To Import	Select Column To Import
1	Data Stewards	Data Steward_GER	mmannigan
2	Data Stewards	Data Steward_GER	mmenza
3	Data Stewards	Data Steward_GER	mmannigan

3. Double-click the **Select Column To Import** cell in the required column.

The available options appear.


#	GROUP NAME	ROLE NAME	USER ID
#	Select Column To Import	Select Column To Import	Select Column To Import
1	Data Stewards	Data Steward_GER	mmannigan

4. Select the appropriate option.

Field corresponds to options and Value corresponds to value of an option. You can import multiple columns. Use Clear Selection to undo the selection.


5. Click .

The <UI_Element> Options page appears. It displays the imported columns. You can delete a row that is not required. To delete rows, click a row and then click **Delete**.



6. Click **Save**.

The option values appear in the UI element under the Configure Form section.



Reference Data Manager

When you configure extended properties using UI elements, such as combo box, radio button, and list, you also need to configure their option values. You can use the Reference Data Manager connector to import option values from tables in the Reference Data Manager.


To configure option values using reference data manager connector, follow these steps:

1. In the **Configure Form** section, click the required UI element.

Ensure that you are in edit mode.


2. In the **Properties** section, click **Configure**.

The Connectors page appears.




3. On the **Connectors** page, click **Reference Data Manager** and then click **Next**.

The Reference Data Manager page appears. It displays the reference folders in the Connector View pane.



4. In the **Connector View** pane, expand a reference folder and select a reference table. The Parameters pane displays the columns in the reference table. You can also click Preview to view the data in the reference table.



5. In the **Parameters** pane, click the radio button next to the required column.
 You can select the controlling field from the drop down option. Ensure that you define the required dependencies in the Properties pane and that the option values for controlling field are configured using the same reference column.
6. Click **Finish**.
 The Extended Properties Configuration page appears.

7. Under the **Properties** section, switch **Load on Startup** to **ON**.
8. Click **Save**.

The option values are configured. For example, in the following form the List of Cities is the controlling field for Selected City. Both the fields get their option values from the same reference column.


Importing from Excel

You can import user-defined properties of a mapping specification from an XLSX file. You can either use an existing XLSX file or download a extended properties file from a mapping specification. Ensure that the XLSX file follows the correct template.

To import extended properties from XLSX files, follow these steps:


1. On the **Extended Properties** tab, click **Import From Excel**.

The Upload Excel page appears.



2. Click **Choose File**.
3. Browse and select the XLSX file.
4. Click .

The Upload Excel page appears. It displays the data in the XLSX file.



#	FIELD	VALUE	TYPE	PARENTFIELD	CREATED_BY	CREATED_DATE_TIME
#	Select Column To Import					
1	Data Stewards	Data Stewards	Combo Box			
2	Data Steward_UK	Data Steward_UK	Text Box	/Data Stewards	Administrator	10/20/2020 06:42:38
3	Data Steward_GER	Data Steward_GER	Text Box	/Data Stewards	Administrator	10/20/2020 06:42:38
4	Data Owners	Data Owner_GER	Text Box		Administrator	10/20/2020 06:42:38

5. Double-click the **Select Column To Import** cell in the required column.

The available options appear.

Upload Excel

#	FIELD	VALUE	TYPE	PARENTFIELD
#	Select Column To Import			
1			Combo Box	
2	Data Steward_UK	Data Steward_UK	Text Box	/Data Stewards
3	Data Steward_GER	Data Steward_GER	Text Box	/Data Stewards

6. Select an appropriate option.

For example, if you select Field, then the selected column is imported as Field.

Similarly, you can also select the Value, Type, and Parentfield columns. Ensure that you at least select a Field column.

7. Click .

The extended properties are imported.

Configure Edit Delete Import From Excel Export To Excel

Form Values

Data Stewards Select an option

Data Owners Data Owner_GER

Technical Data Steward Tech Data Steward_GER

Compliance Officer Mapping Designer

Self Help

Branching and Merging Maps

Branching a map enables multiple users to work on a mapping specification. You can create multiple branches of a parent map depending on the number of users. Different users can work on these branches and make changes in the mapping specification. These branches can then be merged into the parent map.

Branching and merging maps involves:


- [Branching maps](#)
- [Merging changes into parent maps](#)

Branching Maps


Branching a map means copying the map and pasting it in another subject area or a project. The copied map acts as a child map and the original map is called the parent map.

To branch maps, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, right-click a map and hover over the **Copy Map**.




3. Click **Copy Selected**.
4. Right-click the **Mappings** node under the required project or subject area.



5. Click **Paste**.

The mail comments page appears.



6. Enter **Mail Comments** and click .

The map is copied successfully into the subject area or the project. You can rename the child map and modify as needed. For example, you can change the reference

table, business rule, or add or remove columns. For more information on renaming mappings, refer to the [Updating Map Spec Overview](#) topic.


If you enable notifications in Mapping Manager Settings, project users receive an email notification when the map is copied to a project. For more information on configuring notifications, refer to the [Configuring Notifications](#) topic.

Merging Changes into Parent Maps

After making the required changes in a child map you can merge it with a parent map. You can also notify project users about the merge through email notifications.


To merge child maps with parent maps, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, right-click a parent map.



3. Click **Merge Mapping**.


The Merge Map page appears.



4. Select a child map.

5. Click .

The Merge Map page shows the changed data with respect to the parent map.



6. Use the following options:

Overwrite existing version

Use this option to overwrite the existing version.

Create New Version

Use this option to create new version of the parent map.

7. Enter relevant **Mail Comments**.

8. Click .

The child map is merged with the parent map.

If you enable notifications in the Mapping Manager Settings the project users receive mail comments through an email notification. For more information on configuring notifications, refer to the [Configuring Notifications](#) topic.

Deleting Maps


You can delete maps that are not required in a project. You can also opt to delete all the versions of a map.

To delete maps, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, select a map or multiple maps.

You can use shift key to select multiple maps.

3. Right-click the selection.



4. Click **Delete Mapping(s)**.

The Delete Mappings-Selected Mappings List page appears.

#	Project Hierarchy	Map Name	Current Version	All Versions	
			<input type="radio"/>	<input type="radio"/>	
1	Sales Data Mart	4_L_Customer_dim	<input type="radio"/>	<input type="radio"/>	✘
2	Sales Data Mart	3-L_Customer	<input type="radio"/>	<input type="radio"/>	✘

5. Use the following options:

Remove Mapping from Current Selection (✘)

Use this option to remove mappings from the current selection.

Delete all Versions

Use this option to delete all versions of the mappings.

Delete Current Version

Use this option to delete current version of the maps.

Viewing Workflow Logs


A default workflow, Mapping_Manager_Default_Workflow is assigned to all projects in the Mapping Manager. You can also create a workflow and assign it to your project. For more information on assigning workflow to projects, refer to the [Managing Mapping Manager Workflows](#) section.

You can view the flow of actions of the workflow assigned to a map. Along with other information, the workflow displays the current state of the map in the workflow.

To view workflow logs, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, click a map.


By default, the Mapping Specification tab opens.



#	Source System Name	Source Environment Name	Source Table Name	Source Column Name	Source Column Data Type	Source Column Length	Business Rule
1	erwinDIS	erwinDIS	dbo.ADS_ASSOCI	ID	bigint	8	ABS
2	erwinDIS	erwinDIS	dbo.ADS_ASSOCI	SOURCE_OBJECT_	bigint	8	ABS

3. Click the **Workflow Log** tab.

The workflow log of the map appears. The current workflow stage blinks in the diagram.



Use the following options:

User Comments (🗨️)

Use this option to view users and their comments in each stage.

Expand/Hide Users and Roles

Use this option to view or hide users and roles assigned to workflow stages.

Collapse/Expand Roles

Use this option to switch between the collapsed and expanded roles view. This option is enabled when you are in the Expand Users and Roles view.

Collapse/Expand Users

Use this option to switch between the collapsed and expanded users view. This option is enabled when you are in the Expand Users and Roles view.

Export Image

Use this option to download the workflow in the JPG format.

Analyzing Mappings

This section walks you through the multiple ways of analyzing source to target mappings.

Analyzing mappings involves:

- Data preview
 - [Generating virtual preview of target](#)
 - [Previewing data through Metadata Catalogue](#)
- Gap analysis
 - [Performing table gap analysis](#)
 - [Performing column gap analysis](#)
- Impact analysis
 - [Running impact analysis for tables and columns](#)
- Lineage analysis
 - [Running dual, forward, or reverse lineage analysis](#)
 - [Running end to end lineage](#)
- [Business view](#)
- [Mapping statistics](#)

Generating Virtual Preview of Targets

When you create a mapping specification, source column values undergo modifications based on the applied transformations. These modified values are updated in target columns based on the target update strategy. You can generate a virtual preview of targets to view the updated target columns.



Mapping specifications involving multiple source or target systems do not support virtual preview of targets.

To generate a virtual preview of targets, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, click a map.

The Mapping Specification grid appears.

#	Source System Name	Source Environment Name	Source Table Name	Source Column Name	Source Column Data Type	Source Column Length	Business Rule
1	Erwin_Sales	Integration	dbo.RM_RESOURCE	RESOURCEID	int	4	FLOOR
2	Erwin_Sales	Integration	dbo.RM_RESOURCE	RESOURCENAME	varchar	100	REVERSE
3	Erwin_Sales	Integration	dbo.RM_RESOURCE	RESOURCEDESC	varchar	150	

3. Click

Mapping Preview page appears, displaying the virtual preview of the target based on the source and transformations.



Mapping preview is currently supported for RDBMS only. Here is the list of transformation supported in Mapping Preview:

CONCAT, LTRIM, RTRIM, TRIM, CEIL, FLOOR, RPAD, LPAD, ROUND, SQRT, SUBSTR, UPPER, LOWER, TRUNC, SIN, COS, TAN, SINH, TANH, REVERSE, IS_DATE, IS_NUMBER, IS_SPACES, ISNULL, IIF, ISEMPTY, NVL, DECODE.

RESOURCEID_New	RESOURCE_NAME_New	RESOURCEDESC_New	RESOURCECELLPHONE_New	RESOURCEHOMEPHONE_New	RESOURCEEMAIL_New
1	nimdA				
2	rahdiS kitraK				
3	emaN_ecluoseR	desc			
4	steliV eoJ				

You can download the mapping preview details in the XLSX format. To download the mapping preview details, click  .


Previewing Data

You can preview data in a table using the Metadata Catalogue pane. You can also enter SQL queries to preview the required data in the database.


To preview data from databases, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, click a project.

The Metadata Catalogue pane appears on the right.



3. In the **Metadata Catalogue** pane, right-click a table and hover over **Preview Data**.



4. Click any one of the following:

Preview 100 Records

Click this option to preview the first 100 records.


Preview 1000 Records

Click this option to preview the first 1000 records.

Advanced Preview

Click this option to preview data based on a SQL query.

For example, if you click **Preview 100 Records**, then the User Credentials page appears.



5. Enter **User Name** and **Password** to connect with the database.

You can preview the data based on the options you selected.

#	CAT_DIALOG_TAB_ID	CAT_DIALOG_PROFILE_ID	CAT_DIALOG_TAB_NAME	CAT_DIALOG_TAB_PROPERTIES	CREATED_BY	CREATED_DATE_TIME
1	1	1	DefaultTab		Administrator	2018-09-14 10:39:46.02
2	2	2	DefaultTab		Administrator	2018-09-14 10:39:46.02
3	3	3	DefaultTab		Administrator	2018-09-14 10:39:46.02
4	4	4	DefaultTab		Administrator	2018-09-14 10:39:46.02
5	5	5	DefaultTab		Administrator	2018-09-14 10:39:46.023
6	6	6	DefaultTab		Administrator	2018-09-14 10:39:46.023
7	7	7	DefaultTab		Administrator	2018-09-14 10:39:46.027
8	8	8	DefaultTab		Administrator	2018-09-14 10:39:46.027
9	9	9	DefaultTab		Administrator	2018-09-14 10:39:46.027
10	10	10	DefaultTab		Administrator	2018-09-14 10:39:46.027
11	11	11	DefaultTab		Administrator	2018-09-14 10:39:46.03
12	12	12	DefaultTab		Administrator	2018-09-14 10:39:46.03
13	13	13	DefaultTab		Administrator	2018-09-14 10:39:46.03
14	14	14	DefaultTab		Administrator	2018-09-14 10:39:46.03
15	15	15	DefaultTab		Administrator	2018-09-14 10:39:46.03
16	16	16	DefaultTab		Administrator	2018-09-14 10:39:46.03
17	17	17	DefaultTab		Administrator	2018-09-14 10:39:46.033
18	18	18	DefaultTab		Administrator	2018-09-14 10:39:46.4
19	19	19	DefaultTab		Administrator	2018-09-14 10:39:46.423



If you use Advanced Preview then you need to enter a SQL query in the space provided and click  to preview the data.

Advanced Preview Records

```
SELECT [CAT_DIALOG_TAB_ID],[CAT_DIALOG_PROFILE_ID],[CAT_DIALOG_TAB_NAME],[CAT_DIALOG_TAB_PROPERTIES],[CREATED_BY],[CREATED_DATE_TIME],[LAST_MODIFIED_BY],[LAST_MODIFIED_DATE_TIME] FROM dbo.CAT_DIALOG_TAB
```

Preview Data

System Name:A_System
Environment Name:A_Environment

#	CAT_DIALOG_TAB_ID	CAT_DIALOG_PROFILE_ID	CAT_DIALOG_TAB_NAME	CAT_DIALOG_TAB_PROPERTIES	CREATED_BY	CREATED_DATE_TIME
1	1	1	DefaultTab		Administrator	2018-09-14 10:39:46.02
2	2	2	DefaultTab		Administrator	2018-09-14 10:39:46.02
3	3	3	DefaultTab		Administrator	2018-09-14 10:39:46.02
4	4	4	DefaultTab		Administrator	2018-09-14 10:39:46.02
5	5	5	DefaultTab		Administrator	2018-09-14 10:39:46.023
6	6	6	DefaultTab		Administrator	2018-09-14 10:39:46.023
7	7	7	DefaultTab		Administrator	2018-09-14 10:39:46.027
8	8	8	DefaultTab		Administrator	2018-09-14 10:39:46.027
9	9	9	DefaultTab		Administrator	2018-09-14 10:39:46.027
10	10	10	DefaultTab		Administrator	2018-09-14 10:39:46.027
11	11	11	DefaultTab		Administrator	2018-09-14 10:39:46.03
12	12	12	DefaultTab		Administrator	2018-09-14 10:39:46.03
13	13	13	DefaultTab		Administrator	2018-09-14 10:39:46.03

Performing Table Gap Analysis

You can perform a table gap analysis and find:

- Tables not being used in mappings
- Tables existing on mapping without valid source or target


You can perform table gap analysis at the following levels:

- System
- Environment
- Table

To perform table gap analysis, follow these steps:


1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, click a project.

The Metadata Catalogue pane appears on the right.




3. In the **Metadata Catalogue** pane, you can right-click a:
 - **System:** Use this option to run the analysis on all the tables under a system.
 - **Environment:** Use this option to run the analysis on all the tables under an environment.
 - **Table:** Use this option to run the analysis on a table.

For example, the following image displays the available options when you right-click a system.



4. Click **Table Gap Analysis**.

The Table Gap Analysis page appears.



5. Select projects and mappings.

6. Click .

The Table Gap Analysis Report for the selected projects and mappings appears.

Development Team

Export:

Table Gap Analysis Report

Table Gap Analysis Result For PROJECT(S) : AdventureWorks_Migration

Tables not being used on any mapping

#	System Name	Environment Name	Table Name
1	Erwin_Sales	Integration	dbo.RM_RESOURCE
2	Erwin_Sales	Integration_Target	dbo.RM_RESOURCE
3	Erwin_Sales	N_Environment	dbo.RM_PROJECT
4	Erwin_Sales	N_Environment	dbo.RM_RESOURCE

Tables existing on Mapping without valid Source (or) Target

#	System Name	System Env Name	Table Name	Project Name	Map Name	Usage
No Records Found						

Performing Column Gap Analysis

A column gap analysis enables you to find:

- Columns not existing in mappings
- Source columns existing on mappings without valid target
- Target columns listed on mappings without business rule and source column


You can perform column gap analysis at the following levels:

- System
- Environment
- Table

To perform column gap analysis, follow these steps:


1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, click a project.

The Metadata Catalogue pane appears on the right.




3. In the **Metadata Catalogue** pane, you can right-click a:
 - **System:** Use this option to run the analysis on all the columns under a system.
 - **Environment:** Use this option to run the analysis on all the columns under an environment.
 - **Table:** Use this option to run the analysis on all the columns under a table.

For example, the following image displays the available options when you click a system.



4. Click **Column Gap Analysis**.

The Column Gap Analysis page appears.



5. Select projects and mappings.

6. Click .

The Column Gap Analysis Report for the selected projects and mappings appears.

Column Gap Analysis

Development Team

Export:

Column Gap Analysis Report

Column Gap Analysis Result For PROJECT(S) : Erwin_Sales

Columns not existing on any Mapping

#	System Name	Environment Name	Table Name	Column Name
1	Erwin_Sales	Integration_Target	dbo.RM_RESOURCE	RESOURCEID
2	Erwin_Sales	Integration_Target	dbo.RM_RESOURCE	RESOURCENAME
3	Erwin_Sales	Integration_Target	dbo.RM_RESOURCE	RESOURCEDESC
4	Erwin_Sales	Integration_Target	dbo.RM_RESOURCE	RESOURCECELLPHONE
5	Erwin_Sales	Integration_Target	dbo.RM_RESOURCE	RESOURCEHOMEPHONE
6	Erwin_Sales	Integration_Target	dbo.RM_RESOURCE	RESOURCEEMAIL
7	Erwin_Sales	N_Environment	dbo.RM_PROJECT	PROJECTID
8	Erwin_Sales	N_Environment	dbo.RM_PROJECT	RESOURCEID
9	Erwin_Sales	N_Environment	dbo.RM_PROJECT	PROJECTNAME
10	Erwin_Sales	N_Environment	dbo.RM_PROJECT	PROJECTDESC
11	Erwin_Sales	N_Environment	dbo.RM_RESOURCE	RESOURCE_ID
12	Erwin_Sales	N_Environment	dbo.RM_RESOURCE	RESOURCENAME
13	Erwin_Sales	N_Environment	dbo.RM_RESOURCE	RESOURCEDESC
14	Erwin_Sales	N_Environment	dbo.RM_RESOURCE	RESOURCECELLPHONE
15	Erwin_Sales	N_Environment	dbo.RM_RESOURCE	RESOURCEHOMEPHONE
16	Erwin_Sales	N_Environment	dbo.RM_RESOURCE	RESOURCEEMAIL

Source Columns existing on Mapping without valid Target (with or without BR) (or) Target Columns listed on Mapping without BR (Without Source Col)

#	System Name	Environment	Table Name	Column Name	Project Name	Map Name	Usage
No Records Found							

© 2018 erwin, Inc. All rights reserved

Page 1 of 1


Running Impact Analysis

A technical asset may act as a source, target, or both in mappings. You can run impact analysis on a table or column using the Mapping Specification grid. The impact analysis displays the impact of the table or column as source or target. It includes information about indirect impact (upstream and downstream) and impacts of the table or column on business rules, source extract SQL, and lookups.

To run impact analysis, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, click the required map.


The Mapping Specification grid appears.



#	Source System Name	Source Environment Name	Source Table Name	Source Column Name	Source Column Data Type	Source Column Length	Business Rule
1	Erwin_Sales	Integration	dbo.RM_RESOURCE	RESOURCEID	int	4	FLOOR
2	Erwin_Sales	Integration	dbo.RM_RESOURCE	RESOURCENAME	varchar	100	REVERSE
3	Erwin_Sales	Integration	dbo.RM_RESOURCE	RESOURCEDESC	varchar	150	

3. Select a row.
4. Right-click a table or column.

For example, the following image displays the options available when you right-click a table.



5. Hover over **Impact Analysis Report**.

The available options appear.

6. Use the following options:


Default Search

Use this option to view the default report. The default report includes all the mappings in the impact analysis.

Advanced Search

Use this option to customize the impact analysis report by including the required mappings.

For example, if you click Advance Search, then the Impact Analysis Report page appears.




You can use the following options to select the required mappings:

- **Load Passive Mappings/Load Active Mappings:** Use this option to load passive or active mappings.
- **Load All Mappings:** Use this option to load all the mappings.

Select the mappings to include them in the impact analysis and click .


For example, the following image displays the Impact Analysis Report, if you click the Default Search.

By default, the Direct Impact tab opens. It displays the impact of the technical asset as a source and as a target.



To view the indirect impact, click the **Indirect** tab.


It displays the upstream and downstream impact of the technical asset.



To view other impacts, click the **Other Impacts** tab.

It displays the impact of the technical asset on:

- Business rules
- Source Extract SQL
- Lookups



To export the report in the XLSX format, click .

To export the report in the PDF format, click .

Running Lineage Analysis

After mapping source metadata with target metadata, you can run the lineage analyzer on the mapping through the Mapping Specification grid. The generated data lineage report helps you trace the data's origin, its transformations, and its destination after source to target mappings.

You can run the lineage at the following levels:

- [System](#)
- [Environment](#)
- [Table](#)
- [Column](#)

System


You can run forward and reverse lineage analysis to trace metadata at the system level. Forward lineage analysis generates lineage with the system as source. And, reverse lineage analysis generates lineage with the system as target. The Dual-Combined View lineage analysis generates a lineage, which includes both forward and reverse lineage.

Viewing Lineage

To run lineage analyzer at the system level, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, click the required mapping.

The Mapping Specification grid appears.



The screenshot shows a software interface with a tabbed menu at the top containing 'Mapping Specification', 'Graphical Designer', 'Test Specification', and 'Workflow Log'. Below the tabs is a toolbar with various icons and a 'Profiles:' dropdown menu. The main area displays a grid with the following data:

#	Target System Name	Target Environment Name	Target Table Name	Target Column Name	Target Column Data Type	Target Column Length	Target Column Precision	T S
1	SQLTechPubs	SQLTechPubs	dbo.Customers	CustomerID	nchar	5	0	
2	SQLTechPubs	SQLTechPubs	dbo.Customers	CompanyName	nvarchar	40	0	
3	SQLTechPubs	SQLTechPubs	dbo.Customers	ContactName	nvarchar	30	0	
4	SQLTechPubs	SQLTechPubs	dbo.Customers	ContactTitle	nvarchar	30	0	

3. Select a row.
4. Right-click a system and hover over **Lineage Analyzer**.

The options available for Lineage Analyzer appear.

#	Target System Name	Target Environment Name	Target Table Name	Target Column Name	Target Column Data Type
1	SQLTechPubs	SQLTechPubs	dbo.Customers	CustomerID	nchar
2	SQLTechPubs	SQLTechPubs	dbo.Customers	CompanyName	nvarchar
3	SQLTech		Customers	ContactName	nvarchar
4	SQLTech		Customers	ContactTitle	nvarchar
5	SQLTech				nvarchar

- Font Color
- Font Styles
- Background Color
- Font Size
- Clear Formatting
- Lineage Analyzer
- Extended Properties
- Share Link

- Forward
- Reverse
- Dual - Combined View

5. Hover over any one of the following:

- **Forward:** Use this option to view forward lineage.
- **Reverse:** Use this option to view reverse lineage.
- **Dual - Combined View:** Use this option to view combined forward and reverse lineage.

For example, when you hover over Forward, All Projects and By Project appear as options.

#	Target System Name	Target Environment Name	Target Table Name	Target Column Name	Target Column Data Type	Target Length
1	SQLTechPubs	SQLTechPubs	dbo.Customers	CustomerID	nchar	5
2	SQLTechPubs	SQLTechPubs	dbo.Customers	CompanyName	nvarchar	40
3	SQLTechPubs	SQLTechPubs	dbo.Customers	ContactName	nvarchar	30
4	SQLTechPubs	SQLTechPubs	dbo.Customers	ContactTitle	nvarchar	30
5	SQLTechPubs	SQLTechPubs	dbo.Customers	Address	nvarchar	60


6. Use the following options:

All Projects

Use this option to include all the projects in lineage analysis.


By Project

Use this option to select projects for lineage analysis.



By default, all projects are selected. Clear the check boxes for the projects that are not required. Then, click .


The system's lineage is generated based on the options you selected.



Working on Lineage

Lineage of a system shows how metadata moves through systems. It provides a summary of environments used as source and target. Also, it gives you information about the systems and environments involved in the lineage.

For example, the following image displays a system's lineage.




Use the following options:

Sensitivity Indicator

Use this option to view sensitivity of the environments in the lineage.

For example, in the following lineage, the SQLTechPubs and SQL Env environments are sensitive.



Overview Lineage

Use this option to switch between detailed and overview lineage view.

Detailed lineage view: This view is helpful to technical users like ETL developers. When you reverse engineer ETL jobs or SQL scripts, the lineage might contain


temporary tables, ETL components (filters, joiners, routers etc.). This view includes systems and environments, that do not exist in the Metadata Manager.

For example, the following lineage displays the erwinDOC system and erwinDOC environment. These do not exist in the Metadata Manager.



Overview lineage view: This view is helpful to business users. It excludes systems and environments that do not exist in the Metadata Manager.

For example, the following lineage does not display erwinDOC system and erwinDOC environment. These do not exist in the Metadata Manager.



Collapse/Expand (📁)

Use this option to switch between collapsed and expanded view. The expanded view includes environments involved in the lineage and the collapsed view excludes environments in the lineage.


For example, in the following lineage the collapsed view does not display environments involved in the lineage.



Auto Expand/Autofit (📏)

This switch is enabled when you use the expanded view (). Use this option to switch between the Auto Expand view and Auto Fit view. The Auto Expand view shrinks the space for the list of environments and the Autofit view expands the space to fit the list of environments.

For example, the following lineage displays the Auto Expand view.



Export to Image

Use this option to download the lineage in the JPG format.

Export to PDF


Use this option to download the lineage in the PDF format.

Export to Excel


Use this option to download the lineage in the XLSX format.

Highlighting Lineage Path of an Environment

To highlight an environment's lineage path, click the environment. The environment is highlighted in orange color, its forward lineage path appears in red, and its reverse lineage path appears in blue.



Systems that are not part of a lineage path disappear. For example, in the following lineage, the Oracle system disappears in the lineage path with respect to the erwinSales environment.



System Details

By default, this pane displays properties of a system for which, you ran lineage analysis. You can click a system in the lineage to view its properties in this pane.

Environment Details

By default, this pane displays a list of environments under the system for which, you ran lineage analysis.

You can click a system in the lineage to view list of environments under the system. You can then click <Environment_Name> to view lineage of the environment.



Environments that are not involved in lineage, are not included in the list.

Extended Properties

By default, this pane displays the extended properties of a system for which, you ran lineage analysis. You can click a system in the lineage to view its extended properties in this pane.

For more information, on configuring extended properties of a system, refer to the [System](#) topic.

Summary

This pane displays a summary of the lineage report. It gives information about number of environments acting as source, target, or both in the lineage.

Environment


You can run forward and reverse lineage analysis to trace metadata at the environment level. Forward lineage analysis generates lineage with the environment as source. And, reverse lineage analysis generates lineage with the environment as target. The Dual-Combined View lineage analysis generates a lineage, which includes both forward and reverse lineage.

Viewing Lineage

To run lineage analyzer at the environment level, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, click the required mapping.

The Mapping Specification grid appears.



#	Target System Name	Target Environment Name	Target Table Name	Target Column Name	Target Column Data Type	Target Column Length	Target Column Precision
1	Oracle	TechPubs	APPQOSSYS.WLM_	OPER	NUMBER		
2	Oracle	TechPubs	APPQOSSYS.WLM_	NCLSR	NUMBER		
3	Oracle	TechPubs	APPQOSSYS.WLM_	CLPCSTR	VARCHAR2	4000	
4	Oracle	TechPubs	APPQOSSYS.WLM_	ACTIVE	CHAR	1	
5	Oracle	TechPubs	APPQOSSYS.WLM_	SEQNO	NUMBER		

3. Select a row.
4. Right-click an environment and hover over **Lineage Analyzer**.

The options available for Lineage Analyzer appear.

#	Target System Name	Target Environment Name	Target Table Name	Target Column Name	Target Column Data Type	Target Column Length
1	Oracle	TechPubs	APPQOSSYS.WLM	OPER	NUMBER	
2	Oracle	TechPubs	APPQOSSYS.WLM	NCLSR	NUMBER	
3	Oracle	TechPubs		STR	VARCHAR2	4000
4	Oracle	TechPubs				
5	Oracle	TechPubs				

5. Hover over any one of the following:

- **Forward:** Use this option to view forward lineage.
- **Reverse:** Use this option to view reverse lineage.
- **Dual - Combined View:** Use this option to view combined forward and reverse lineage.

For example, when you hover over Reverse, All Projects and By Project appear as options.

#	Target System Name	Target Environment Name	Target Table Name	Target Column Name	Target Column Data Type	Target Column Length	Target Column Precision
1	Oracle	TechPubs	APPQOSSYS.WLM_OPER		NUMBER		
2	Oracle	TechPubs	APPQOSSYS.WLM_NCLSR		NUMBER		
3	Oracle	TechPubs		STR	VARCHAR2	4000	
4	Oracle	TechPubs					
5	Oracle	TechPubs	APPQOSSYS.WLM_SEQN				


6. Use the following options:

All Projects

Use this option to include all the projects in lineage analysis.


By Project

Use this option to select projects for lineage analysis.



By default, all projects are selected. Clear the check boxes for the projects that are not required. Then, click .


The environment's lineage is generated based on the options you selected.



Working on Lineage

Lineage of an environment shows how metadata moves through environments. It provides a summary of tables used as source and target. Also, it gives information about the environments and tables involved in the lineage.

For example, the following image displays an environment's lineage.




Use the following options:

Logical Name

Use this option to view logical names of the tables in the lineage.


For example, in the following lineage, the table names are replaced with their logical names.



Expanded Logical Name

Use this option to view expanded logical names of the tables in the lineage.


For example, in the following lineage, the table names are replaced with their expanded logical names.



Sensitive Data Indicator

Use this option to view sensitivity of tables in the lineage.

For example, the following lineage, displays the sensitivity of the tables.




Overview Lineage

Use this option to switch between detailed and overview lineage view.

Detailed lineage view: This view is helpful to technical users like ETL developers. When you reverse engineer ETL jobs or SQL scripts, the lineage might contain temporary tables, ETL components (filters, joiners, routers etc.). This view includes environments and tables that do not exist in Metadata Manager.

For example, the following lineage displays the erwinDOC environment and CustDetails table. These, do not exist in the Metadata Manager.



Overview lineage view: This view is helpful to business users. It excludes environments and tables that do not exist in the Metadata Manager.

For example, the following lineage does not display erwinDOC environment and CustDetails table. These, do not exist in the Metadata Manager.



Collapse/Expand (☑)

Use this option to switch between collapsed and expanded view. The expanded view includes tables involved in the lineage and the collapsed view excludes tables in the lineage.


For example, in the following lineage the collapsed view does not display tables involved in the lineage.



Auto Expand/Autofit (↕)

This switch is enabled when you use the expanded view (☑). Use this option to switch between the Auto Expand view and Auto Fit view. The Auto Expand view shrinks the space for the list of tables and the Autofit view expands the space to fit the list of tables.

For example, the following lineage displays the Auto Expand view.



Export to Image

Use this option to download the lineage in the JPG format.

Export to PDF


Use this option to download the lineage in the PDF format.

Export to Excel

Use this option to download the lineage in the XLSX format.


Highlighting Lineage Path of a Table

To highlight a table's lineage path, click the table. The table is highlighted in orange color, its forward lineage path appears in red, and its reverse lineage path appears in blue.



Environments that are not part of a lineage path disappear.

For example, in the following lineage, the TechPubs environment disappears in the lineage path with respect to the dbo.Categories table.



Environment Details

By default, this pane displays properties of an environment for which, you ran lineage analysis. You can click an environment in the lineage to view its properties in this pane.

Table Details

By default, this pane displays a list of tables under the environment for which, you ran lineage analysis.

You can click an environment in the lineage to view list of tables under the environment. You can then click <Table_Name> to view lineage of the table.



Tables that are not involved in lineage, are not included in the list.

Extended Properties

By default, this pane displays the extended properties of an environment for which, you ran lineage analysis. You can click an environment in the lineage to view its extended properties in this pane.

For more information, on configuring extended properties of an environment, refer to the [Environment](#) topic.

Summary

This pane displays a summary of the lineage report. It gives information about number of tables acting as source, target, or both in the lineage.

Table


You can run forward and reverse lineage analysis to trace metadata at the table level. Forward lineage analysis generates lineage with the table as source. And, reverse lineage analysis generates lineage with the table as target. The Dual-Combined View lineage analysis generates a lineage, which includes both forward and reverse lineage.

Viewing Lineage

To run lineage analyzer at the table level, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, click the required mapping.

The Mapping Specification grid appears.



#	Target System Name	Target Environment Name	Target Table Name	Target Column Name	Target Column Data Type	Target Column Length	Target Column Precision	T S
1	SQLTechPubs	SQLTechPubs	dbo.Customers	CustomerID	nchar	5	0	
2	SQLTechPubs	SQLTechPubs	dbo.Customers	CompanyName	nvarchar	40	0	
3	SQLTechPubs	SQLTechPubs	dbo.Customers	ContactName	nvarchar	30	0	
4	SQLTechPubs	SQLTechPubs	dbo.Customers	ContactTitle	nvarchar	30	0	

3. Select a row.
4. Right-click a table and hover over **Lineage Analyzer**.

The options available for Lineage Analyzer appear.

#	Target System Name	Target Environment Name	Target Table Name	Target Column Name	Target Column Data Type	Target Column Length	Target Column Precision	T	S
1	SQLTechPubs	SQLTechPubs	dbo.Customers	CustomerID	nchar	5	0		
2	SQLTechPubs	SQLTechPubs	dbo.			40	0		
3	SQLTechPubs	SQLTechPubs	dbo.			30	0		
4	SQLTechPubs	SQLTechPubs	dbo.						
5	SQLTechPubs	SQLTechPubs	dbo.						

5. Hover over any of the following:

- **Forward:** Use this option to view forward lineage.
- **Reverse:** Use this option to view reverse lineage.
- **Dual - Combined View:** Use this option to view combined forward and reverse lineage.

For example, when you hover over Reverse, All Projects and By Project appear as options.

#	Target System Name	Target Environment Name	Target Table Name	Target Column Name	Target Column Data Type	Target Column Length	Target Column Precision	Target Column Scale
1	SQLTechPubs	SQLTechPubs	dbo.Customers	CustomerID	nchar	5	0	0
2	SQLTechPubs	SQLTechPubs	dbo.			40	0	0
3	SQLTechPubs	SQLTechPubs	dbo.			30	0	0
4	SQLTechPubs	SQLTechPubs	dbo.					0
5	SQLTechPubs	SQLTechPubs	dbo.Customers	Address	varchar			


6. Use the following options:

All Projects

Use this option to include all the projects in lineage analysis.


By Project

Use this option to select projects for lineage analysis.



By default, all projects are selected. Clear the check boxes for the projects that are not required. Then, click .


The table's lineage is generated based on the options you selected.



Working on Lineage

Lineage of a table shows how metadata moves through tables. It provides a summary of columns used as source and target. Also, it gives you information about the technical and business properties of columns involved in the lineage.

For example, the following image displays a table's lineage.




Use the following options:

Logical Name

Use this option to view logical names of columns in the lineage.


For example, in the following lineage, column names are replaced with their logical names.



Expanded Logical Name

Use this option to view expanded logical names of the columns in the lineage.


For example, in the following lineage, column names are replaced with their expanded logical names.



Sensitive Data Indicator

Use this option to view sensitivity of columns in the lineage.

For example, the following lineage displays the sensitivity of columns.




Overview Lineage

Use this option to switch between detailed and overview lineage view.


Detailed lineage view: This view is helpful to technical users like ETL developers. When you reverse engineer ETL jobs or SQL scripts, the lineage might contain temporary tables, ETL components (filters, joiners, routers etc.). This view includes tables and columns that do not exist in the Metadata Manager.

For example, the following lineage displays the CustDetails table that does not exist in the Metadata Manager.



Overview lineage view: This view is helpful to business users. It excludes tables and columns that do not exist in the Metadata Manager.


For example, the following lineage does not display CustDetails table that does not exist in the Metadata Manager.



Collapse/Expand (☑)

Use this option to switch between collapsed and expanded view. The expanded view includes columns involved in the lineage and the collapsed view excludes columns in the lineage.


For example, in the following lineage the collapsed view does not display columns involved in the lineage.



Auto Expand/Autofit (↔)

This switch is enabled when you use the expanded view (). Use this option to switch between the Auto Expand view and Auto Fit view. The Auto Expand view shrinks the space for the list of columns and the Autofit view expands the space to fit the list of columns.

For example, the following lineage displays the Auto Expand view.



Export to Image ()

Use this option to download the lineage in the JPG format.

Export to PDF ()

Use this option to download the lineage in the PDF format.

Export to Excel

Use this option to download the lineage in the XLSX format.


Highlighting Lineage Path of a Column

To highlight a column's lineage path, click the column. The column is highlighted in orange color, its forward lineage path appears in red, and its reverse lineage path appears in blue.



Tables that are not part of a lineage path disappear.

For example, in the following lineage, the CustDetails and Account table disappear in the lineage path with respect to the City column.



Summary

This pane displays a summary of the lineage report. It gives information about number of columns acting as source, target, or both in the lineage.

Column Details

By default, this pane displays a list of columns under the table for which, you ran lineage analysis.

You can click a table in the lineage to view list of columns under the table. You can then click <Column_Name> to view lineage of the column.

 Columns that are not involved in lineage, are not included in the list.

Technical


This pane displays technical properties of a table. By default, it displays the technical properties of the table for which, you ran lineage analysis. You can click a table in the lineage and view its technical properties. The technical properties of a table include System Name, Environment Name, Table Name, and so on. For more information on updating table properties, refer to the [Updating Table Properties](#) topic.

Business

This pane displays business properties of a table. By default, it displays the business properties of the table for which, you ran lineage analysis. You can click a table in the lineage and view its business properties. The business properties of a table include Logical Table Name, Table Definition, Expanded Logical Name, and so on. For more information on updating table properties, refer to the [Updating Table Properties](#) topic.

Transformations

To view transformations between two columns, click the link between the columns. The Transformations pane expands and displays the transformations.



You can expand the transformation node to view the transformation details that includes Business Rule, Extended Business Rule, Trans lookup Condition, and Lookup On.

Extended Properties

By default, this pane displays the extended properties of a table for which, you ran the lineage analysis. You can click a table in the lineage to view its extended properties in this pane. For more information on configuring extended properties of tables, refer to the [Table](#) topic.

Column


You can run forward and reverse lineage analysis to trace metadata at the column level. Forward lineage analysis generates a lineage with the column as source. And, reverse lineage analysis generates a lineage with the column as target. The Dual-Combined View lineage analysis generates a lineage, which includes both forward and reverse lineage.

Viewing Lineage

To run lineage analyzer at the column level, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, click the required mapping.

The Mapping Specification grid appears.



#	Target System Name	Target Environment Name	Target Table Name	Target Column Name	Target Column Data Type	Target Column Length	Target Column Precision
1	SQLTechPubs	SQLTechPubs	dbo.Customers	CustomerID	nchar	5	0
2	SQLTechPubs	SQLTechPubs	dbo.Customers	CompanyName	nvarchar	40	0
3	SQLTechPubs	SQLTechPubs	dbo.Customers	ContactName	nvarchar	30	0
4	SQLTechPubs	SQLTechPubs	dbo.Customers	ContactTitle	nvarchar	30	0

3. Select a row.
4. Right-click a column and hover over **Lineage Analyzer**.

The options available for Linear Analyzer appear.

#	Target System Name	Target Environment Name	Target Table Name	Target Column Name	Target Column Data Type	Target Column Length	Target Column Precision	Target Column Scale
1	SQLTechPubs	SQLTechPubs	dbo.Customers	CustomerID	nchar	5	0	0
2	SQLTechPubs	SQLTechPubs	dbo.Customers	Comp			0	0
3	SQLTechPubs	SQLTechPubs	dbo.Customers	Contact			0	0
4	SQLTechPubs	SQLTechPubs	dbo.Customers	Contact			0	0
5	SQLTechPubs	SQLTechPubs	dbo.Customers	Address			0	0

5. Hover over any one of the following:

- **Forward:** Use this option to view forward lineage.
- **Reverse:** Use this option to view reverse lineage.
- **Dual - Combined View:** Use this option to view forward and reverse lineage of the column combined together.
- **Dual - Split View:** Use this option to view combined forward and reverse lineage.

For example, when you hover over the Reverse, All Projects and By Project appear as options.

#	Target System Name	Target Environment Name	Target Table Name	Target Column Name	Target Column Data Type	Target Column Length	Target Column Precision	Target Column Scale	Target Column Nullable Flag
1	SQLTechPubs	SQLTechPubs	dbo.Customers	CustomerID	int	9	0	0	<input type="checkbox"/>
2	SQLTechPubs	SQLTechPubs	dbo.Customers	CompanyID	int	9	0	0	<input type="checkbox"/>
3	SQLTechPubs	SQLTechPubs	dbo.Customers	ContactID	int	9	0	0	<input checked="" type="checkbox"/>
4	SQLTechPubs	SQLTechPubs	dbo.Customers	ContactID	int	9	0	0	<input checked="" type="checkbox"/>
5	SQLTechPubs	SQLTechPubs	dbo.Customers	Address	varchar	60	0	0	<input type="checkbox"/>


6. Use the following options:

All Projects

Use this option to include all the projects in lineage analysis.


By Project

Use this option to select projects for lineage analysis.



By default, all the projects are selected. Clear the check boxes for the projects that are not required. Then, click .


The column's lineage is generated based on the options you selected.



Working on Lineage

Lineage of a column shows how metadata moves through columns. It provides a summary of columns used as source and target. Also, it gives information about technical and business properties of columns involved in the lineage.

For example, the following image displays a column's lineage.




Use the following options:

Logical Name

Use this option to view logical names of the columns in the lineage.


For example, in the following lineage the column names are replaced with their logical names.



Expanded Logical Name

Use this option to view expanded logical names of the columns in the lineage.


For example, in the following lineage the column names are replaced with their expanded logical names.



Sensitivity Indicator

Use this option to view sensitivity of columns in the lineage.

For example, the following lineage displays the sensitivity of the columns.




Overview Lineage

Use this option to switch between detailed and overview lineage view.


Detailed lineage view: This view is helpful to technical users like ETL developers. When you reverse engineer ETL jobs or SQL scripts, the lineage might contain temporary tables, ETL components (filters, joiners, routers etc.). This view includes tables and columns that do not exist in the Metadata Manager.

For example, the following lineage displays the CustDetails table that does not exist in the Metadata Manager.



Overview lineage view: This view is helpful to business users. It excludes tables and columns that do not exist in the Metadata Manager.

For example, the following lineage does not display CustDetails table that does not exist in the Metadata Manager.



Collapse/Expand (📁)

Use this option to switch between collapsed and expanded view. The expanded view includes columns involved in the lineage and the collapsed view excludes columns in the lineage.


For example, in the following lineage the collapsed view does not display columns involved in the lineage.



Auto Expand/Autofit (📏)

This switch is enabled when you use the expanded view (). Use this option to switch between the Auto Expand view and Auto Fit view. The Auto Expand view shrinks the space for the list of columns and the Autofit view expands the space to fit the list of columns.

For example, the following lineage displays the Auto Expand view.



Export to Image ()

Use this option to download the lineage in the JPG format.

Export to PDF ()


Use this option to download the lineage in the PDF format.

Export to Excel

Use this option to download the lineage in the XLSX format.

Highlighting Lineage Path of a Column

To highlight a column's lineage path, click the column. The column is highlighted in orange color, its forward lineage path appears in red, and its reverse lineage path appears in blue.



Tables that are not part of a lineage path disappear.

For example, in the following lineage, the Account table disappears in the lineage path with respect to the SRSLCN column.



Summary

This pane displays a summary of the lineage report. It gives information about number of columns acting as source, target, or both in the lineage.

Technical

By default, this pane displays technical properties of the column for which, you ran lineage analysis. You can click a column in the lineage and view its technical properties. The technical properties of a column include Column Data Type, Column Precision, Column Length, and so on. For more information on updating column properties, refer to the [Updating Column Properties](#) topic.

Business

By default, this pane displays business properties of the column for which, you ran the lineage analysis. You can click a column in the lineage and view its business properties. The business properties of a column include Column Definition, Logical Column Name, Column Class, and so on. For more information on updating column properties, refer to the [Updating Column Properties](#) topic.

Transformations

To view transformations between two columns, click the link between the columns. The Transformations pane expands and displays the transformations.



You can expand the transformation node to view the transformation details that includes Business Rule, Extended Business Rule, Trans lookup Condition, and Lookup On.

Transformations	
Property	Value
Target Column Scale	
Business Rule	UPPER
Extended Business Rule	
Trans lookup Condition	SELECT CompanyName FROM db dbo.Customers.CompanyName
Lookup On	CompanyName

Valid Values

To view valid values for a column, Click a column in the lineage, expand the Valid Values pane, and click the **Click Here** hyperlink. For more information on assigning valid values using codesets, refer to the [Assigning Codesets to Columns](#) topic.

Extended Properties

By default, this pane displays the extended properties of the column for which, you ran the lineage analysis. You can click a column in the lineage to view its extended properties in this pane. For more information on configuring extended properties of columns, refer to the [Column](#) topic.


Running End to End Lineage

You can run end to end lineage analysis at project level and trace the data between any two mapping projects. The end to end lineage report can be drilled down further to trace intermediate stages of data.

To run end to end lineage at project level, follow these steps:


1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, right-click the required source project.

The available options appear.



3. Click **End to End Lineage**.

The Select Target page appears.



4. Select a target subject or a target project.

5. Click .

The End to End Lineage Summary page appears. You can drag and arrange column positions on the page for better visibility.

#	Source Project	Source Subject	Source System	Source Environment	Source Table	Source Column	Source XPath	Source User Defined-1	Source User Defined-2	Source Valid Values	Target Column	Target
1	Erwin_Project		3rd Party Flat Files	3rd Party Flat Files	dbo.ADS_ASSOCIATION	TARGET_OBJECT_ID				Click Here		
2	Erwin_Project		3rd Party Flat Files	3rd Party Flat Files	dbo.ADS_ASSOCIATION	TARGET_OBJECT_TYPE_ID				Click Here		
3	Erwin_Project		3rd Party Flat Files	3rd Party Flat Files	dbo.ADS_ASSOCIATION	RELATIONSHIP				Click Here		
4	Erwin_Project		3rd Party Flat Files	3rd Party Flat Files	dbo.ADS_ASSOCIATION	ID				Click Here		
5	Erwin_Project		New_Erwin	Erwin_Environment	dbo.ADS_ASSOCIATION	ID				Click Here	F_ID_New	
6	Erwin_Project		New_Erwin	Erwin_Environment	dbo.ADS_ASSOCIATION	ID				Click Here	F_ID_New	
7	Erwin_Project		New_Erwin	Erwin_Environment	dbo.ADS_ASSOCIATION	RELATIONSHIP				Click Here	F_ID_New	
8	Erwin_Project		New_Erwin	Erwin_Environment	dbo.ADS_ASSOCIATION	RELATIONSHIP				Click Here	N_RELATIONSHIP_New	
9	Erwin_Project		New_Erwin	Erwin_Environment	dbo.ADS_New_ASSOCIATION	TARGET_OBJECT_ID_New				Click Here		
10	Erwin_Project		New_Erwin	Erwin_Environment	dbo.ADS_ASSOCIATION	SOURCE_OBJECT_ID				Click Here	S_SOURCE_OBJECT_ID	
11	Erwin_Project		New_Erwin	Erwin_Environment	dbo.ADS_New_ASSOCIATION	TARGET_OBJECT_TYPE_ID_New				Click Here		
12	Erwin_Project		New_Erwin	Erwin_Environment	dbo.ADS_ASSOCIATION	SOURCE_OBJECT_ID				Click Here		
13	Erwin_Project		New_Erwin	Erwin_Environment	dbo.ADS_New_ASSOCIATION	RELATIONSHIP_New				Click Here		
14	Erwin_Project		New_Erwin	Erwin_Environment	dbo.ADS_ASSOCIATION	ID				Click Here		
15	Erwin_Project		New_Erwin	Erwin_Environment	dbo.ADS_ASSOCIATION	SOURCE_OBJECT_TYPE_ID				Click Here	F_ID_New	
16	Erwin_Project		New_Erwin	Erwin_Environment	dbo.ADS_ASSOCIATION	SOURCE_OBJECT_ID				Click Here		
17	Erwin_Project		New_Erwin	Erwin_Environment	dbo.ADS_ASSOCIATION	SOURCE_OBJECT_TYPE_ID				Click Here	K_SOURCE_OBJECT_TYPE	

Use the following options to work on the End to End Lineage Summary page:

Navigate

Use  or  to navigate.

Expand ()

To expand the lineage summary, use . The expanded summary shows the intermediate stages of data.

#	Project Name	Map Id	Map Name	Source System	Source Environment	Source Table	Source Column	Source XPath	Source Valid Values	Business Rule	Extended Business Rule	Target Valid Values	Target XPath	Target
1	Erwin_Project	233	Erwin_Map	3rd Party Flat	3rd Party Flat	dbo.ADS_ASSOCIATION	TARGET_OBJECT_ID		Click Here	ABS		Click Here		TARGE
2	A_Project	248	K_New_Mapp	3rd Party Flat	3rd Party Flat	dbo.ADS_New_ASSOCI	TARGET_OBJECT_ID_Ne		Click Here			Click Here		L_TAR

Reset Column Ordering (🔌)

Use this option to reset the column order on the page.

Export (📄)

Use this option to export the lineage summary in the XLSX format.


Opening Business View

You can open a concise view of mappings with an ability to instantly generate lineage and impact analysis. It is an alternate view for both workspace and published maps and more suitable for business users.

To open business view of mappings, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, right-click a map.

The available options appear.



3. Click **Mapping Alternate View**.

The Mapping Summary page appears. It has two sections, Mapping Details and Mapping Specifications.

The screenshot shows a 'Mapping Summary' window with two main sections: 'Mapping Details' and 'Mapping Specification'.

Mapping Details:

Specification Name	Erwin_Map	Map Id	221
Version	1.00	Version Label	
Mapping Description	mapping description		
Target Tables	dbo.ADS_New ASSOCIATIONS	Source Tables	dbo.ADS_ASSOCIATIONS
SQL Query	SQL Query Description		
Target Update Strategy		Map Spec Docs	View
Graphical View	View	Extended Properties	View
User Defined1		User Defined2	
User Defined3		User Defined4	
User Defined5		View all User Defined Details	

Mapping Specification:

#	Info	Target Details				Transformations		System	
		System	Environment	Table	Column	Data Type (L/P/S)	Business Rule		Extended Business Rule
1		New_Erwin	Erwin_Environment	dbo.ADS_New_ASSOC_ID_New		bigint(8,19,0)	ABS		erwinDIS
2		New_Erwin	Erwin_Environment	dbo.ADS_New_ASSOC_SOURCE_OBJECT_ID_New		bigint(8,19,0)	ABS		erwinDIS
3		New_Erwin	Erwin_Environment	dbo.ADS_New_ASSOC_SOURCE_OBJECT_TYPE_ID		bigint(8,19,0)	ABS		erwinDIS
4		New_Erwin	Erwin_Environment	dbo.ADS_New_ASSOC_TARGET_OBJECT_ID_New		bigint(8,19,0)	ABS		erwinDIS
5		New_Erwin	Erwin_Environment	dbo.ADS_New_ASSOC_TARGET_OBJECT_TYPE_ID		bigint(8,19,0)	ABS		erwinDIS

At the bottom of the window, there are navigation controls: 'Records from 1 to 6', 'Page 1', and '100 rows per page'.

Mapping Details

It displays mapping details that includes mapping specification name, version, target update strategy, and lists of target and source tables.

Mapping Specification

It displays the Mapping Specification grid with source and target details.


Under the Mapping Details and Mapping Specification sections, you can click a <Table_Name> or <Column_Name> to view their respective details.

Table Details

To view table details, on the **Mapping Summary** page, click <Table_Name>.

The Table Details page appears. By default, the Impact Analysis tab opens. You can view direct, indirect, and other impacts of the table.

For more information on impact analysis, refer to the [Running Impact Analysis](#) topic.



You can click the following tabs to work on the Table Details page:

- **Data Lineage:** This tab displays the forward and reverse lineage of the table. For more information on lineage of tables, refer to the [Table](#) topic.
- **Extended Properties:** This tab displays the extended properties configured for the table. For more information on configuring extended properties, refer to the [Extending Table Properties](#) topic.
- **Table Properties:** On this tab, you can view the table properties. For more information on table properties, refer to the [Updating Table Properties](#) topic.
- **Columns:** This tab displays a list of columns in the table.
- **Workflow Log:** This tab displays the workflow log of the table. For more information on configuring workflows, refer to the [Using Workflow Manager](#) section.
- **Data Quality:** On this tab, you can preview and profile the data in the table. For more information on previewing and profiling data, refer to the [Previewing Data](#) topic.

- **Documents:** On this tab, you can view or add documents related to the table.
- **Test Specifications:** On this tab, you can view the test cases related to the table. For more information on test cases, refer to the [Creating Test Cases](#) topic.

Column Details

To view column details, on the Mapping Summary page, click <Column_ Name>.

The Column Details page appears. By default, the Impact Analysis tab opens. You can view direct, indirect, and other impacts of the column.

For more information on impact analysis, refer to the [Running Impact Analysis](#) topic.

The screenshot shows the 'Column Details' window for the column 'ID(dbo.ADS_ASSOCIATIONS.Data_Migration.erwinDIS)'. The 'Impact Analysis' tab is active, showing a summary of direct and indirect impacts. The 'Direct Impact' section is expanded, showing three mappings:

#	Project Name	Mapping Name	Target Information	Business Rule			
			Column	Table	Environment	System	
1	A_Project	Erwin_Map	ID_New	dbo.ADS_New_ASSOCIATIONS	Data_Migration	erwinDIS	ABS
2	Erwin_Feb	Integration_Feb	RESOURCEID	dbo.RM_RESOURCE	Integration	Erwin_Sales	
3	Erwin_Project	Child_Map	ID_New	dbo.ADS_New_ASSOCIATIONS	Data_Migration	erwinDIS	

The 'As Target' section shows 'No Records Found'.

You can click the following tabs to work on the Column Details page.

- **Data Lineage:** This tab displays the forward and reverse lineage of the column. For more information on lineage of columns, refer to the [Column](#) topic.

- **Extended Properties:** This tab displays the extended properties configured for the column. For more information on configuring extended properties, refer to the [Extending Column Properties](#) topic.
- **Column Properties:** This tab displays the column properties. For more information on column properties, refer to the [Updating Column Properties](#) topic.
- **Workflow Log:** This tab displays the workflow log of the column. For more information on configuring workflows, refer to the [Using Workflow Manager](#) section.
- **Valid Values:** This tab displays the codesets assigned to the column as valid values. For more information on assigning codesets to columns, refer to the [Assigning Codesets to Columns](#) topic.
- **Documents:** This tab displays the uploaded documents related to the column.

Viewing Mapping Statistics


You can view mapping statistics and view the following information about mapping specifications:

- Total rows
- Number of target tables
- Targets not mapped
- Sources not mapped
- Business rules
- Lookups

To view mapping statistics, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, click the required map.

The Mapping Specification grid appears.



#	Source System Name	Source Environment Name	Source Table Name	Source Column Name	Source Column Data Type	Source Column Length	Business Rule
1	erwinDIS	erwinDIS	dbo.ADS_ASSOCI	ID	bigint	8	ABS
2	erwinDIS	erwinDIS	dbo.ADS_ASSOCI	SOURCE_OBJECT_	bigint	8	ABS
3	erwinDIS	erwinDIS	dbo.ADS_ASSOCI	SOURCE_OBJECT_	bigint	8	ABS

3. click .

The mapping statistics are shown with hyperlinks.

Test Specification		Workflow Log	
Profiles: Default		    	
Source Column Name	Source Column Data Type		
ID	bigint	Total Rows: 6	Rule
		Target Tables: 1	
		Source Tables: 1	
		Targets Not Mapped: 0	
		Sources Not Mapped: 0	
SOURCE_OBJECT_	bigint	Business Rules: 1	
		Possible Truncations: 0	
		Look Ups: 0	

You can click the required hyperlinks to get the detailed information.

Associating Mappings

This section walks you through the process of associating mappings with the following:

- Code Mappings or Code Crosswalks
- Reference Tables
- Requirements

It involves:

- [Associating code maps with data item mappings](#)
- [Associating reference tables with mappings](#)
- [Linking requirements with mappings](#)

Associating Code Maps with Data Item Mappings

A code map can be associated with a data item mapping to standardize data across the organization. These code maps are maintained in Codesets Manager. For more information on codesets and code mappings, refer to the [Using Codesets Manager](#) section.


Before associating a code map with data item mappings, ensure that you publish the code map.

Publishing Code Maps

To publish code maps, follow these steps:

1. Go to **Application Menu > Data Catalog > Codeset Manager > Codeset Mappings**.
2. In the **Code Mappings Workspace** pane, right-click a code map.

The available options appear.



3. Click **Publish**.

The Publish Codeset Map page appears.

4. Enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.


Field Name	Description
Codeset Map Name	Specifies the name of the code map. For example, Gender Crosswalk.
Codeset Map Version	Specifies the new version of the code map. For example, 1.02.
Codeset Map Description	Specifies the description about the code map. For example: The codeset map is the code mappings between the two codesets, Misc Gender Codes and Gender.
Map Version Label	Specifies the version label of the code map. For example, Beta.
Map Changed Description	Specifies the description about the changes made in the code map. For example: Code values were updated.
Publish Environment	Specifies the environment where the code map is being published. For example, test. You can create publish environments in Enterprise Codesets.

Field Name	Description
	For more information on creating publish environments, refer to the Publishing Codesets topic.

5. Click .

The code map is published and it can be found in the Published Code Mappings pane under the selected Publish Environment.

A new version of the code map is created under the Mappings tree.



A published code map can be associated with a mapping in the Mapping Manager. The published code map is available under the Code Mappings Catalogue.

Associating Code Maps

To associate published code maps with data item mappings, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, click the required map.

The Mapping Specification grid appears.

#	Source System Name	Source Environment Name	Source Table Name	Source Column Name	Source Column Data Type	Source Column Length	Business Rule
1	A_System	A_Environment	dbo.CAT_DIALOG	CAT_DIALOG_TAB	int	5	TRUNC
2	erwinDIS	Data_Migration	dbo.ADS_ASSOCI	ID	bigint	80	TRUNC
3	erwinDIS	Data_Migration	dbo.ADS_ASSOCI	SOURCE_OBJECT	bigint	8	ABS
4	A_System	A_Environment	dbo.CAT_DIALOG	CAT_DIALOG_PRC	int	4	

3. Click .

4. In the **Mapping Specification** grid, right-click the header menu.

#	Source System Name	Source Environment Name	Source Table Name	Source Column Name	Source Column Data Type	Source Column Length	Business Rule
1	A_System	A_Environment	dbo.CAT_DIALOG	CAT_DIALOG			TRUNC
2	erwinDIS	Data_Migration	dbo.ADS_ASSOCI	ID			TRUNC
3	erwinDIS	Data_Migration	dbo.ADS_ASSOCI	SOURCE_OBJECT	bigint	8	ABS

5. Select the **CSM Mapping** check box.

The CSM Mapping Column appears in the Mapping Specification grid.

6. In the right pane, expand **Code Mapping Catalogue**.

7. Drag the code map into the **Mapping Specification** grid and drop it under the **CSM Mapping** column for the required row.

Mapping Specification Graphical Designer Test Specification Workflow Log

[Erwin_Map] Profiles: Default

target Column length	Created By	Created Date	CSM Mapping	Last Modified By	Last Modified Date Time	Reference Table
		2019-10-21 14:36:15.057				
	Administrator	2019-10-21 14:36:15.057	Integrated_Map(1.00)	Administrator	2019-12-10 14:49:07.187	
	Administrator	2019-10-21 14:36:15.057		Administrator	2019-12-10 14:49:07.187	

Metadata Catalogue

Code Mappings Catalogue

- Code Mappings
 - C_Name
 - EDW
 - ICD Crosswalks
 - Integrated_Data
 - Mappings
 - Integrated_Map(1.00)
 - Map1(1.00)
 - New_Category

8. Click .

The code map is associated with the data item mappings.


Associating Reference Tables with Mappings

Reference data sets the permissible values for other data fields. To standardize your data, you can associate a reference table with mappings. Ensure that you publish the required reference table before associating it with mappings.

To associate reference tables with Mappings, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, click a map.


The Mapping Specification grid appears.



#	Source System Name	Source Environment Name	Source Table Name	Source Column Name	Source Column Data Type	Source Column Length	Business Rule
1	Erwin_Sales	Integration	dbo.RM_RESOURCEID	RESOURCEID	int	4	FLOOR
2	Erwin_Sales	Integration	dbo.RM_RESOURCENAME	RESOURCENAME	varchar	100	REVERSE
3	Erwin_Sales	Integration	dbo.RM_RESOURCEDESC	RESOURCEDESC	varchar	150	dbo.RM_Resource

3. Click .

4. Right-click the header menu.




#	Source System Name	Source Environment Name	Source Table Name	Source Column Name	Source Column Data Type	Source Column Length	Business Rule
1	Erwin_Sales	Integration	dbo.RM_RESOURCEID	RESOURCEID	int	4	FLOOR
2	Erwin_Sales	Integration	dbo.RM_RESOURCENAME	RESOURCENAME	varchar	100	REVERSE

5. Select the **Reference Table** check box.

The Reference Table column appears in the Mapping Specification grid.

6. Drag the reference table from **Reference Table Catalogue** and drop it on the required row under the **Reference Table** column.

 You can associate multiple source columns with the reference tables.



Target Column	Created By	Created Date	CSM Mapping	Last Modified By	Last Modified Date Time	Reference Table
englh	Administrator	2019-10-21 14:36:15.057	Integrated_Map(1.00)	Administrator	2019-12-10 14:49:07.187	
	Administrator	2019-10-21 14:36:15.057		Administrator	2019-12-10 14:49:07.187	

7. Click .

The reference table is associated with the mappings.


Linking Requirements to Mappings

To ensure enterprise-wide traceability, you can link your functional requirements to data mappings.

To link functional requirements to mappings, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. Click a mapping.

The mapping opens in the detailed view.




The screenshot displays the Mapping Manager interface. The main area shows a table with the following columns: #, Source System Name, Source Environment Name, Source Table Name, Source Column Name, Source Column Data Type, Source Column Length, and Business Rule. The table contains six rows of data:

#	Source System Name	Source Environment Name	Source Table Name	Source Column Name	Source Column Data Type	Source Column Length	Business Rule
1	A_System	A_Environment	dbo.CAT_DIALOG	CAT_DIALOG_TAB	int	4	
2	A_System	A_Environment	dbo.CAT_DIALOG	CAT_DIALOG_PRC	int	4	
3	A_System	A_Environment	dbo.CAT_DIALOG	CAT_DIALOG_TAB	varchar	50	
4	A_System	A_Environment	dbo.CAT_DIALOG	CAT_DIALOG_TAB	varchar	4000	
5	A_System	A_Environment	dbo.CAT_DIALOG	CREATED_BY	varchar	50	
6	A_System	A_Environment	dbo.CAT_DIALOG	CREATED_DATE_TL	datetime	8	

The interface also includes a left sidebar with a tree view of workspace mappings, a top navigation bar with tabs for Mapping Specification, Graphical Designer, Test Specification, and Workflow Log, and a right sidebar with a Metadata Catalogue. The bottom status bar shows 'Records from 1 to 9', 'Page 1', and '100 rows per page'.

3. On the **Mapping Specification** tab, right click the grid header.
A list of header columns appears.




4. Scroll down the list and select the **sSpecification Artifact** check box.

The specification Artifact column becomes visible on the Mapping Specification tab.

5. In the right pane, click **Specification Artifact Catalogue**.

6. Expand the project that contains the required specification.

7. Drag and drop the specification on the **Specification Artifacts** column in the required row.



8. Click .

Requirements are linked to the selected mapping.

Publishing and Creating Versions of Mappings

This section walks you through the process of publishing mappings to corresponding source or target production environments. Production environments of the source and the target are defined in the Metadata Manager. You can also create new versions of the mappings while archiving the older versions.

It involves:

- [Creating versions of maps](#)
- [Base-lining Projects](#)
- [Comparing two different mapping versions](#)
- [Publishing mappings](#)
- [Restoring archived maps as active](#)


Creating Versions of Maps

You can create new version of maps and track history of changes made in the mapping specification. You can also notify and send mail comments to all the project users about the creation of new version. For more information on notifying project users, refer to the [Configuring Notifications](#) topic.

To create versions of maps, follow these steps:


1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, right-click a map.

The available options appear.



3. Click **New Version**.

The New Version page appears.



4. Enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.


Field Name	Description
Mapping Name	Specifies the mapping specification name. For example, EDW_PROD_IDS_Benefits_Detail.
Mapping Version	Specifies the new version of the mapping specification. For example, 1.02.
Mapping Description	Specifies the description about the mapping. For example: This is a map between EDW source and IDS target systems.
Version Label	Specifies the version label of the mapping specification. For example, Beta. For more information on configuring version display of mapping specifications, refer to the Configuring Version Display topic.
Changed Description	Specifies the description of the changes made in the mapping specification. For example: A business rule for a source column was added.
Mail Comments	Specifies the mail comments, which can be sent to the project users through an email notification. For example: Target update strategy is not updated.

Field Name	Description
	For more information on configuring notifications, refer to the Configuring Notifications topic.

5. Click .


A new version of the map is created and the previously active version moves under the archive folder.

 Archived maps are in read-only mode and cannot be edited.



The screenshot shows the 'Mapping Manager' interface. On the left, a tree view under 'Workspace Mappings' shows a folder 'Mappings' containing 'Projects' and 'Mappings'. Under 'Mappings', there is a folder 'M_Map (v1.01)' which contains 'MappingTargets' and an 'Archive' folder. The 'Archive' folder contains 'M_Map (v1.00)'. On the right, the 'Mapping Specifica' pane shows a table with the following data:

#	Source System Name
1	New_Erwin
2	New_Erwin
3	New_Erwin



4. Enter **Version Label**, **Change Description**, and **Mail Comments**.

For example:

- **Version Label** - Beta.
For more information on version display, refer to the [Configuring Version Display](#) topic.
- **Change Description** - Business rule for all the source column was changed to ASCII.
- **Mail Comments** - The target update strategy needs to be updated.
For more information on notifying project users, refer to the [Configuring Notifications](#) topic.

5. Click .

The project is base-lined and all the maps in the project now have the same version. Project users receive email notifications about the base-lining and mail comments, if you enable notifications for it. For more information on configuring notifications, refer to the [Configuring Notifications](#) topic.

Comparing Two Different Mapping Versions

You can use the advanced mapping comparison ability to quickly and efficiently compare any two mapping versions. You can view the changes on a row by row basis and improve your debugging ability.

To compare two different mapping versions, follow these steps:


1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, select two mapping versions.



Use shift keys to select the two mapping versions.

3. Right-click the selection.

The available options appear.



4. Click **Compare To**.

The Compare To page appears. All the changes are highlighted in red color in the comparison report.



To exclude exporting common rows in the report, select **Exclude Common Rows Export**.

Use the following options to export the comparison report:

- To export the report in the PDF format, click .
- To export the report in the XLSX format, click .
- To export the report in the HTML format, click .


Publishing Mappings

You can publish a map on an effective date and enter publishing notes for a record. Before publishing mappings, ensure that the source and the target environments have their corresponding production environments.

Publishing Mappings


To publish mappings, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, right-click a map.



3. Click **Publish Map**.

The Publish Map page appears.



4. Enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.

Field Name	Description
Mapping Name	Specifies the mapping specification name. For example, EDW_PROD_IDS_Benefits_Detail. It is autopopulated and you cannot edit this field.
Mapping Version	Specifies the version of the mapping specification. For example, 1.00. It is autopopulated. For more information on configuring version display of maps, refer to the Configuring Version Display topic.
Version Label	Specifies the version label of the mapping specification. For example, EDW_PROD_IDS_Benefits_Detail (Alpha). For more information on configuring version display of maps, refer to the Configuring Version Display topic.
Effective Date	Use  to enter the effective date of publishing. For example, 04/02/2020.

Field Name	Description
Change Description	Specifies the description for changes made in the mapping specification. For example: Business rule was modified from ABORT to ASCII for the source column ID.
Publish Notes	Specifies the publish notes about the mapping specification. For example: The mapping specification is approved for publishing on 1 Feb 2020.


5. Click .

The mapping is published on the effective date and saved in the **Published Mappings** pane. The source and the target environments in the published mapping are updated to their corresponding production environments. All previously published versions of the same mapping are stored in the History folder. A published mapping cannot be edited.

A new version of the mapping is automatically created in **Workspace Mappings** that can be edited.

To view published map details, in the **Published Mappings** pane, click the <Mapping_Name>.

The business view of the mapping appears which can be used to run impact analysis, lineage analysis, and data quality etc. For more information on business view, refer to the [Opening Business View](#) topic.




Updating Publishing Details

To update publishing details of published maps, follow these steps:


1. In the **Workspace Mappings** pane, right-click the required project.

The available options appear.



2. Click **Edit Published Maps**.

The Edit Publish Mappings page appears. You can use **Filter by Effective Date** to filter the mappings based on the effective publishing date.



3. In the **Publish Tree** pane, select the required published map.

Now, you can update Publish Notes and Effective Date.

4. Click .


The publishing details of the map is updated.

Restoring Archived Maps As Active


When you create a new version of a map, the older version is archived. The archived map is in read-only mode and cannot be edited. You can restore an archived map as an active map and work on the map.

To restore archived maps as active, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, right-click the required archived map.



The Restoring Archived Mapping as Active page appears.




3. Enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.

Field Name	Description
Mapping Name	Specifies the mapping specification name. For example, EDW_PROD_IDS_Benefits_Detail.
Mapping Version	Specifies the new version of the mapping specification. For example, 1.02.
Mapping Description	Specifies the description of the mapping. For example: This is a map between EDW source and IDS target systems.
Version Label	Specifies the version label of the mapping specification. For example, Beta. For more information on configuring version display of mapping specifications, refer to the Configuring Version Display topic.
Changed Description	Specifies the description of the changes made in the mapping specification. For example: A business rule for a source column was added.
Mail Com-	Specifies the mail comments which can be sent to the project users

Field Name	Description
ments	<p>through an email notification.</p> <p>For example: Target update strategy is not updated.</p> <p>For more information on configuring notifications, refer to the Configuring Notifications topic.</p>

4. Click .

The archived map is restored as a new version and the existing active map is archived.



The screenshot shows the 'Mapping Manager' window in the 'DATA INTELLIGENCE SUITE'. The left pane shows a tree view of 'Workspace Mappings' with 'M_Map (v1.02)' selected. The right pane shows the 'Mapping Specification' table for '[M_Map]'.

#	Source System Name	Source Environment Name
1	New_Erwin	Erwin_Environment
2	New_Erwin	Erwin_Environment
3	New_Erwin	Erwin_Environment

Exporting Mapping Specifications

This section walks you through the process of exporting mapping specifications. Once the mappings are approved for coding requirements like ETL Jobs, SQL Scripts, Python Code, Spark Code, DDL Scripts, or Stored Procedures then you can export them.

You can export mapping specifications to:

- [the proprietary XML format](#)
- [generate ETL jobs](#)


Proprietary XML Format

Once the mappings are approved for coding, you can export the mappings as coding requirements in the XML format.

To export mapping specifications into proprietary XML format, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, click a map.

The Mapping Specification grid appears.




The screenshot shows the 'Mapping Manager' window in the 'DATA INTELLIGENCE SUITE'. The 'Workspace Mappings' pane on the left shows a tree view with 'Erwin_Map (v1.03)' selected. The main area displays the 'Mapping Specification' grid for the selected map. The grid has the following columns: #, Source System Name, Source Environment Name, Source Table Name, Source Column Name, Source Column Data Type, Source Column Length, Business Rule, and Extended Business Transformation. The data rows are as follows:

#	Source System Name	Source Environment Name	Source Table Name	Source Column Name	Source Column Data Type	Source Column Length	Business Rule	Extended Business Transformation
1	erwinDIS	erwinDIS	dbo.ADS_ASSOCI	ID	bigint	8	ABS	
2	erwinDIS	erwinDIS	dbo.ADS_ASSOCI	SOURCE_OBJECT_	bigint	8	ABS	
3	erwinDIS	erwinDIS	dbo.ADS_ASSOCI	SOURCE_OBJECT_	bigint	8	ABS	

3. Click .

The Export Window page appears.




4. Select **Mapping Manager XML** and click .



5. Click .

6. Select the required mappings and click .

The following notification appears.



7. Click the **Download file** hyperlink.


A ZIP file is downloaded. Unzip this file to use the mapping specification in the XML format.

ETL Jobs

Once the mappings are considered 'approved for coding', you can export the mappings as coding requirements to automatically generate ETL/ELT jobs. The ETL jobs can be generated for tools, such as Informatica PowerCenter, IBM DataStage, Microsoft SQL Server SSIS, and Talend.

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, click the required map.


The **Mapping Specification** grid appears.




#	Source System Name	Source Environment Name	Source Table Name	Source Column Name	Source Column Data Type	Source Column Length	Business Rule
1	erwinDIS	erwinDIS	dbo.ADS_ASSOCI	ID	bigint	8	ABS
2	erwinDIS	erwinDIS	dbo.ADS_ASSOCI	SOURCE_OBJECT_	bigint	8	ABS
3	erwinDIS	erwinDIS	dbo.ADS_ASSOCI	SOURCE_OBJECT_	bigint	8	ABS

3. Click .

The **Export Window** page appears.




4. Click the **ETL Engineering** tab.




5. Select the required ETL tool and click .

The Multi Mapping page appears.



6. Select the mapping and click .

The following notification appears.



7. Click the **Download File** hyperlink.

The mapping specification is exported.

Creating and Managing Test Cases for Mappings

You can create test cases for testing data mappings and ETL processes in the Mapping Manager for:

- Projects
- Mappings

The test cases created at project-level apply to all the mappings created under the project. Whereas, map-level test cases apply to particular map.

Creating and managing test cases involves:

- [Creating test cases](#)
- [Adding validation steps](#)
- [Adding documents](#)
- [Managing test cases](#)

Creating Test Cases

In the Mapping Manager, you can define test cases at:

- [Project-level](#)
- [Map-level](#)


At the project-level, you can create multiple test cases. Whereas, at the map-level, you can create a single test case.

Creating Project-Level Test Cases

To create project-level test cases, follow these steps.

1. Go to **Application Menu > Data Catalog > Mapping Manager > Workspace Mappings**.
2. Expand a project and click the **Test Case** node.

The Test Case Summary page appears.



3. Click

The Add New Test Case page appears.



Test cases created for a project are also applicable to the mappings under a project.

4. Enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.

Field Name	Description
Test Case Name	Specifies the name of the test case. For example, Verifying the Completeness of Source Metadata.
Test Case Label	Specifies the unique label for the test case. For example, Source Metadata.
Type of Testing	Specifies the type of testing. For example, Metadata Testing.
Test SQL Script	Specifies the SQL script required in the test execution. For example, select * from dbo.ADS_ASSOCIATIONS.
Description	Specifies the test objective in brief. For example: The objective of the test case is to verify the completeness of source metadata.
Expected Result	Specifies the expected result of the test case in detail. For example: The source table should have 50 columns.
Actual Result	Specifies the actual test result after the execution of the test.

Field Name	Description
	For example: The source table has 39 columns.
Testing Comments	Specifies the testing comments about the test case. For example: The source metadata was scanned from a Sql Server database.

5. Click **Save and Exit**.

The test case is created and added to the **Test Cases** node.

Creating Map-Level Test Cases

To create map-level test cases, follow these steps.

1. Go to **Application Menu > Data Catalog > Mapping Manager > Workspace Mappings**.
2. Click a mapping and click the **Test Specification** tab.


It displays the existing project-level test cases.

The screenshot shows the 'Mapping Manager' application window. The 'Test Specification' tab is active, displaying a table of existing test cases. Below the table, there is a 'Test Case Overview' section with input fields for 'Test Case Id', 'External Test Case Id', 'Test Case Name', and 'Test Case Label'. The 'Test Case Name' field contains the value 'T_Name'.

#	Test Case Id	Test Case Name	Test Case Label	Type of Testing	Description	Priority	Test Case Status	Approved	Map
1	9	T_Name							

3. Click .

The Add New Test Case page appears.



4. Enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.

Field Name	Description
Test Case Name	Specifies the name of the test case. For example, Verifying the Completeness of Source Metadata.
Test Case Label	Specifies the unique label for the test case. For example, Source Metadata.
Priority	Specifies the priority of the test case. For example, High. Priority for business rules and functional test cases can be medium or higher.
Type of Testing	Specifies the type of testing. For example, Metadata Testing.
Extendable	Specifies whether the test case is visible even when this map is archived. A map is archived whenever you create a new version of the map.
Test SQL Script	Specifies the SQL script required in the test execution. For example, select * from dbo.ADS_ASSOCIATIONS.

Field Name	Description
Description	Specifies the test objective in brief. For example: The objective of the test case is to verify the completeness of source metadata.
Expected Result	Specifies the expected result of the test case in detail. For example: The source table should have 50 columns.
Actual Result	Specifies the actual test result after the execution of the test. For example: The source table has 39 columns.
Testing Comments	Specifies the testing comments about the test case. For example: The source metadata was scanned from a Sql Server database.
Test Case Status	Specifies the status of the test case. For example, Passed.
Approved	Specifies whether the test case is approved.

5. Click **Save and Exit**.

The test case is added under the Test Specification tab.

Once a test case is created, you can enrich it by:

- [Adding validation steps](#)
- [Adding documents](#)

[Managing test cases](#) involves:

- Updating test case status
- Approving test cases
- Exporting test cases
- Deleting test cases

Adding Validation Steps

You can add multiple validation steps to the test cases at:

- [Project-level](#)
- [Map-level](#)

You can also specify actual and expected results for each validation step.

Adding Validation Steps to Project-Level Test Cases

To add validations to project-level test cases, follow these steps.


1. In the **Workspace Mappings** pane, expand a project and click the **Test Case** node. The Test Case Summary pane appears.

The screenshot shows the Mapping Manager interface. On the left, the 'Workspace Mappings' pane is expanded to show a tree view of projects and test cases. The 'Test Cases' node is selected. The main pane, titled 'Test Case Summary', displays a table with the following data:

#	Test Case Id	Test Case Name	Test Case Label	Type of Testing	Description	Created By
1	9	T_Name				Administrator


Below the table, there are tabs for 'Test Case Overview', 'Validation Steps', and 'Document Upload'. The 'Test Case Overview' tab is active, showing input fields for 'Test Case Id' (9), 'Test Case Label', and 'Test Case Name*' (T_Name). There are 'Save' and 'Cancel' buttons at the bottom right of the overview pane.

2. In the bottom pane, click the **Validation Steps** tab.



3. Click .

The Add Validation Steps page appears.



4. Enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.

Field Name	Description
Validation Step Type	Specifies the type of validation step. For example, Data Check.
Step Name	Specifies the unique name of the step. For example, Validating Number of Columns.
Description	Specifies the description of the validation step. For example: This step validates the number of columns in the source metadata.
Expected Result	Specifies the expected result in detail. For example: The source table, dbo.ADS_ASSOCIATIONS should have 50 columns.
Actual Result	Specifies the actual test result after the execution of the test. For example: The source table contains 50 columns.
Test Step Comments	Specifies the comments about the step. For example: The source metadata was scanned from a Sql Server database.

5. Click **Save**.


The validation step is added to the test case.

Adding Validation Steps to Map-Level Test Cases


To add validations to map-level test cases, follow these steps.

1. In the **Workspace Mappings** pane, expand a project and click a mapping.
2. Click the **Test Specification** tab.
3. Double-click a map-level test case.

The Test Case Summary pane appears.




- In the bottom pane, click the **Validation Steps** tab.
The Validation Steps tab appears.



- Click .

The Add New Step page appears.



6. Enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.

Field Name	Description
Step Name	Specifies the unique name of the step. For example, Validating Number of Columns.
Validation Step Type	Specifies the type of the validation step. For example, Data Check.
Step Status	Specifies the status of the step. For example, Passed.
Description	Specifies the description about the validation step. For example: This step validates the number of columns in the source metadata.
Expected Result	Specifies the expected result in detail. For example: The source table, dbo.ADS_ASSOCIATIONS should have 50 columns.
Actual Result	Specifies the actual test result after the execution of the test. For example: The source table contains 50 columns.
Expected Result	Enter the expected result in detail, including the error-message that is displayed on screen.

Field Name	Description
Test Step Comments	Specifies the comments about the step. For example: The source metadata was scanned from a Sql Server database.

7. Click **Save**.

The validation step is added to the test case.

Adding Documents

You can add supporting documents such as text files, audio files, video files, and so on to a test case at:


- [Project-level](#)
- [Map-level](#)

Adding Documents to Project-Level Test Cases

To add documents to project-level test cases, follow these steps.

1. In the **Workspace Mappings** pane, click the **Test Cases** node of a project.

The Test Case Summary pane appears.



The screenshot shows the Mapping Manager application interface. On the left, the 'Workspace Mappings' pane is expanded to show a tree view of projects and test cases. The 'Test Cases' node under the 'Erwin_Project (2)' is selected. The main area displays the 'Test Case Summary' pane, which contains a table with the following data:

#	Test Case Id	Test Case Name	Test Case Label	Type of Testing	Description	Created By
1	9	T_Name				Administrator

Below the table, there are tabs for 'Test Case Overview', 'Validation Steps', and 'Document Upload'. The 'Test Case Overview' tab is active, showing input fields for 'Test Case Id' (9), 'Test Case Label', and 'Test Case Name*' (T_Name). There are 'Save' and 'Cancel' buttons at the bottom right of the form.

2. In the bottom pane, click **Document Upload** and click .

The Add Test Case Document page appears.

The screenshot shows a web form titled "Add Test Case Document". At the top right, there are "Save" and "Cancel" buttons. The form contains the following fields:

- Document Name***: A text input field with an asterisk indicating it is mandatory.
- Document Owner**: A text input field.
- Document Object**: A text input field with a "Drag-n-Drop files here or click to select files for upload." instruction and an upload icon.
- Document Link**: A text input field.
- Intended Use Description**: A rich text editor with a toolbar containing icons for text color, background color, bold, italic, underline, bulleted list, numbered list, link, unlink, and undo.
- Approval Required Flag**: A checkbox.


3. Enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.

Field Name	Description
Document Name	Specifies the name of the added document to the test case. For example, Source Metadata Details.
Document Object	Drag and drop document files or use  to select and upload documents.
Document Owner	Specifies the document owner's name. For example, John Doe.
Document Link	Specifies the URL of the document. For example, https://drive.google.com/file/d/2sC2_SZlyeFKI70On-b5YkMBq4ptA7jhg5/view
Intended Use Description	Specifies the intended use of the document. For example: The document has information about the source metadata.
Approval Required Flag	Specifies whether the document requires approval. Select the Approval Required Flag check box to select the doc-

Field Name	Description
	Document status.
Document Status	Specifies the status of the document. For example, In Progress. This field is available only when the Approval Required Flag check box is selected.

4. Click **Save**.

The document is added to the test case and saved under the **Document Upload** tab.



Once a supporting document is added, use the following options:

Preview (📄)

Use this option to preview the document.

Edit (✎)

Use this option to update the document details.

Delete (✖)


Use this option to delete the document that is not required.

Adding Documents to Map-Level Test Cases


To add documents to map-level test cases, follow these steps.

1. In the **Workspace Mappings** pane, click a mapping and click the **Test Cases** node of a project.
2. Double-click a map-level test case.

The Test Overview page appears.



3. Click the **Document Upload** tab.



4. Click .

The Add Test Case Document page appears.

5. Enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.

Field Name	Description
Document Name	Specifies the name of the physical document being attached to the test case. For example, Source Metadata Details.
Document Object	Drag and drop document files or use  to select and upload document files.
Document Owner	Specifies the document owner's name. For example, John Doe.
Document Link	Specifies the URL of the document. For example, https://drive.google.com/file/d/12sC2_SZlYeFKI70On-b5YkMBq4ptA7jhq5/view
Intended Use Description	Specifies the intended use of the document. For example: The document has information about the source metadata.

Field Name	Description
Approval Required Flag	Specifies whether the document requires approval. Select the Approval Required Flag check box to select the document status.
Document Status	Specifies the status of the document. For example, In Progress. This field is available only when the Approval Required Flag check box is selected.

6. Click **Save**.

The document is added to the test case.

Once a supporting document is added, use the following options:

Preview()

Use this option to preview the document.

Edit ()

Use this option to update the document details.

Delete()

Use this option to delete the document that is not required.

Managing Test Cases

Managing [project-level](#) or [map-level](#) test cases involve:


- Updating test cases
- Exporting test cases
- Deleting test cases

Managing Project-Level Test Cases

To update project-level test cases, follow these steps

To update test cases, follow these steps:

1. In the **Workspace Mappings** pane, click the **Test Cases** node.



2. In the **Test Case Summary** pane, click the required test case.
3. In the **Test Case Overview** tab, click .
4. Update the necessary information.
For more information on fields, refer to [Creating Test Cases](#) topic.


To export a test case, click the test case in the **Test Case Summary** pane, and click .

To delete a test case, click the test case in the **Test Case Summary** pane, and click .

Managing Map-Level Test Cases

To update map-level test case, follow these steps:

1. In the **Workspace Mappings** pane, click a map and click the **Test Specification** tab.




The screenshot shows the 'Mapping Manager' application window. The 'Workspace Mappings' pane on the left shows a tree view with 'Erwin_Map (v1.04)' selected. The main area is titled 'Test Specification' and contains a table with the following data:

#	Test Case Id	Test Case Name	Test Case Label	Type of Testing	Description	Priority	Test Case Status	Approved
1	9	T_Name						<input type="checkbox"/>
2	11	Erwin_Test					UnSpecified	<input checked="" type="checkbox"/>
3	12	New_Association	Association	Source to Target	Data Migration			<input type="checkbox"/>


2. Click .

The Map and Test Cases Status page appears. You can update test case status in the Test Cases Grid and Map Test Status in the bottom pane.




To approve map-level test cases, follow these steps:

1. In the **Workspace Mappings** pane, click a mapping, and click the **Test Specification** tab.



2. Click .

The Approved Test Cases page appears.



3. Select the check box against the test case under the **Approved** column.
4. Click **Save**.

To export a test case, click the test case in the **Test Case Summary** pane, and click .


To delete a test case, click the test case in the **Test Case Summary** pane, and click .

Viewing Mapping Manager Dashboard

The Mapping Manager Dashboard displays metrics that help you analyze and track your projects and mappings. It presents this information using charts and graphs.

To access Mapping Manager Dashboard, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.




The screenshot displays a web interface for the Mapping Manager Dashboard. At the top, there is a blue header bar labeled "Project Summary" with a dropdown arrow. Below this is a table with four columns: "#", "Project Name", "Project Description", and "Project Ow". The table contains several rows of data, including entries for "WhatfixIntegrator", "ABC", "TechPubs", and "Tech Pubs Online". The "Project Description" column for rows 6, 7, and 9 contains HTML code for an embedded editor. To the right of the table, there is a vertical red button labeled "Self Help". At the bottom of the interface, there is a blue bar labeled "Mapping Manager Dashboard" with an upward-pointing arrow.

#	Project Name	Project Description	Project Ow
	<input type="text"/>	<input type="text"/>	<input type="text"/>
6	WhatfixIntegrator	<iframe id="editorembd" tabindex="-1" style="position: absolute; width: 0px; height: 0px; border: none; left: -1000px; top: -1000px;"></iframe>	
7	ABC	<iframe id="editorembd" tabindex="-1" style="position: absolute; width: 0px; height: 0px; border: none; left: -1000px; top: -1000px;"></iframe>	
8	TechPubs		
9	Tech Pubs Online	<iframe id="editorembd" tabindex="-1" style="position: absolute; width: 0px; height: 0px; border: none; left: -1000px; top: 0px;"></iframe>	

2. Click the **Mapping Manager Dashboard** pane.

The Mapping Manager Dashboard appears.



It displays the following panes:

- **Statistics:** It displays a snapshot of statistics related to mapping projects.
- **Mapping Summary:** It displays the number of mappings in each project.
- **Mapping Status:** It displays the number of mappings in each mapping state.
- **Proactive Impact Analysis - Truncation Impacts:** It displays the number of instances of source truncation in each project.
- **Project Overview:** It displays the number of subjects, mappings, and assigned users in each project.
- **Mapping Classification:** It displays the number of active, archived, and published mappings in each project.
- **Mapping Assignments:** It displays the number of designers, approvers, developers, and testers assigned to mappings
- **Sources/Targets Not Mapped:** It displays the number of sources and targets not mapped in each project.
- **Test Case Status:** It displays the number of test cases under a test case status.
- **Project Test Cases:** It displays the number of test cases in each project.
- **User Test Cases:** It displays the number of test cases created by each user.

Statistics

The Statistics pane displays the total number of projects, subjects, mappings, source tables, target tables, possible truncations, and users. For example, in the following image there are sixteen projects, eighty-six mappings, forty-four source tables, forty-six target tables, eighty-four possible truncations, and four users.


Statistics	Σ Projects: 16	Σ Subjects: 0	Σ Mappings: 86	Σ Source Tables: 44	Σ Target Tables: 46	Σ Possible Truncations: 84	Σ Users: 4	
------------	--------------------------------	-------------------------------	--------------------------------	-------------------------------------	-------------------------------------	--	----------------------------	---

You can click the hyperlink to view further details. For example, if you click the hyperlink for the Target Tables. The Target Table Details page appears.

Target Tables Details			
#	Table Name	Environment Name	System Name
1	Account	erwinSales	SQLTechPubs
2	Account	Presentation Layer	TABLEAU
3	Account	Presentation Layer	TABLEAU
4	Account	PRESENTATION LAYER	TABLEUAU
5	Account	TechPubs	PRESENTATION LAYER
6	Account	TechPubs	Salesforce
7	APPQOSSYS.WLM_CLASSIFIER_PLAN	TechPubs	Oracle
8	APPQOSSYS.WLM_CLASSIFIER_PLAN	TechPubs	Oracle

Mapping Summary

The Mapping Summary pane displays the number of mappings in each project in a pie chart. To open the chart in the Dashboard View, click the pie-chart.




Each slice of the pie chart corresponds to a project. You can drill down and view detailed information in the list format. To view detailed information about mappings in a project, click a slice. The Details View tab opens. It displays project name, subject name, map name, and map version.

Mapping Summary				
Dashboard View		Details View		
#	Project Name	Subject Name	Map Name	Map Version
	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
1	Lineage Demo		Informatica_m_CBDR_BDM_CASA	1.00
2	Lineage Demo		Talend_staging	1.00
3	Lineage Demo		test	1.00
4	Lineage Demo		TestDataMap1	1.00
5	Lineage Demo		TestMap2	1.00
6	Lineage Demo		TestMap3	1.00
7	Lineage Demo		Tech Pubs	1.00
8	Lineage Demo		Create a New Map	1.00
9	Lineage Demo		how	1.00
10	Lineage Demo		Account Tableau Report	1.02
11	Lineage Demo		Line Mapping	1.00
12	Lineage Demo		map_map	1.00

Mapping Status

The Mapping Status pane displays the number of mappings under each mapping state in a pie chart. By default there are two mapping states, In Progress and Approved. You can create your own mapping states depending on your requirements. For more information on creating mapping states, refer to the [Configuring Mapping State Settings](#) topic.

To open the chart in the Dashboard View, click the pie chart.




Each slice corresponds to a mapping state. You can drill down and view detailed information in the list format. To view detailed information about maps in a mapping state, click a slice of the pie-chart.

Mapping Status					
Dashboard View		Details View			
#	Project Name	Subject Name	Map Name	Map Version	State Name
	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
1	erwinDIS		Data Integration	1.00	Approved
2	erwinDIS		SalesforceIntegratic	1.00	Approved
3	erwinDIS		BugTrial	1.00	Approved
4	erwinDIS		erwinSalesIntegratic	1.01	Approved

Proactive Impact Analysis - Truncation Impacts

The Proactive Impact Analysis - Truncation Impacts pane displays the number of instances where the target column length is smaller than the source column length in each project in a pie-chart. To open the chart in the Dashboard View, click the pie chart.




Each slice of the pie chart corresponds to a project. You can drill down and view detailed information in the list format.

To view detailed information about truncated sources in a project, click a slice of the pie chart. The Details View tab opens. It displays project name, subject name, map name, source and target column names.

#	Project Name	Subject Name	Map Name	Source Table Name	Target Table Name	Source Column Name	Target Column Name	Source Column Length	Source Column Precision	Target Column Length	Target Column Precision	Map Version
1	Test Source		mo_STGTPCH_SF10000	TPCH_SF10000.LINEITEM	stg.STG_LINEITEM	L_LINENUMBER	LINEITEM_HSH	38		16		1.00
2	Test Source		mo_STGTPCH_SF10000	TPCH_SF10000.LINEITEM	stg.STG_LINEITEM	L_LINENUMBER	LINEITEM_HSH_DIFF	38		16		1.00
3	Test Source		mo_STGTPCH_SF10000	TPCH_SF10000.LINEITEM	stg.STG_LINEITEM	L_ORDERKEY	TPCH_SF10000.ORDER	38		16		1.00
4	Test Source		mo_STGTPCH_SF10000	TPCH_SF10000.LINEITEM	stg.STG_LINEITEM	L_PARTKEY	TPCH_SF10000.PART_H	38		16		1.00

Project Overview

The Project Overview pane displays the number of subjects, mappings, and assigned users in each project in a bar graph. To open bar graph in the Dashboard View, click the bar graph.



Each set of three bars corresponds to a project. You can view detailed information in the list format. To view the Detailed information about mappings, subjects, or assigned users of a project click the corresponding bar. For example, if you click the mappings bar then the Mappings tab opens.


Dashboard View		Details View		
Mappings		Subjects	Assigned Users	
#	Project Name	Subject Name	Map Name	Map Version
	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
1	erwinDIS		Data Integration	1.00
2	erwinDIS		SalesforceIntegration	1.00
3	erwinDIS		BugTrial	1.00
4	erwinDIS		TechPubsBUGTrial	1.00
5	erwinDIS		erwinSalesIntegration	1.01

To view a list of subjects, click the **Subjects** tab.

To view a list of the assigned users, click the **Assigned Users** tab.

Mapping Classification

The Mapping Classification pane displays the number of active, archived, and published mappings in each project in a bar graph. To open the bar graph in the Dashboard View, click the bar graph.




Each set of three bars corresponds to a project. You can drill down and view detailed information. To view detailed information about status of mappings in a project, click a bar. The Details View tab opens. It displays project name, subject name, map name, map version, and status.

#	Project Name	Subject Name	Map Name	Map Version	Status	Map Published
1	erwinDIS		BugTital	1.00	Active	
2	erwinDIS		Data Integration	1.00	Active	
3	erwinDIS		erwinSalesIntegration	1.00	Passive	✓
4	erwinDIS		erwinSalesIntegration	1.01	Active	
5	erwinDIS		SalesforceIntegration	1.00	Active	
6	erwinDIS		TechPubsBUgTital	1.00	Active	

Mapping Assignments

The Mapping Assignments pane displays the number of designers, approvers, developers, and testers assigned to mappings in each project in a bar graph. For more information on mapping assignments, refer to the [Assigning Mapping Specifications to Users](#) topic.

To open the bar graph in the Dashboard View, click the bar graph.




Each set of three bars corresponds to a project. You can drill down and view detailed information in the list format. To view detailed information about mapping assignments in a pro-

ject, click a bar. The Detail View tab opens. It displays project name, subject name, map name, assigned user's full name, and assignment status.

Dashboard View		Details View						
#	Project Name	Subject Name	Map Name	Map Description	Assignee Full Name	Responsibility	Assignment Status	Last Modified By
	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
1	erwinDIS		Data Integr		Administrator	Mapping D	In Progress	Administrator
2	erwinDIS		SalesforceL		Administrator	Mapping D	In Progress	Administrator
3	erwinDIS		BugTrial	Testing for c	Saras Ojha	Mapping A	Not Started	Administrator
4	erwinDIS		BugTrial	Testing for c	Administrator	Mapping D	In Progress	Administrator
5	erwinDIS		BugTrial	Testing for c	Jane Doe	Mapping E	Not Started	Administrator
6	erwinDIS		BugTrial	Testing for c	public - De	Mapping T	Not Started	Administrator
7	erwinDIS		TechPubsB	TechPubsB	Administrator	Mapping D	In Progress	Administrator
8	erwinDIS		erwinSales		Administrator	Mapping D	In Progress	Administrator

Sources/Targets Not Mapped

The Sources/Targets Not Mapped pane displays the number of sources and targets not mapped in each project in a bar graph. To open the bar graph in the Dashboard View, click the bar graph.




Each set of two bars corresponds to a project. You can drill down and view detailed information in the list format. To view the detailed information about sources and target not mapped in a project, click a bar. The Details View tab opens. It displays project name, map name, and target and source details.

Dashboard View		Details View					
Targets Not Mapped			Sources Not Mapped				
#	Project Name	Subject Name	Map Name	Target System Name	Target Environment Name	Target Table Name	Target Column Name
	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
1	Lineage Demo		Account Tableau	Snowflake	Snowflake_STG	stg.STG_LINEITEM	SQN_NUM
2	Lineage Demo		Account Tableau	Snowflake	Snowflake_STG	stg.STG_LINEITEM	LOAD_DTS
3	Lineage Demo		Account Tableau	Snowflake	Snowflake_STG	stg.STG_LINEITEM	REC_SRC
4	Lineage Demo		Account Tableau	Snowflake	Snowflake_STG	stg.STG_LINEITEM	MLTID
5	Lineage Demo		Account Tableau	Snowflake	Snowflake_STG	stg.STG_LINEITEM	BKCC
6	Lineage Demo		Account Tableau	Snowflake	Snowflake_STG	stg.STG_LINEITEM	BWSC
7	Lineage Demo		Account Tableau	Snowflake	Snowflake_STG	stg.STG_LINEITEM	SQN_NUM
8	Lineage Demo		Account Tableau	Snowflake	Snowflake_STG	stg.STG_LINEITEM	LOAD_DTS
9	Lineage Demo		Account Tableau	Snowflake	Snowflake_STG	stg.STG_LINEITEM	REC_SRC
10	Lineage Demo		Account Tableau	Snowflake	Snowflake_STG	stg.STG_LINEITEM	MLTID
11	Lineage Demo		Account Tableau	Snowflake	Snowflake_STG	stg.STG_LINEITEM	BKCC
12	Lineage Demo		Account Tableau	Snowflake	Snowflake_STG	stg.STG_LINEITEM	BWSC
13	Lineage Demo		map.map(1.00)	erwin DM	DM Landing	Citizens	CitizenID

Test Case Status

The Test Case Status pane displays the number of test cases under a test case status in a pie chart. To open the chart in the Dashboard View, click the pie chart.




Each slice of the pie chart corresponds to a test case status. You can drill down and view detailed information in the list format. To open the detailed information about test cases, click a slice. The Details View tab opens. It displays project name, map name, and test case names.

Dashboard View		Details View				
#	Project Name	Subject Name	Map Name	Test Case Id	Test Case Name	Test Case Label
	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
1	Lineage Demo			3	ETL Testing	Alpha
2	Lineage Demo		Account Tablea	4	Account_Tak	
3	erwinDIS			1	Validating sc	Alpha

Project Test Cases

The Project Test Cases pane displays the number of test cases in each project in a pie-chart. To open the chart in the Dashboard View, click the pie chart.




Each slice in the pie chart corresponds to a project. You can drill down and view detailed information in the list format.

To view the detailed information about test cases in a project, click a slice of the pie chart. The Details View tab opens. It displays project name, subject name, map name, test case ID, test case name, and test case label.

#	Project Name	Subject Name	Map Name	Test Case Id	Test Case Name	Test Case Label
1	erwinDS			1	Validating sour	Alpha
2	erwinDS		Data Integration	2	Customer-Acc	Alpha

User Test Cases

The User Test Cases pane displays the number of test cases created by each user in a pie chart. To open the chart in the Dashboard View, click the pie chart.



Each slice of the pie chart corresponds to a user. You can drill down to view detailed information in the list format.

To view the detailed information about test cases created by a user, click a slice of the pie chart. The Details View tab opens. It displays project name, subject name, map name, test case ID, test case name, and test case label.

#	Project Name	Subject Name	Map Name	Test Case Id	Test Case Name	Test Case Label
	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
1	Lineage Demo			3	ETL Testing	Alpha
2	erwinDIS			1	Validating sour	Alpha
3	erwinDIS		Data Integration	2	Customer-Acc	Alpha