



erwin Data Intelligence

User Guide

Release v14.0

Legal Notices

This Documentation, which includes embedded help systems and electronically distributed materials (hereinafter referred to as the Documentation), is for your informational purposes only and is subject to change or withdrawal by Quest Software, Inc and/or its affiliates at any time. This Documentation is proprietary information of Quest Software, Inc and/or its affiliates and may not be copied, transferred, reproduced, disclosed, modified or duplicated, in whole or in part, without the prior written consent of Quest Software, Inc and/or its affiliates

If you are a licensed user of the software product(s) addressed in the Documentation, you may print or otherwise make available a reasonable number of copies of the Documentation for internal use by you and your employees in connection with that software, provided that all Quest Software, Inc and/or its affiliates copyright notices and legends are affixed to each reproduced copy.

The right to print or otherwise make available copies of the Documentation is limited to the period during which the applicable license for such software remains in full force and effect. Should the license terminate for any reason, it is your responsibility to certify in writing to Quest Software, Inc and/or its affiliates that all copies and partial copies of the Documentation have been returned to Quest Software, Inc and/or its affiliates or destroyed.

TO THE EXTENT PERMITTED BY APPLICABLE LAW, QUEST SOFTWARE, INC. PROVIDES THIS DOCUMENTATION AS IS WITHOUT WARRANTY OF ANY KIND, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NONINFRINGEMENT. IN NO EVENT WILL QUEST SOFTWARE, INC. BE LIABLE TO YOU OR ANY THIRD PARTY FOR ANY LOSS OR DAMAGE, DIRECT OR INDIRECT, FROM THE USE OF THIS DOCUMENTATION, INCLUDING WITHOUT LIMITATION, LOST PROFITS, LOST INVESTMENT, BUSINESS INTERRUPTION, GOODWILL, OR LOST DATA, EVEN IF QUEST SOFTWARE, INC. IS EXPRESSLY ADVISED IN ADVANCE OF THE POSSIBILITY OF SUCH LOSS OR DAMAGE.

The use of any software product referenced in the Documentation is governed by the applicable license agreement and such license agreement is not modified in any way by the terms of this notice.

The manufacturer of this Documentation is Quest Software, Inc and/or its affiliates Provided with Restricted Rights. Use, duplication or disclosure by the United States Government is subject to the restrictions set forth in FAR Sections 12.212, 52.227-14, and 52.227-19(c)(1) - (2) and DFARS Section 252.227-7014(b)(3), as applicable, or their successors.

Copyright © 2024 Quest Software, Inc. and/or its affiliates All rights reserved. All trademarks, trade names, service marks, and logos referenced herein belong to their respective companies.

Contact erwin

Understanding your Support

Review [support maintenance programs and offerings](#).

Registering for Support

Access the [erwin support](#) site and click Sign in to register for product support.

Accessing Technical Support

For your convenience, erwin provides easy access to "One Stop" support for [erwin Data Intelligence \(erwin DI\)](#), and includes the following:

- Online and telephone contact information for technical assistance and customer services
- Information about user communities and forums
- Product and documentation downloads
- erwin Support policies and guidelines
- Other helpful resources appropriate for your product

For information about other erwin products, visit <http://erwin.com/>.

Provide Feedback

If you have comments or questions, or feedback about erwin product documentation, you can send a message to distechpubs@erwin.com.

News and Events

Visit [News and Events](#) to get up-to-date news, announcements, and events. View video demos and read up on customer success stories and articles by industry experts.

Contents

Introduction	7
Architecture	8
User Interface	12
Application Menu	14
Quick Start	18
Resource Management	18
Metadata Management	18
Data Literacy	18
Reference Data Management	18
Life Cycle Management	19
Mapping Management	19
Creating Roles	20
Creating Users and Assigning Roles	24
Creating Systems	29
Creating Environments	35
Scanning Metadata	43
Creating Maps	47
Defining Transformations	52
Mapping Source and Target	55
Categorizing Codesets and Defining Code Values	58
Publishing Codesets	65
Creating Code Crosswalks (Mappings)	69

Associating Code Mappings with Data Item Mappings	78
Publishing Code Maps	78
Associating Code Maps	80
Creating Business Terms	83
Setting Up Associations for Business Terms	86
Creating Test Cases	89
Documenting Requirements	92
Linking Requirements to Mappings	97
Running Lineage Analysis	99
Running Impact Analysis	105
Exporting Mapping Specifications to ETL Tools	109

Introduction


erwin Data Intelligence (erwin DI) is a unified platform for data professionals that offers metadata-driven framework to:

- **Discover data:** Identify metadata from isolated data management sources.
- **Harvest data:** Automate metadata collection from the isolated data management sources, and consolidate it into a single source.
- **Discover assets:** Search, discover, access, and analyze assets across the organization.
- **Structure and deploy data sources:** Connect physical metadata to specific data models, business terms, definitions, and reusable design standards.
- **Analyze metadata:** Analyze the harvested data to understand its attributes and relation to business.
- **Map data flows:** Identify data integration possibilities, and track its flows and transformations.
- **Govern data:** Develop a governance model to manage standards, policies, and best practices, and associate them with physical assets.
- **Socialize data:** Empower stakeholders with role-based data availability in one place.
- **erwin Data Marketplace:** Shop, share, and compare enterprise datasets at a centralized location. Create and manage datasets, view insights, raise data literacy, and ensure governance.
- **Data Quality:** Data quality analysis provides in-depth analysis of your environments, tables, and columns.

This section introduces you to [erwin DI architecture](#), its [user interface \(UI\)](#), and the tasks that you can accomplish using it.

Architecture

To get you started with erwin Data Intelligence (erwin DI), this topic gives you an overview of erwin DI architecture and its modules. The following diagram shows a high-level architecture and data flow.



The following sequence gives a high-level understanding of how the modules interact in a typical data integration project:

1. Scan metadata from data sources.
2. Connect your environment with DQLabs and get data quality for technical assets.
3. Create business assets and associate them with technical assets.
4. Create marketplace assets, set up association, and add tasks.
5. Add tasks to collaborate with team members.
6. Tag your assets for asset discovery and sensitivity.
7. Create source data to target data maps, and track data flow and transformations.

Architecture

8. Analyze lineage, impact, and mind maps.
9. Capture functional requirements.
10. Associate requirements with mappings.
11. Define codesets and perform code crosswalks (mappings).
12. Associate code crosswalks with mappings.
13. Validate and manage reference data.
14. Associate reference data with Mappings.
15. Generate code for:
 - ETL jobs
 - SQL scripts
 - Python code
 - Spark code
 - DDL scripts
 - Stored procedures


erwin DI consists feature rich modules that are categorized as core and add-on modules.

- Core modules perform the major functions of erwin DI offering.
- Add-on modules offer additional functions on top of the core functions.

The following table gives an overview of modules and their functions.

Module	Type	Function
Discover Assets	Core	Use Discover Assets for asset (technical, business, and mapping assets) discovery, lineage, mind maps, impact analysis, and tasks.
My Action Center	Core	Use My Action Center to track and manage tasks for better collaboration with team members.
Resource Manager	Core	Use the Resource Manager to add application users and create roles for them here. You can also manage access-level permissions.
Metadata Manager	Core	Use the Metadata Manager to harvest source or target metadata from a data source. You can run impact and lineage analysis to have better control on a data integration project.

Architecture

Module	Type	Function
Mapping Manager	Core	Use the Mapping Manager to perform source to target mappings. You can also link code mapping objects, reference data objects, and requirements to the mappings.
Business Glossary Manager	Core	<p>Use the Business Glossary Manager to create, manage, and collaborate on common business vocabulary across the organization. You can also view lineage maps to understand how semantic definitions are related to physical data dictionaries, data mappings, and data lineages.</p>  <p>Business Glossary Manager is core module of erwin DI, and it is available as an add-on.</p>
Data Marketplace	Core	Use the Data marketplace to create, manage, share, and compare enterprise datasets and other marketplace assets at a centralized location.
Codeset Manager	Add-On	Use the Codeset Manager to manage your enterprise and legacy codesets. You can perform code mappings (crosswalks) and manage them.
Reference Data Manager	Add-On	Use the Reference Data Manager to manage your reference data (tables). You can run validation rules on the reference data and perform data quality checks. Further, you can associate codesets with the reference data.
Requirements Manager	Add-On	Use the Requirements Manager to standardize functional requirements documentation. Further, you can link requirements with data mappings.
Test Manager	Add-On	Use the Test Manager to manage test specifications created under Metadata Manager and Mapping Manager.
Release Manager	Add-On	Use the Release Manager to release data mappings, database objects, and release notes to standardize the release process.
Reports Manager	Add-On	Use the Reports Manager to create statistical reports and evaluate your team's productivity.
Workflow Manager	Add-On	Use the Workflow Manager to manage Business Glossary Manager, Metadata Manager, and Mapping Manager workflows. You can also create custom workflows and monitor their execution.
Data Quality	Add-On	Use DQLabs to profile and analyze your metadata and gain in-depth

Architecture

Module	Type	Function
	On	knowledge on key data quality parameters such as DQ Score. Then, you can view these data quality parameters for environments, tables, and columns in erwin DI.
Enterprise Tags	Add-On	Use Enterprise Tags to classify and organize all business assets, technical assets, and mapping assets.

For more information on erwin DI's user interface, refer to the [User Interface](#) topic.

User Interface

To get you started with using erwin Data Intelligence (erwin DI), this topic walks you through the erwin DI UI, its components, and their functions.

Once you have installed erwin DI, follow these steps to access and use it:

1. Start erwin DI.

The Login page appears. It displays your license information at the bottom of the page.

2. Enter your credentials.
3. Select the **I accept & agree to the terms of the EULA** check box.
4. Click **Sign In**.

After a successful log in, the following page appears.

Alternatively, you can setup a Single Sign On (SSO) for login. For more details on configuring SSO, refer to the [SSO Configuration Guide](#).



By default, the landing module is set to the Mapping Manager. You can change this under your [account settings](#).

User Interface

The screenshot shows the erwin Data Intelligence Mapping Manager interface. It features a top navigation bar with the erwin logo, the title 'Mapping Manager', a search bar, and utility icons. A left sidebar displays 'Workspace Mappings' with a tree view of various projects. The main area shows a 'Project Summary' table with columns for Project Name, Project Description, Project Owner, Subject Count, Mapped Count, Created By, Created Date Time, Last Modified By, and Last Modified Date Time. A bottom status bar includes 'Published Mappings' and 'Mapping Manager Dashboard'.


#	Project Name	Project Description	Project Owner	Subject Count	Mapped Count	Created By	Created Date Time	Last Modified By	Last Modified Date Time
1	Lineage Demo			0	14	Administrator	26-02-2020 04:01:32	Administrator	26-02-2020 04:01:32
2	Test Source			0	3	Administrator	26-02-2020 04:02:38	Administrator	26-02-2020 04:02:38
3	TestData Map			0	30	Administrator	26-02-2020 04:03:32	Administrator	26-02-2020 04:03:32
4	TestMap			0	4	Administrator	26-02-2020 04:04:19	Administrator	26-02-2020 04:04:19
5	WhatfixTrial			0	0	Administrator	16-03-2020 05:30:34	Administrator	16-03-2020 05:30:34
6	WhatfixIntegration			0	0	Administrator	16-03-2020 06:12:05	Administrator	16-03-2020 06:12:05
7	ABC			0	3	Administrator	17-03-2020 05:34:23	Administrator	17-03-2020 05:34:23
8	TechPubs			0	6	Administrator	15-04-2020 09:56:37	Administrator	15-04-2020 09:56:37
9	Tech Pubs Online			0	6	Administrator	23-04-2020 07:28:42	Administrator	23-04-2020 07:28:42
10	Test			0	4	Administrator	23-04-2020	Administrator	23-04-2020


UI Section	Function
1-Navigation Pane	Application Menu: Click this icon to access modules of erwin DI. For more information, refer to the Application Menu section.
	Messaging Center: Click this icon to view notifications and messages.
	Search: Use this feature to search for a keyword based on the module that you are working in.
	Search Options: Click this icon to set the search criteria.
	Help: Click this icon to access the context sensitive help.
	Bookshelf: Click this icon to access the erwin DI bookshelf.
	Options: Click this icon to manage your profile options. <ul style="list-style-type: none"> Suggestions: Send an enhancement request to our team through an email.

User Interface

UI Section	Function
	<ul style="list-style-type: none">▪ Change Password: Change your password.▪ My Dashboard: View your activity report and mapping assignments.▪ My Profiles: View your profiles.▪ My Workflow: View and update your workflow queues.▪ Logout: Log out of the application.
2-Workspace Mappings	Use this pane to browse and work on different projects and mappings.
3-Published Mappings	Use this pane to browse through published mappings and export them, if needed.
4-Central Pane	Based on your selection in the Workspace Mappings pane, use this pane to view or work on the data.
5-Mapping Manager Dashboard	Use this pane to view statistics related to mappings and projects in the Mapping Manager.

Application Menu

To access the Application Menu, click .



The Application Menu classifies the functional module in different categories. Select a category to view its modules. Refer to the following table for a list of categories and their relevant modules.

User Interface

Category	Modules
Discover Assets	<ul style="list-style-type: none">Discover Assets
My Action Center	<ul style="list-style-type: none">My Action Center
Data Catalog	<ul style="list-style-type: none">Resource ManagerMetadata ManagerMapping ManagerCodeset ManagerReference Data ManagerRequirements ManagerRelease ManagerTest Manager
Data Marketplace	<ul style="list-style-type: none">Data Marketplace
Data Literacy	<ul style="list-style-type: none">Business Glossary ManagerAIMatch
Data Quality	<ul style="list-style-type: none">Data Quality
Miscellaneous	<ul style="list-style-type: none">Enterprise TagsReporting ManagerWorkflow ManagerDownload TemplatePluginsAutomation Framework
Settings	<ul style="list-style-type: none">Mapping MangerMetadata ManagerCodeset Manager

User Interface

Category	Modules
	<ul style="list-style-type: none"><li data-bbox="500 260 760 296">▪ Release Manager<li data-bbox="500 317 711 352">▪ Test Manager<li data-bbox="500 373 792 457">▪ Requirements Manager<li data-bbox="500 478 764 562">▪ Business Glossary Manager<li data-bbox="500 583 719 619">▪ Miscellaneous<li data-bbox="500 640 630 676">▪ License<li data-bbox="500 697 630 732">▪ Plugins

Quick Start

This section gives a quick hands-on experience of erwin Data Intelligence (erwin DI). It walks you through the operations that you would perform regularly and helps you understand Metadata Management, Mapping Management, Data Literacy, Data Governance, and Life Cycle Management.

The following are the tasks that you would be performing regularly in a data integration project.

Resource Management

[Creating Roles](#)

[Creating Users and Assigning Roles](#)

Metadata Management

[Creating Systems](#)

[Creating Environments](#)

[Scanning Metadata](#)

[Performing Lineage Analysis](#)

[Performing Impact Analysis](#)

Data Literacy

[Creating Business Terms](#)

[Defining Associations for Business Terms](#)

Reference Data Management

[Categorizing Codesets and Defining Code Values](#)

[Publishing Codesets](#)

[Creating Code Crosswalks \(Mappings\)](#)

Life Cycle Management

[Documenting Requirements](#)

[Creating Test Cases](#)

Mapping Management

[Creating Projects and Maps](#)

[Defining Transformations](#)

[Mapping Source and Target](#)

[Associating Code Crosswalks with Data Item Mappings](#)

[Linking Requirements to Mappings](#)

[Exporting Mapping Specifications to ETL Tools](#)

Creating Roles

Use roles to assign access-level permissions to users. While few roles are available by default in erwin DI, you can create custom roles.



The Administrator role is system-generated and you cannot edit or delete it.

To create roles, follow these steps:


1. Go to **Application Menu > Data Catalog > Resource Manager**.

The Resource Manager page appears. By default the Users tab opens.

Users	Roles	Profiles	Governance Responsibilities	Access Rights Report
SETTINGS	User Details	User Account Activities	User Assignments	Access Rights
USERS (26)	Login Type	Database	Telephone Number	9999999999
AD Administrator Administrator - Default System	User ID	Administrator	Email ID	abc@abc.com
DV dvaghani Daya Vaghani	User Full Name	Administrator - Default System U	Alternate Telephone Number	9999999999
ES esimpson Erica Simpson	Password	/ / / / / / / / / /	Manager Name	
JA jadams Joey Adams	Mobile	9999999999	Company	erwin, Inc.
	Company Title	Administrator	Created Date Time	26-02-2020 03:48:28
	Default Role	Admin	Last Modified Date Time	26-02-2020 03:48:28
	Created By	System	Theme	erwin
	Last Modified By	System	Language Preference	English

2. Click the **Roles** tab.

Creating Roles



3. Click .

The Role page appears.

Creating Roles

The screenshot shows a web form titled "Role" with the following fields and components:

- Role Name***: A text input field with a red asterisk. A note below it states: "Note: Role Name once created cannot be edited".
- Business Name**: A text input field.
- Role Type**: A dropdown menu currently showing "DI".
- Role Description**: A large text area for entering a description.
- Permissions Tree**: A tree view showing a hierarchy of permissions:
 - Permissions (expanded)
 - Resource Manager
 - Metadata Manager
 - Mapping Manager
 - Codeset Manager
 - Release Manager
 - Reference Data Manager
 - Automation Framework
 - Test Manager

Buttons for "Save" and "Cancel" are located at the top right of the form.

4. Enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.

Tab	Description
Role Name	Specifies the user-defined role name. For example, Data Steward_AsiaPacific.
Business Name	Specifies the user-defined business name. For example, Data_Steward_Mapping.
Role Type	Specifies the role type <ul style="list-style-type: none"> ▪ DI: Indicates that the role is available only for a Data Intelligence (DI) user ▪ BU: Indicates that the role is available only for a Business User (BU)
Role Description	Specifies the role description. For example, This role has access to the Resource Manager and Mapping Manager.

Creating Roles

5. Under the **Permissions Tree** section, select the check box for the modules or the permission object to which you want to grant access to the role.
6. Click **Save**.

A role is created and added to the Roles list.

Users		Roles	
AD	Administrator Type: DI		Role
DO	Data Owner_GER Type: DI		Role Name
DO	Data Owner_RO Type: DI		Business Name
DO	Data Owner_UK Type: DI		Role Type
DS	Data Steward_AsiaPacific Type: DI		Role Description
DS	Data Steward_GER Type: DI		Permissions Tree
DS	Data Steward_Hung Type: DI		
DS	Data Steward_RO Type: DI		

Once roles are created, you can create users and assign roles to them. For more information on managing resources, refer to the [Managing Resources](#) section.

Creating Users and Assigning Roles

Users are used to grant members of your team access to erwin DI and your projects. While a few users are available by default, you can create users for your organization using the Resource Manager. While you create users, you also assign them roles to define their access-level permissions.

When you upgrade from 11.5 or lower app version, the Business User Portal (BUP) users migrate to the latest erwin DI version as BU user type.




The Administrator user is available by default and you cannot edit or delete this user.

To create users, follow these steps:

1. Go to **Application Menu > Data Catalog > Resource Manager**.

By default, the Users tab opens.



2. Click **+**.

The New User page appears.

Creating Users and Assigning Roles

3. Enter appropriate values in the fields. Refer to the following table for field descriptions.



The fields marked with an asterisk (*) is mandatory.

Field Name	Description
Login Type	<p>Specifies whether the user type is Database, LDAP (Lightweight Directory Access Protocol), SAML (Security Assertion Markup Language), or NON LOGIN.</p> <p>For example, Database.</p> <ul style="list-style-type: none"> ▪ Database: Select this option if the user authentication is through the credentials created in the Resource Manager. ▪ LDAP: Select this option if the user authentication is through a directory server, such as MS Active Directory, OpenLDAP or OpenDJ. ▪ SAML: Select this option if the user authentication is through SAML attributes. <p>For more details on configuring SSO, refer to the SSO Configuration Guide.</p>


Creating Users and Assigning Roles

Field Name	Description
	<ul style="list-style-type: none"> ▪ NON LOGIN: Select this option if the user is not required to log on to the application.
User ID*	Specifies the user name of the user to log on to erwin DI. For example, lmicahal.
User Full Name*	Specifies the user's full name. For example, Luqman Michal.
Password*	Specifies the password to log on to erwin DI. For example, Luqman@1. The administrator provides a default password, which can be changed later. The administrator can also enforce a password policy. For more information on enforcing password policy, refer to the Configuring Settings topic.
Mobile	Specifies the user's valid mobile number. For example, +658374414288.
Company Title	Specifies the user's company title or designation. For example, Data Administrator.
Default Role	Specifies the default role of the user. For example, Data Steward_RO.
Landing Module	Specifies the landing module for the user. For example, Mapping Manager. The Landing Module is the first page displayed when a user logs in.
User Roles*	Select roles under Available Roles list-box and move them to Assigned Roles list-box using the arrows (➡ or ➡➡). Similarly, to change existing role assignment, select roles under Assigned Roles list-box and move them back to Available Roles list-box using the arrows (⬅ or ⬅⬅). For adding a new role under the Available Roles list-box, refer to the Creating Roles topic. You can assign the Legacy Data Steward role to a user. This enables you

Creating Users and Assigning Roles

Field Name	Description
	to assign this user as a Data Steward in the Metadata Manager and Reference Data Manager.
Telephone Number	Specifies the valid telephone number of the user. For example, 1-800-783-7946.
Email ID*	Specifies the user's email address. For example, l.michal@mauris.edu
Alternate Telephone Number	Specifies the user's valid alternate telephone number. For example, 1-802-456-7946.
Manager Name	Specifies the name of the user's reporting manager. For example, John Doe.
Company	Specifies the name of the user's company. For example, ABC Consulting Services.
Send Email	Specifies whether to send email to the user's email ID. Select the Send Email check box to send an email notification to the user's email ID. For more information on configuring notifications, refer to the Configuring Notifications topic.
Theme	Specifies the theme for the user to set the appearance of erwin DI. By default, it is set to erwin (Web Blue).
Language Preference	Specifies the language preferred by the user. For example, English. For more information on language settings, refer to the Configuring Language Settings topic.
User Type	Specifies the user type. <ul style="list-style-type: none">▪ DI: Indicates the user type is Data Intelligence (DI), and the users have access to DI, and BU modules▪ BU: Indicates that the user type is Business User (BU), and the users have access to BU module

Creating Users and Assigning Roles

Field Name	Description
User Image	Specifies the physical image file being attached to the user. Drag and drop a user's image file or click  to select and upload the image file.

4. Click .

A new user is created and added to the Users list.

For more information on managing resources, refer to the [Managing Resources](#) section.

Creating Systems


You can harvest (scan) metadata from data sources in the Metadata Manager. The scanned metadata is stored in a hierarchical manner (System > Environment > Table > Column) in the Data Catalog.

A System can contain multiple environments and in a typical data integration project a system can be a source or target type. You can create a system and specify data steward, system owner, and its business purpose etc.

Apart from creating systems, you can manage other system configurations using **Metadata Options** available in the top-right corner.

To create systems, follow these steps:

1. Go to **Application Menu > Data Catalog > Metadata Manager > Explore**.
2. In the Data Catalog pane, click **Metadata Options**.



3. Click **New System**.

Creating Systems

The New System page appears.

4. Enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.

Field Name	Description
System Name	Specifies the physical name of the system. For example, Enterprise Data Warehouse. For more information on naming conventions, refer to the Best Practices section.
Server Platform	Specifies the server platform of the system. For example, Windows.
DBMS Platform	Specifies the DBMS platform of the system (if the system is an RDBMS source). For example, SQL Server.
File Management Type	Specifies the file management system (if the system is a file-based source). For example, MS Excel.
Owner Name	Specifies the full name of the system owner. For example, Talon Smith.


Creating Systems

Field Name	Description
Telephone Number	Specifies the telephone number of the system owner. For example, 1-800-783-7946.
Primary Move Type (Source/Target)	Specifies whether the system is source, target, or both. Valid values are: <ul style="list-style-type: none"> ▪ Source ▪ Target ▪ Both
Server OS version	Specifies the OS version of the system's server. For example, Windows Server 2012 R2.
DBMS Version	Specifies the DBMS version of the system (if the system is an RDBMS source). For example, SQL Server 2017.
File Location	Specifies a file path (if the system is a file-based source). For example, C:\Users\Talon Smith\erwin\Mike - Target System
Release	Specifies the system release including the point release number. For example, Oracle 18c.
Email Address	Specifies the system owner's email address. For example, talon.smith@mauris.edu
Sensitive Data Indicator (SDI) Classification	Specifies the sensitivity classification of the system. Also, you can add multiple classifications to the system. For example, PHI, Confidential. For more information on configuring Sensitive Data Indicator (SDI) classifications, refer to the Configuring Sensitivity Classifications topic.
Sensitive Data Indicator Description	Specifies the description of the SDI classification.
Data Steward	Specifies the name of the data steward responsible for the system. For example, Jane Doe.

Creating Systems

Field Name	Description
	<p>Users assigned with the Legacy Data Steward role appear as drop down options. You can assign this role to a user in the Resource Manager.</p> <p>To assign data steward, select a data steward from the drop down options.</p>
DQ Score	<p>Specifies the overall data quality score of the system.</p> <p>For example, High (7-8).</p> <p>For more information on configuring DQ scores, refer to the Configuring Data Profiling and DQ Scores topic.</p>

5. Click the **Miscellaneous** tab or click .



6. Enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.

Field Name	Description
ESB Platform Type	Specifies the enterprise platform bus type (if the system is an ESB)

Creating Systems

Field Name	Description
	source). For example, Mule.
ESB Q Manager Name	Specifies the ESB queue manager's name of the system (if the source is an ESB). For example, John Doe.
Total DBSize	Specifies the total physical size of the database. For example, 198 GB.
Total Number of Tables	Specifies the total number of tables associated with the system. For example, 300.
Definition of the Day	Specifies the definition of the system at the end of the day. For example: Extraction of details from the source system is complete.
Batch Extract Window	Specifies the daily batch extract window of the system. For example: Batch extract from the source system is scheduled at 3:30 P.M. everyday.
Average User	Specifies the average number of system users. For example, 30.
Average Concurrent Users	Specifies the average number of concurrent system users. For example, 15.
Special Instructions	Specifies any special instructions or comments about the system. For example: The system acts as a source for creating the mapping specification.
Business Purpose	Specifies the DBMS platform of the system (if the system is an RDBMS source). For example, SQL Server.

7. Click .

A new system is created.


Creating Systems

Alternatively, before saving this system, you can add a new environment and configure the connections. To setup an environment, click [→](#) to view the New Environment page.


Once a system is created, you can create environments under it and scan metadata from different database types. For more information on managing metadata, refer to the [Managing Metadata](#) section.

Creating Environments

After creating a system in the Metadata Manager, you can create environments under the system. An environment can be created for different database types and flat files by fulfilling prerequisites and providing the connection parameters.

1. Go to **Application Menu > Data Catalog > Metadata Manager > Explore**.
2. In the Asset Catalog pane, hover over the system card and click .

The system details page appears and displays available environments in the Data Catalog pane.




The screenshot shows the 'erwin DI Suite' interface. The 'Data Catalog' pane on the left lists environments: erwin_Sales (v1.00), erwinHR (v1.00), and _Local (v1.01). The main pane displays the 'Environment Listing' table with the following data:

#	Environment Name	Environment Type	DBMS Name	DBMS Schema Name	IP Address	Port	La Dc
1	_Local	erwin DM Mart - C	N/A		N/A	N/A	03-
2	erwin_Sales		MS Excel File	dbo			12-

Creating Environments

3. Click **Options**.


The available options appear.



4. Click **New Environment**.

The New Environment page appears and displays supported database in the Data-sources tab.


Creating Environments




5. Click a datasource, the Configuration Details tabs appears.
The screenshot below displays connection details for Sql Server. The connection details vary based on database selection.

Creating Environments


Alternatively, enter a keyword in the search bar to search for datasources. Enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.

Field Name	Description
Datasource Type	<p>Specifies the datasource (database) type from where you wish to scan metadata. You can change the datasource type using the drop down list.</p> <p>For example, Sql Server.</p> <p>Depending upon your choice of database type, you need to provide additional fields in the Connection Properties tab.</p> <div style="background-color: #e6f2ff; padding: 10px; border: 1px solid #add8e6;"> <p> For SQL Server (Windows Authentication), Sybase, HP Vertica, and Netezza databases, the TestConnectionQuery option is selected by default to validate the internal connection. The system displays exceptions if this option is not selected.</p> </div>

Creating Environments




Field Name	Description
	 There are no additional fields for MS Excel File, and XSD.
System Environment Name	<p>Specifies the unique name of the environment.</p> <p>For example, EDW-Test.</p> <p>The environment name supports - (hyphen), ((opening parenthesis),) (closing parenthesis), / (slash), # (hash), . (full stop), [] (left and right square brackets), ! (exclamation mark), + (plus), % (percentage), ~ (tilde), ; (semicolon), , (comma), = (equals sign), ^ (circumflex accent), and {} (left and right curly brackets) as special characters.</p> <p>For more information on naming conventions, refer to the Best Practices section.</p>
System Environment Type	<p>Specifies the type of the environment.</p> <p>For example, development, test, or production.</p>
Server Platform	<p>Specifies the server platform of the environment.</p> <p>For example, Windows.</p>
Server OS Version	<p>Specifies the OS version of the environment's server.</p> <p>For example, Windows Server 2012 R2.</p>
File Management Type	<p>Specifies the file management system (if the environment is a file-based source).</p> <p>For example, MS Excel.</p>
File Location	<p>Specifies a file path (if the environment is a file-based source).</p> <p>For example, C:\Users\Jane Doe\erwin\Mike - Target System</p>
Production System Name	<p>Specifies the system name being associated with the environment as the production system.</p> <p>For example, Enterprise Data Warehouse.</p>
Production Environment Name	<p>Specifies the environment name being associated with the environment as the production environment.</p> <p>For example, EDW-PRD.</p>
Version Label	<p>Specifies the version label of the environment to track change history.</p> <p>For example, Alpha.</p>

Creating Environments


Field Name	Description
	For more information on configuring version display, refer to the Configuring Version Display of the Environments topic.
Enable DQ Sync	<p>Specifies whether to sync data quality analysis results from DQLabs. To view data quality analysis, ensure that you have configured DQLabs connection setting in erwin DI. For more information, refer to the Configuring DQLabs topic.</p> <div style="border: 1px solid #ccc; background-color: #f0f8ff; padding: 10px; margin-top: 10px;">  <p>Data quality analysis is available for environments using Oracle, Salesforce, Snowflake, MySQL, MSSQL, Hadoop, and PostgreSQL database types.</p> </div>
Sensitive Data Indicator (SDI) Classification	<p>Specifies the sensitivity data indicator (SDI) classification of the environment. Also, you can add multiple classifications to the environment. For example, PHI, Confidential.</p> <p>For more information on configuring SDI classifications, refer to the Configuring Sensitivity Classifications topic.</p>
Sensitive Data (SDI) Indicator Description	Specifies the description of the SDI classification.
Business Entity Type	Specifies the database type of business entity.

6. Click [→](#) to navigate to the Connection Properties tab. Different datasource types have different prerequisites and connection parameters. See the list below for datasource type and its connection parameters:
 - [SQL Server - via SQL or Window authentication mode](#)
 - [Oracle and Oracle RAC](#)
 - [MySQL](#)
 - [Snowflake](#)

Creating Environments

- [MS Dynamics CRM \(and other datasources\)](#)
 - [SAP ECC R/3 and IS-U Metadata via JCO Driver](#)
7. Click  to test the connection.
- If the connection with database is established successfully then a success message pops up.
8. Click  to save and continue to **Miscellaneous** tab.
Or, click  to save and exit.
9. On the Miscellaneous tab, enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.

Field Name	Description
Intended Use Description	Specifies the description about the objective of the environment. For example: The environment contains the source metadata for the data integration project.
Environment Notes	Specifies relevant notes about the environment. For example: The environment uses Sql Server as database to scan the metadata.
Approval Instructions	Specifies any instructions for the environment's approval. For example: The environment must contain 50 tables from erwin DI database.

10. Click  to save and exit.
- A new environment is created.
- Once an environment is created, you can scan source or target metadata from the database type.

Different database types have different prerequisites and connection parameters:

- [SQL Server - via SQL or Window authentication mode](#)
- [Oracle and Oracle RAC](#)
- [MySQL](#)
- [Snowflake](#)

Creating Environments

- [MS Dynamics CRM](#)
- [SAP ECC R/3 and IS-U Metadata via JCO Driver](#)


Scanning Metadata

After creating systems and environments, the next logical step is to scan source and target metadata. Ensure that the environment database type and connection parameters are correct and the environment is able to establish connection with the database.

To scan source or target metadata, follow these steps:

1. Go to **Application Menu > Data Catalog > Metadata Manager > Explore**.
2. On the Explore tab, click an environment tile.
3. Click **Options**.


The available options appear.



4. Click **Scan Metadata**.

Scanning Metadata


The <Data_Base> Metadata Scan-Step1 page appears. For example, if it is the SQL Server environment, then the SqlServer Metadata Scan - Step1 page appears.



5. In the **Database Schema(s)** pane, select the database schemas.
6. In the **Metadata Content** pane, select the appropriate **Import Metadata Options**.
Refer to the following table for the descriptions of the metadata import options.


Import Metadata Options	Description
Add New	This option adds new objects to the existing object list. The existing metadata is not updated.
Update Existing + Add New	This option adds new objects to the existing list and at the same time the existing metadata is also updated.
Update Existing + Add New + Invalidate	This option adds new objects to the existing list, updates existing and invalidates table/column during the scanning process.
Delete & Reload	This option deletes all existing metadata and scans only the new objects that have been selected.

Scanning Metadata

Import Metadata Options	Description
Import Comments	Select the check box to import comments.
Import Sensitive Data	Select the check box to import sensitivity classification of the metadata from the data source. <div style="border: 1px solid #ccc; background-color: #e6f2ff; padding: 5px; margin-top: 10px;">  This option is available for SQL, Oracle, and Snowflake environments. </div>
Table(s)	Select the check box to import Tables.
View(s)	Select the check box to import Views.
Synonym(s)	Select the check box to import Synonyms.
Version Environment	Select the check box to create a version of the environment.

7. Click .

The <Database_Name> Metadata Scan Step-2 page appears. It pulls up the objects selected in Metadata Scan Step-1, such as Tables, Views and Synonyms.



8. Select the required objects.

9. Click .

The metadata is scanned successfully and saved under the environment node.

For more information on managing metadata, refer to the [Managing Metadata](#) section.

Scanning Metadata

You can also import metadata from:


- [MS Excel File](#)
- [JSON](#)
- [CSV \(Flat File\)](#)
- [XMI](#)
- [MS Access File](#)
- [XSD](#)

Creating Maps

Maps are categorized under projects and a project can have multiple maps. The maps are stored in a hierarchical manner, Projects > Mappings. Source to target mappings are performed in maps. You can create maps under a new or existing projects.

To create maps under a new project, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. Under the **Workspace Mappings** pane, right-click the **Projects** node.



3. Click **Create Project**.

The Create Project page appears.

Creating Maps

4. Enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.

Field Name	Description
Project Name	Specifies the name of the project. For example, Data Lake Migration. For more information on naming conventions, refer to the Best Practices section.
Description	Specifies the description of the project. For example: The project contains the mapping specifications for the sales data migration.
Project Manager Name	Specifies the project manager's name. For example, John Doe.
Business Sponsor Name	Specifies the business sponsor of the project. For example, ABC Consulting Services.
Project ETL	Specifies the ETL tool assigned to the project. For example, Informatica Pseudocode.
Cost Center	Specifies the cost center of the project. For example, Finance and Accounting.
IT Sponsor Name	Specifies the IT sponsor of the project. For example, XYZ IT Services.


Creating Maps

Field Name	Description
Enable display of Transformation without pseudocode	Specifies whether the transformation is displayed without pseudocode. Switch Enable display of Transformation without pseudocode to Yes to display transformation without pseudocode.

5. Click **Save and Exit**.

A new project is created and stored in the project tree.

6. Right-click the project.



7. Click **New Map**.

Creating Maps

The New Mapping Wizard appears.

- Enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.

Field Name	Description
Mapping Name	Specifies the mapping specification name. For example, EDW_PROD_IDS_Benefits_Detail. For more information on naming conventions, refer to the Best Practices section.
Mapping Version	Specifies the version of the mapping specification. For example, 1.00. It is autopopulated. For more information on configuring version display of maps, refer to the Configuring Version Display topic.
Sync Source Metadata	Switch Sync Source Metadata to ON to sync source metadata with the mapping.
Sync Target Metadata	Switch Sync Target Metadata to ON to sync target metadata with the mapping.

Creating Maps

Field Name	Description
Mapping Description	Specifies the description about the mapping. For example: This is a map between EDW source and IDS target systems.
Mail Comments	Specifies the mail comments, which can be sent to the project users through an email notification. For example: Source and target have identical columns, hence they can be mapped using auto-map technique. For more information on configuring notifications, refer to the Configuring Notifications topic.

9. Click **Finish**.

A new map is created and saved under the map tree.

For more information on performing source to target mappings, refer to the [Creating and Managing Mapping Specifications](#) section.


Defining Transformations

Transformations specify rules that derive values from source columns to get the required values in target columns. You can define enterprise-level and project-level transformations. These transformations can be used as business rules and extended business rule transformations in mapping specifications. Ensure that you define transformations for the same ETL option as that of your mapping project.

To define transformations, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, click any one of the following:
 - **Transformations node:** Click this option to define enterprise-level transformations.
 - **Transformations node under a project:** Click this option to define project-level transformations.

For example, if you click the Transformations node, then the Transformation Details page appears.



#	Transformation Name	SSIS Pseudocode	Informatica Pseudocode
1	1-DataGov(HighDate:12/31/9999)		To_date(mm/dd/yyyy,12/31/9999)
2	2-DataGov(LowDate01/01/0001)		To_date(mm/dd/yyyy, 01/01/0001)
3	3-DataGov(AverageChurn)		Count(active customers)/(Count o Cancelled Customers for current month)


3. Click .

The Transformation Rule Editor page appears.


Defining Transformations

The screenshot shows the 'Transformation Rule Editor' interface. It includes a 'Published' toggle switch (currently OFF), a 'Transformation Name*' text input field, a 'Scope' dropdown menu (set to 'All Projects'), an 'ETL Option' dropdown menu (set to 'SSIS Pseudocode'), a 'Pseudocode' text area (containing '1') with an 'ON' toggle switch and the label 'Replace Transformation Name with Pseudocode', and an 'Intended Use' text area. A note at the bottom indicates: 'Note: Press `Ctrl + Space` to select Transformations'.

4. Enter or select appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.

Field Name	Description
Published	Switch Published on () to publish the transformation.
Transformation Name	Specifies a unique name of the transformation. For example, ASCII.
Scope	Specifies the projects to which the transformation can be applied. For example, All Projects.
ETL Option	Specifies the ETL option. For example, Informatica Pseudocode.

Defining Transformations

Field Name	Description
	You can configure ETL option list and add or remove an ETL option from the list.
Replace Transformation Name with Pseudocode	Switch Replace Transformation Name with Pseudocode on () to replace the transformation name with pseudocode.
Pseudocode	Specifies the pseudocode for the transformation. Enter a pseudocode or use Ctrl + Space keys to select a pseudocode. For example, To_date(mm/dd/yyyy,1231,9999).
Intended Use	Specifies the objective of the transformation. For example: Data governance rule - use on projects.

5. Click .

A new transformation is added on the Transformations Details page.

For more information on transformations, refer to the [Defining Transformations](#) section.


Mapping Source and Target

You can create mapping specifications using drag and drop method, even when source column names are different from target column names. After mapping source to target, you can set the target update strategy and enter a description about the strategy.

To create mapping specifications using drag and drop method, follow these steps:

1. Under the **Workspace Mappings** pane, click the required map.

By default, it opens the Mapping Specification tab.




2. Click .

You can now, edit the Mapping Specification tab.

3. Drag source table or column from **Metadata Tree View** and drop in **Mapping Specification**.

You cannot drop source system or source environment in Mapping Specification. Ensure that you drop source table or column under the respective column.



4. Drag target table or column from **Metadata Tree View** and drop in **Mapping Specification**.

You cannot drop target system or target environment in Mapping Specification. Ensure that you drop target table or column under the respective column.

Mapping Source and Target

5. Click .


The mapping specification is saved.

To set the target update strategy, follow these steps:

1. Expand the **Additional Mapping Information** pane.

The pane is available at bottom of the central pane when you click the map in Work-space Mappings.

2. Click the **Target Update Strategy** tab.



3. In the **Target Update Strategy** tab, click .

4. Click the required strategy, enter **Update Strategy Description**, and click .

The target update strategy is set.

You can enrich a mapping specification by:

- [Adding transformation and lookup details](#)
- [Associating code cross walks \(code mappings\)](#)
- [Associating reference tables](#)
- [Linking requirements](#)

After creating a mapping specification, you can analyze a mapping specification. [Analyzing mapping specification](#) involves:

- Generating virtual preview of target
- Previewing Data
- Performing table gap analysis

Mapping Source and Target

- Performing column gap analysis
- Running impact analysis
- Running lineage analysis
- Running end to end lineage
- Opening business view
- Viewing mapping statistics


Categorizing Codesets and Defining Code Values

You can create and manage codesets in Codesets Manager. Its workspace has two sections, Enterprise Codesets and Codeset Mappings. You can categorize and define codesets in the Enterprise Codesets section, while you can create codeset crosswalks (mappings) in the Codeset Mappings section.

Before defining codesets, you need to create categories to hold the codesets.

To create categories, follow these steps:

1. Go to **Application Menu > Data Catalog > Codeset Manager**.
2. In **Codesets Workspace**, right-click the **Codesets** node.



The screenshot shows the 'Codesets Manager' interface. On the left, the 'Codesets Workspace' is visible with a tree view containing 'Enterprise Codesets', 'Environments', and 'Codesets'. A context menu is open over the 'Codesets' node, showing 'New Category' and 'Export All' options. On the right, a 'Summary' table is displayed with the following data:

#	Category Name
1	SAP
2	EDW
3	EDW
4	EDW
5	ICD 10
6	ICD 10

3. Click **New Category**.

The New Category page appears.

The screenshot shows a window titled "New Category". In the top right corner of the window, there are icons for a save function (a floppy disk) and a close function (an 'X'). The main area of the window contains two input fields. The first is labeled "Category Name*" and is a single-line text box. The second is labeled "Category Description" and is a multi-line text area.

4. Enter **Category Name** and **Category Description**.

For example:

- Category Name - EDW
- Category Description - This category contains three codesets, Country Codes, Gender, and Marital Status.

5. Click .


A new category is created and added to the category tree.

After creating a category, you can define codesets, which are stored inside the category.

To define codesets, follow these steps:


Categorizing Codesets and Defining Code Values

1. Right-click the category node created by you in the above step.



2. Click **New Codeset**.

The New Codeset page appears.

A screenshot of the 'New Codeset' form window. The window title is 'New Codeset'. It contains two input fields: 'Codeset Name*' with an asterisk indicating it is required, and 'Codeset Description'. There are icons for a document and a close button in the top right corner of the form area.

3. Enter **Codeset Name** and **Codeset Description**.

For example:

Categorizing Codesets and Defining Code Values

- Codeset Name - Country Codes
- Codeset Description - This codeset has code names and code values for four countries.


4. Click .

A codeset is created and stored in the codesets tree.

We can populate code values in codesets by scanning the database.

To populate code values in codesets via DB scan, follow these steps:

1. Click the codeset created by you.



The screenshot shows the 'Enterprise Codesets' workspace. On the left, a tree view displays the 'Codesets' folder expanded, with 'A_Codeset(1.00)' selected. On the right, the 'Code Value Grid' is visible, featuring a table with two columns: 'Code Name' and 'Code Value'. The table currently contains two empty rows.

Code Name	Code Value

2. In **Code Value Grid**, click .

3. Click  and expand the **Quick Connection** pane.

Categorizing Codesets and Defining Code Values

Quick Connection

*Mandatory Fields

DBType: *

Driver Name:

IP Address/Host Name:*

Port:*

Database Name:*

System Name:*

4. Enter appropriate values in the fields (connecting parameters). Fields marked with a red asterisk are mandatory. Refer to the following table for field description.

Field Name	Description
DBType	Specifies the database type. For example, Sql Server. Select the database type from which you wish to scan codes.
Driver Name	Specifies the JDBC driver name for connecting to the database. For example, com.microsoft.sqlserver.jdbc.SQLServerDriver It is autopopulated depending on the DB type. You can also update the driver name.
IP Address/Host Name	Specifies the IP address or server host name of the database. For example, localhost.
Port	Specifies the port to connect with the database. For example: 1433 is the default port for a Sql Server database type.
Database Name	Specifies the database name being used to connect to the code-set. For example, ErwinDIS931.
System Name	Specifies the name of the system related with the codeset. For example, EDW.

Categorizing Codesets and Defining Code Values

Field Name	Description
	The name of the system should be same as provided in Metadata Manager.
System Environment Name	Specifies the name of the environment related with the codeset. For example, EDW-DEV. The name of the environment should be same as provided in Metadata Manager.
User Name	Specifies the user name to connect with database. For example, sa.
Password	Specifies the password to connect with database. For example, goerwin@1.
URL	Specifies the full JDBC URL that is used to establish a connection with the database. For example, <code>jdbc:sqlserver://SERVER_NAME:PORT#;databaseName=DatabaseName</code> It is autopopulated based on the other parameters.

5. Click  to test the connection.

If connection is established then a success message pops up.

6. Write a query in the **Query Panel** and click  to validate the query.

7. Click  to preview the query result.

8. Double-click the **Select CSMHeader Template** cell of the required column.

The columns of the Code Value Grid appears as an option list.

Categorizing Codesets and Defining Code Values


The screenshot shows the DB Scan application interface. The top left pane is the Query Panel with the text "Select*from CAT_DIALOG_TAB". The top right pane is the Quick Connection settings, including DBType (Sql Server), Driver Name (com.microsoft.sqlserver.jdbc.S), IP Address/Host Name (localhost), Port (1433), Database Name (ErwinDIS931), and System Name (A_System). The bottom pane is the Query Result grid, which displays a table with columns: #, CAT_DIALOG_TAB_ID, CAT_DIALOG_PROFILE_ID, CAT_DIALOG_TAB_NAME, CAT_DIALOG_TAB_PROPERTIES, and CREATED_BY. The grid shows 5 rows of data. A dropdown menu is open over the CAT_DIALOG_PROFILE_ID column, showing options: Code Name, Code Value, Code Description, System Environment Name, Start Date, and End Date. A note at the bottom states: "Note*: Only top 50 rows will be displayed in grid."

#	CAT_DIALOG_TAB_ID	CAT_DIALOG_PROFILE_ID	CAT_DIALOG_TAB_NAME	CAT_DIALOG_TAB_PROPERTIES	CREATED_BY
	Select CSMHeader Template	Code Value	Select CSMHeader Template	Select CSMHeader Template	Select CSMHeader Templat
1	1	Code Name	DefaultTab		Administrator
2	2	Code Value	DefaultTab		Administrator
3	3	Code Description	DefaultTab		Administrator
4	4	System Environment Name	DefaultTab		Administrator
5	5	Start Date	DefaultTab		Administrator
		End Date	DefaultTab		Administrator

9. Select the required **Code Value Grid** column.



You can select multiple columns from the data base.

10. Click  to import the selected columns in the **Code Value Grid**.

The selected columns are imported in the Code Value Grid.

You can also enter codes in the Code Value Grid:

- Manually
- Using MS Excel files


For more information on maintaining codesets, refer to the [Maintaining Enterprise Codesets](#) section.

Publishing Codesets

You can publish your codesets to an environment. To publish the codesets, ensure that you have created and setup an environment.


To create publish environments, follow these steps:

1. Go to **Application Menu > Data Catalog > Codeset Manager**.
2. In the **Codesets Workspace** pane, right-click the **Environments** node.



3. Click **New Environment**.

The New Environment page appears.



4. Enter **Environment Name**.


Publishing Codesets

5. Click .

A new publish environment is created and saved in the Publish Environments pane.

To publish codesets, follow these steps:

1. Go to **Application Menu > Data Catalog > Codeset Manager>**.
2. In the **Codesets Workspace** pane, right-click a codeset.



3. Click **Publish**.

The Publish Codesets page appears.

Publishing Codesets

* Publishing the Codeset will create a new version.

Codeset Name: A_Codeset

Codeset Version: 1.01

Codeset Version Label:

Codeset Changed Description*:

Publish Environment*: DEV, PROD, Production, Test

4. Enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field description.


Field Name	Description
Codeset Name	Specifies the name of the codeset which is being published. For example, Country Codes. It autopopulates with the codeset name and cannot be edited.
Codeset Version	Specifies the new version of the codeset. For example, 1.03. It autopopulates with the new version and cannot be edited.
Codeset Version Label	Specifies the version label of the codeset. For example, Beta.
Codeset Changed Description	Specifies the description about the changes in the codeset. For example: Code Value for CANADA was changed to CAN.
Publish Environment	Specifies the publish environment to which the codeset is

Publishing Codesets

Field Name	Description
	being published. For example, Production.

5. Click .

The codeset is published successfully and the published codesets move under Published Codesets pane.




Creating Code Crosswalks (Mappings)

You can create code crosswalks (mappings) for the source and target codesets in Codeset Manager. These codesets can have the same or different code values. Using the Auto-Map functionality, you can map codesets having same code values. Codesets having different code values can be mapped using the drag and drop method.

A category can hold multiple code maps. Code maps are stored in a hierarchical manner, Category > Mappings. You can also create sub-categories under a category to provide one more level of categorization to mappings.

To create a category, follow these steps:


1. Go to **Application Menu > Data Catalog > Codeset Manager > Codeset Mappings**.
2. In the **Code Mappings Workspace** pane, right-click the **Code Mappings** node.



3. Click **New Category**.

The New Category page appears.

Creating Code Crosswalks (Mappings)



4. Enter **Category Name** and **Category Description**.

For example:

- **Category Name:** EDW
- **Category Description:** This category contains two code mappings, Gender Crosswalk and Marital Status Crosswalk.


5. Click .

A new category is created and saved under the category tree.

To create sub-categories under a category, follow these steps:


Creating Code Crosswalks (Mappings)

1. Under the **Code Mappings Workspace** pane, right-click the required category.



2. Click **New Sub Category**.

The New Category page appears.

A screenshot of the 'New Category' dialog box. It has a title bar with 'New Category' and standard window controls. The form contains two fields: 'Category Name *:' with a text input box, and 'Category Desc ::' with a larger text area. There are icons for a document and a close button in the top right corner.

3. Enter **Category Name** and **Category Description**.

For example:

- Category Name - EDW-Finance
- Category Description - This sub-category contains two code mappings, Gender Crosswalk and Marital Status Crosswalk.

Creating Code Crosswalks (Mappings)


4. Click .

A new sub-category is created and saved under the sub-category tree.

You can use Auto-Map functionality to map source and target codesets having same code values.

To create code mappings when source and target codesets have same code values, follow these steps:

1. Right-click the required category.



2. Click **New Map**.

The New Codeset Map page appears.

Creating Code Crosswalks (Mappings)

3. Enter **Codeset Map Name** and **Codeset Map Description**.

For example:

- Codeset Map Name - Gender Crosswalk
- Codeset Map Description - The codeset map is the code mappings between the two codesets, Misc Gender Codes and Gender.

4. Select the **Source Codeset/System** and **Target Codeset/System**.

5. Select the Auto Map check box and click .


A new code mapping is created and source and target codesets are mapped in the Codeset Mapping Grid.

Creating Code Crosswalks (Mappings)

The screenshot shows the 'Codeset Manager' application. The main window is titled 'Codeset Manager' and has a search bar at the top right. The interface is divided into three main sections: 'Code Mappings Workspace' on the left, 'Codeset Mapping Grid' in the center, and 'Codeset Tree' on the right. The 'Code Mappings Workspace' shows a tree view of code mappings, with 'Integrated_Map (1.00)' selected. The 'Codeset Mapping Grid' is a table with the following data:

#	Source Category	Source Codeset	Source Codeset Version	Source System/Environment	Source Code Description	Source Code ID
1	erwin DIS	Sales_Codeset	1.00	Project_System		710
2	erwin DIS	Sales_Codeset	1.00	Project_System		711
3	erwin DIS	Sales_Codeset	1.00	Project_System		712
4	erwin DIS	Sales_Codeset	1.00	Project_System		713

Below the grid, there is a 'CSM MapSpec Overview' section with a 'Codeset Map Name' field containing 'Integrated_Map' and a 'Codeset Map Version' field containing '1.00'. The 'Codeset Tree' on the right shows a hierarchy of codesets, including 'erwin DIS', 'Sales_Codeset', and 'Project_System'.

6. Click  to validate the code mapping.

You need to use drag and drop method to map codesets having different code values.

To create code mappings when source codesets and target codesets have different code values, follow these steps:

1. Right-click the category.

The screenshot shows the 'Codeset Manager' application with a context menu open over the 'erwin DIS' category in the 'Code Mapping Grid'. The context menu options are:

- New Sub Category
- Edit Category
- Delete Category
- New Map
- Import Legacy Maps
- Assign Users

The 'Code Mapping Grid' shows the following data:

#	Source Category	Source Codeset	Source Codeset Version
	erwin DIS	Sales_Codeset	1.00
	erwin DIS	Sales_Codeset	1.00
	erwin DIS	Sales_Codeset	1.00
	erwin DIS	Sales_Codeset	1.00

Creating Code Crosswalks (Mappings)

2. Click **New Map**.

The New Codeset Map page appears.

The screenshot shows the 'New Codeset Map' window. It has a title bar with a save icon and a close icon. The main area contains the following fields and lists:

- Codeset Map Name***: An empty text input field.
- Codeset Map Version**: A text input field containing '1.00'.
- Codeset Map Description**: A large empty text area.
- Source Codeset**: A dropdown menu with a list of options including '3rd Party Flat Files.Misc Marital Status Codes', '3rd Party Flat Files.Misc Gender Codes', 'APJ Demo.Gender Codes', 'EDW.Gender', 'EDW.Marital Status', and 'EDW.Country Codes'.
- Source**: A dropdown menu with a list of options including '3rd Party Flat Files', '3rd Party Flat Files.3rd Party Flat Files', 'A_System', 'A_System.A_Environment', 'AdventureWorks', and 'AdventureWorks.AdentureWorks_Staging'.
- Target Codeset**: A dropdown menu with a list of options including '3rd Party Flat Files.Misc Marital Status Codes', '3rd Party Flat Files.Misc Gender Codes', 'APJ Demo.Gender Codes', 'EDW.Gender', 'EDW.Marital Status', and 'EDW.Country Codes'.
- Target**: A dropdown menu with a list of options including '3rd Party Flat Files', '3rd Party Flat Files.3rd Party Flat Files', 'A_System', 'A_System.A_Environment', 'AdventureWorks', and 'AdventureWorks.AdentureWorks_Staging'.
- Auto Map**: A checkbox that is currently unchecked.
- Note**: A red asterisk followed by the text '*Auto mapping occurs for source and target codes having the same values.'

3. Enter **Codeset Map Name** and **Codeset Map Description**.

For example:

- Codeset Map Name - Gender Crosswalk
- Codeset Map Description - The codeset map is the code mappings between the two codesets, Misc Gender Codes and Gender.

4. Select the Source Codeset/System.

5. Click .


The source codesets details are updated in the Codeset Mapping Grid.

Creating Code Crosswalks (Mappings)


The screenshot displays the Codeset Manager application interface. The main window is titled "Codeset Manager" and contains several panes:

- Code Mappings Workspace:** A tree view on the left showing a hierarchy of code mappings, including "Integrated_Map(1.00)".
- Codeset Mapping Grid:** A central table with columns: #, Source Category, Source Codeset, Source Codeset Version, Source System/Environment, Source Code Description, and Source Code ID. It contains four rows of data for "erwin DIS" mappings.
- Codeset Tree:** A tree view on the right showing the structure of codesets, including "erwin DIS" and "Sales_Codeset".
- CSM MapSpec Overview:** A pane at the bottom showing fields for "Codeset Map Name" (Integrated_Map) and "Codeset Map Version" (1.00).

#	Source Category	Source Codeset	Source Codeset Version	Source System/Environment	Source Code Description	Source Code ID
1	erwin DIS	Sales_Codeset	1.00	Project_System		710
2	erwin DIS	Sales_Codeset	1.00	Project_System		711
3	erwin DIS	Sales_Codeset	1.00	Project_System		712
4	erwin DIS	Sales_Codeset	1.00	Project_System		713

6. Click .
7. Scroll to right of the Codeset Mapping Grid to see the Target Code Value column.
8. In **Codeset Tree**, expand the target category and the Codesets node.
9. Drag and drop the target codeset into the Code Set Mapping Grid under the Target Code Value column.

Creating Code Crosswalks (Mappings)



10. Click .


The code mappings are successfully saved.

11. Click  to validate the code mapping.

The code map is validated. Ensure that all the required codes are mapped.

Use the following options:

Export

To download the code map details in .xlsx format, click .

Extend Mapping Grid

To extend the Codeset Mapping Grid, click .

Associating Code Mappings with Data Item Mappings

A code map can be associated with a data item mapping to standardize data across the organization. These code maps are maintained in Codesets Manager. For more information on codesets and code mappings, refer to the [Using Codesets Manager](#) section.


Before associating a code map with data item mappings, ensure that you publish the code map.

Publishing Code Maps

To publish code maps, follow these steps:

1. Go to **Application Menu > Data Catalog > Codeset Manager > Codeset Mappings**.
2. In the **Code Mappings Workspace** pane, right-click a code map.

The available options appear.



3. Click **Publish**.

The Publish Codeset Map page appears.

Associating Code Mappings with Data Item Mappings

The screenshot shows a window titled "Publish Codeset Map" with the following fields and values:

- Codeset Map Name***: Integrated_Map
- Codeset Map Version**: 1.01
- Codeset Map Description**: Code map when source and target have different code values.
- Map Version Label**: (empty)
- Map Changed Description***: Updated Code Values.
- Publish Environment***: DEV, PROD, Production, Test

4. Enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.

Field Name	Description
Codeset Map Name	Specifies the name of the code map. For example, Gender Crosswalk.
Codeset Map Version	Specifies the new version of the code map. For example, 1.02.
Codeset Map Description	Specifies the description about the code map. For example: The codeset map is the code mappings between the two codesets, Misc Gender Codes and Gender.
Map Version Label	Specifies the version label of the code map. For example, Beta.
Map Changed Description	Specifies the description about the changes made in the code map. For example: Code values were updated.
Publish Environment	Specifies the environment where the code map is being published. For example, test. You can create publish environments in Enterprise Codesets.


Associating Code Mappings with Data Item Mappings

Field Name	Description
	For more information on creating publish environments, refer to the Publishing Codesets topic.

5. Click .

The code map is published and it can be found in the Published Code Mappings pane under the selected Publish Environment.

A new version of the code map is created under the Mappings tree.



A published code map can be associated with a mapping in the Mapping Manager. The published code map is available under the Code Mappings Catalog.

Associating Code Maps

To associate published code maps with data item mappings, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, click the required map.

Associating Code Mappings with Data Item Mappings

The Mapping Specification grid appears.

#	Target System Name	Target Environment Name	Target Table Name	Target Column Name	Target Column Data Type	Target Column Length
1	SQLTechPubs	SQLTechPubs	dbo.Customers	CustomerID	nchar	5
2	SQLTechPubs	SQLTechPubs	dbo.Customers	CompanyName	nvarchar	40
3	SQLTechPubs	SQLTechPubs	dbo.Customers	ContactName	nvarchar	30
4	SQLTechPubs	SQLTechPubs	dbo.Customers	ContactTitle	nvarchar	30
5	SQLTechPubs	SQLTechPubs	dbo.Customers	Address	nvarchar	60

3. Click .

4. In the **Mapping Specification** grid, right-click the header menu.

Target Table Name	Target Column Name	Target Column Data Type	Target Column Length	Target Column Precision	Target Column Scale	Target Column Nullable Flag
customers	PostalCode	nvarchar	10	0		
customers	City	nvarchar	15	0	0	<input checked="" type="checkbox"/>

5. Select the **CSM Mapping** check box.

The CSM Mapping Column appears in the Mapping Specification grid.

6. In the right pane, expand **Code Mapping Catalog**.

7. Drag the code map into the **Mapping Specification** grid and drop it under the **CSM Mapping** column for the required row.

Associating Code Mappings with Data Item Mappings

8. Click .


The code map is associated with the data item mappings.

Creating Business Terms

Business terms are globally defined terms that represent your business terminology usage. Using business terms, you can maintain a common business vocabulary across your organization. You can create business terms in new or existing catalogs. For more information about catalogs, refer to the [Creating Catalogs](#) topic.

To create business terms, follow these steps:

1. Go to **Application Menu > Data Literacy > Business Glossary Manager > Explore**.
2. Go to the **Business Terms** tab.
The Workspace switches to the business terms view.
3. In the **Asset Workspace** pane, right-click a catalog.



Creating Business Terms

4. Click **New Business Term**.



The New Business Term page appears.

5. Enter appropriate values to the fields. Fields marked with a red asterisk are mandatory.

Refer to the following table for field descriptions.

Field Name	Description
Acronym	Specifies whether the business term is an acronym.
Business Term	Specifies the name of the business term. For example, Account.
Definition	Specifies the definition of the business term. For example: An Account contains data for a party.
Description	Specifies the description of the business term. For example: Account contains data for posting, payments, debt recovery, and taxes.
Notes	Specifies the reference notes, if any. For example: The data for posting, payments, debt recovery, and taxes was imported from the Account.xlsx file.
Governance	Specifies the users assigned with data governance responsibilities for

Creating Business Terms

Field Name	Description
Responsibilities	the business assets. For more information, refer to Updating Data Governance .
Classification	<p>Specifies the sensitive data indicator (SDI) classification of the business term. Also, you can add multiple SDI classifications to a business term.</p> <p>For example, PHI.</p> <p>For more information on configuring SDI classifications, refer to the Configuring Sensitive Data Indicator Classifications topic.</p> <p> By default, this field is enabled for business terms. For more information on enabling sensitivity fields, refer to the Configuring Asset Details topic.</p>
Business Term Image Uploader	Drag and drop a picture of business term or click  to browse and upload a picture.

6. Click .

A business term is created and added to the catalog.

Based on your workflow assignment settings, the business term may need further action for review or approval. For more information, refer to the [Managing Business Glossary Workflows](#) topic.

Once, a business term is created you can set up associations for business terms.


You can also create Business Policies, Business Rules, and other business assets in the Business Glossary Manager. For more information on creating business assets, refer to the [Managing Business Glossary](#) section.

Setting Up Associations for Business Terms


By default, you can associate business terms with business assets (business policies and other business terms) and technical assets (columns, environments, and tables). You can control the available asset types for association using the Business Glossary Manager settings page. For more information, refer to the [configuration](#) topic.

To set up associations, follow these steps:

1. On the **Compact View** tab, click .

Alternatively, on the **Grid View** tab, under the **Options** column, click . Then, click **Associations**.

The Associations tab opens in edit mode.




The screenshot shows the 'Associations' tab for the business term 'Economic Growth' in edit mode. The interface includes a header with the term name and a close button, a navigation bar with tabs for 'Edit Business Term', 'Additional Information', 'Associations', 'Rich Media Library', 'My Action Center', and 'Workflow Log', and a table with columns for 'Actions', 'Qualifier Name', 'Relationship Name', 'Term Name', 'Description', 'Definition', 'Catalog Name', and 'Catalog Hierarchy'. The table is currently empty, displaying 'No Records Found'.

Actions	Qualifier Name	Relationship Name	Term Name	Description	Definition	Catalog Name	Catalog Hierarchy
No Records Found							

Setting Up Associations for Business Terms

2. In the asset type (business policies, business terms, columns, environments, and tables) list, select an asset type to associate with the business term.




The screenshot shows the 'Associations' page for the business term 'Economic Growth' (Customer Terms). The page has a blue header with navigation tabs: 'Edit Business Term', 'Additional Information', and 'Associations'. Below the header is a dropdown menu for selecting an asset type. The dropdown is open, showing a list of asset types: Business Term, Dataset, Business Policy, Business Rule, Tags, System, Environment, and Table. The 'Business Term' option is selected and highlighted in blue. To the right of the dropdown is a table with two columns: 'Relationship Name' and 'Term Name'. Both columns have empty input boxes below them.

Relationship Name	Term Name
<input type="text"/>	<input type="text"/>

3. Click +.
The Relationship Associations page appears. Based on the asset type that you select, it

Setting Up Associations for Business Terms

displays a list of available assets.



Relationship Associations [Save] [Cancel]

Current Context: Economic Growth

Current Context Type: Business Term

Relationship Name: is a Synonym of

Search (partial matches):

<input type="checkbox"/>	Term Name	Description	Definition	Catalog Name	Catalog Hierarchy
<input type="checkbox"/>	3-Hydroxyl End	LEN(D3)	The hydroxyl group that is attached to the 3 carbon atom of the sugar (ribose or deoxyribose) of the terminal nucleotide of a nucleic acid molecule.	Macroeconomics	Monetary Terms → Macroeconomics
			3-A Sanitary Standards, Inc. (3-A SSI) is a non-profit association representing equipment manufacturers, processors, regulatory sanitarians and other public health professionals.		

4. Select assets to associate with your business term.
If you know the asset name, use the Search (partial matches) field to look up for it.
5. Click **Save**.
The selected assets are associated with the business term and added to the list of associations.
You can define as many associations as required.


Creating Test Cases

You can create multiple test cases at project level and, record expected and actual results. Using these test cases, you can test data mappings and ETL process. You can also manage test cases as per your requirements.

To create test cases, follow these steps:

1. In the **Workspace Mappings** pane, expand a project.
2. Click the **Test Cases** node.

The Test Case Summary pane appears.



3. Click .

The Add New Test Case page appears.

Creating Test Cases

4. Enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.

Field Name	Description
Test Case Name	Specifies the name of the test case. For example, Verifying the Completeness of Source Metadata.
Test Case Label	Specifies the unique label for the test case. For example, Source Metadata.
Type of Testing	Specifies the type of testing. For example, Metadata Testing.
Test SQL Script	Specifies the SQL script required in the test execution. For example, select * from dbo.ADS_ASSOCIATIONS.
Description	Specifies the test objective in brief.

Creating Test Cases

Field Name	Description
	For example: The objective of the test case is to verify the completeness of source metadata.
Expected Result	Specifies the expected result of the test case in detail. For example: The source table should have 50 columns.
Actual Result	Specifies the actual test result after the execution of the test. For example: The source table has 39 columns.
Testing Comments	Specifies the testing comments about the test case. For example: The source metadata was scanned from a Sql Server database.

5. Click **Save and Exit**.

The test case is created and saved under the **Test Cases** node.


For more information on test cases, refer to the [Creating and Managing Test Cases](#) topic.

Documenting Requirements

You can document functional requirements in a standardized manner in Requirements Manager. It is an agile and collaborative platform to create customized requirements templates.


To document your requirements in standard templates, follow these steps:

1. Go to **Application Menu > Data Catalog > Requirements Manager > Requirements Workspace**.
2. Right-click the **Specification Templates Catalogue** node.



3. Click **Create Project**.

Create Project page appears.



Documenting Requirements

4. Enter **Project Name** and **Project Description**.


For example:

- Project Name - Nasdaq PDLC
- Project Description - This project captures functional and business requirements of the data migration project.

5. Click .

A new project is created and stored in the project tree.

6. Right-click the project node.



7. Click **Create Specifications**.

Create Specifications page appears.

Documenting Requirements

8. Enter appropriate values in the fields. Fields marked with a red asterisk are mandatory. Refer to the following table for field descriptions.

Field Name	Description
Specification Template Type	Specifies the template of the specification. For example, Health Migration Template. You can create templates and add artifacts to templates in the Requirements Manager Settings .
Specification Template Description	Specifies the description about the specification template. For example: The Health Migration Template is to capture functional and business requirements of the data migration project.
Specification Name	Specifies the name of the specification. For example, OrganMatch.
Specification Version	Specifies the version of the specification. For example, 1.01.

Documenting Requirements


Field Name	Description
	The specification version is autopopulated. For more information on configuring version display of specifications, refer to the Configuring Version Display topic.
Version Label	Specifies the version label of the specification. For example, Beta. For more information on configuring version display of specifications, refer to the Configuring Version Display topic.
Specification Description	Specifies the description about the specification. For example: The specification uses the Health Migration Template to capture functional and business requirements of the data migration project.
Specification Owner	Specifies the specification owner's name. For example, Jane Doe.
Status	Specifies the status of the specification. For example, Pending Review.
Mail Comments	Specifies the mail comments, which are sent to the project users. For example: The specification uses the Health Migration Template. For more information on configuring email notifications, refer to the Configuring Email Settings topic.

9. Click .

A new specification is created and stored in the specifications tree. The specifications tree is nested under the project node.

10. Document your requirements in the **Specification Overview** page.

Documenting Requirements



Specification Overview page depends on the **Specification Template Type** selected while creating the specification.

11. Click .

The artifact is saved.

For more information on creating specifications and documenting requirements, refer to the [Using Requirements Manager](#) section.

Linking Requirements to Mappings

To ensure enterprise-wide traceability, you can link your functional requirements to data mappings.

To link functional requirements to mappings, follow these steps:

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. Click a mapping.

The mapping opens in the detailed view.

#	Source System Name	Source Environment Name	Source Table Name	Source Column Name	Source Column Data Type	Source Column Length	Business Rule
1	A_System	A_Environment	dbo.CAT_DIALOG	CAT_DIALOG_TAB	int	4	
2	A_System	A_Environment	dbo.CAT_DIALOG	CAT_DIALOG_PRC	int	4	
3	A_System	A_Environment	dbo.CAT_DIALOG	CAT_DIALOG_TAB	varchar	50	
4	A_System	A_Environment	dbo.CAT_DIALOG	CAT_DIALOG_TAB	varchar	4000	
5	A_System	A_Environment	dbo.CAT_DIALOG	CREATED_BY	varchar	50	
6	A_System	A_Environment	dbo.CAT_DIALOG	CREATED_DATE_Tl	datetime	8	

3. On the **Mapping Specification** tab, right click the grid header.


A list of header columns appears.

Linking Requirements to Mappings

#	Source System Name	Source Environment Name	Source Table	Source Column	Source Column Data Type	Source Length
1	A_System	A_Environment			nt	4
2	A_System	A_Environment			nt	4
3	A_System	A_Environment	dbo.CAT_DIALOG	CAT_DIALOG_TAB	varchar	50

4. Scroll down the list and select the **Specification Artifact** check box.
The specification Artifact column becomes visible on the Mapping Specification tab.
5. In the right pane, click **Specification Artifact Catalog**.
6. Expand the project that contains the required specification.
7. Drag and drop the specification on the **Specification Artifacts** column in the required row.

st Column Type	Target Column Length	Created By	Created Date	Specification Artifacts	Last Modified By	Last Modified Date Time
	4	Administrator	2019-10-16 15:44:32.383	Sp_Name (v1.00)	Administrator	2019-10-17 11:56:07.883
	4	Administrator	2019-10-16 15:44:32.383		Administrator	2019-10-16 15:45:28.353
ar	50	Administrator	2019-10-16 15:44:32.383		Administrator	2019-10-16 15:45:28.353

8. Click .
Requirements are linked to the selected mapping.

Running Lineage Analysis

After mapping source metadata with target metadata, you can run the lineage analyzer in Metadata Manager. You can run forward, reverse, and dual lineage analysis to trace metadata at the system, environment, table, and column level.


Forward lineage analysis generates lineage with the table as source. And reverse lineage analysis generates lineage with the table as target. The Dual lineage analysis generates a lineage, which includes both forward and reverse lineage.

This topic walks you through the steps to run lineage at the table level as an example.

To run lineage at the table level, follow these steps:


1. Go to **Application Menu > Data Catalog > Metadata Manager**.
2. In the **Data Catalog** pane, click the required table.
3. In the right pane, click the **Data Lineage** tab.

By default, dual lineage of the table appears in Graphical View.



4. You can click **Graphical View** or **Grid View** to switch between them:
 - **Graphical View:** The graphical view displays the lineage of the table in a graphical format. Selecting a table on the graphical view displays its Legends. Hovering over a table displays an **i** icon. Clicking this icon opens the object's properties.

Running Lineage Analysis



- Grid View:** The grid view displays the lineage of the table in a tabular format. You can view the source and target system, environment, table and column associated with the selected table.

#	Source System Name	Source Environment Name	Source Table Name	Source Column Name	Target System Name	Target Environment Name	Target Table Name
1	SQL System	Northwind			SQL System	Northwind	
2	SQL System	TechPubs			SQL System	Northwind	
3	SQL System	SQL Env	dbo AdventureWorksDWBld Version		SQL System	TechPubs	
4	erwinDoc	erwinDOC	CustDetails		TABLEUAU		
5	SQL System	TechPubs			SQLTechPubs	SQLTechPubs	dbo.Categories
6	SQL System	TechPubs			SQLTechPubs	SQLTechPubs	dbo.Categories
7	SQLTechPubs	SQLTechPubs	dbo.Categories	Picture	SQL System	TechPubs	
8	SQL System	TechPubs			SQLTechPubs	SQLTechPubs	dbo.Categories


Use the following options to work on the lineage in graphical view:

Search (🔍)

Use this option to search for tables that you want to see on the lineage.


As you type in the search box, a list of related tables that are available on the lineage appears.

Running Lineage Analysis




Filter Objects ()

Use this option to filter and display required tables in the lineage view.



The unselected objects are replaced with black dots on the lineage diagram.




Switch View ()

Double-click an object to see Switch View option. Use this option to switch the level of objects displayed and see the system, environment, or table in which


Running Lineage Analysis

the object is located.



Options (⚙️)

Use this option to view lineage types, business properties and customizations options. For more information on lineage options, refer to the running lineage analysis on [Table](#) topic.



Export (📄)


Use this option to export the lineage. Click  and use the following options:

- **Image (🖼️)**: Use this option to download the lineage as an image, in the .JPG format. Ensure that you expand the required nodes in a lineage before downloading the lineage as image.

Running Lineage Analysis



- **PDF (📄):** Use this option to download the lineage report in the .PDF format. Ensure that you expand the required nodes in a lineage before downloading the lineage report as PDF.
- **Excel (📊):** Use this option to download the lineage report in the .XLSX format. Ensure that you expand the required nodes in a lineage before downloading the report.

On the lineage, expand a table node, and select a column to view its lineage path. The column is highlighted in blue color, its forward lineage path appears in red, and its reverse lineage path appears in blue. The assets that are not part of a lineage path disappear.



Click a path around the selected object to highlight its path of the source or target in the lineage.

Viewing Transformations

Transformations between columns are indicated using  in the lineage. Hover over  to view transformation rules for the columns on a pop-up. Or, click the path between the columns to highlight it to view detailed transformations between them in the Transformation Details pane.

Running Lineage Analysis

The screenshot displays the 'Dual Lineage: SQLTechPubs' interface. On the left, a list of properties is shown, including Map ID (105), Project Name (Project Tech Pubs), Map Name (erwinsalesintegration), Map Spec Version (1.01), Source Extract SQL, Source Column Name (customerid), Source Column Data Type (nvarchar), Source Column Precision (0), Source Column Length (5), Source Column Scale (0), Target Column Name (OPER), Target Column Data Type (NUMBER), Target Column Precision, Target Column Length, Target Column Scale, Business Rule (TRUNC), Extended Business Rule, Trans lookup Condition (SELECT CustomerID FROM dbo.Customers WHERE CustomerID = dbo.Customers.CustomerID), Lookup On (CustomerID), and Map Sequence Id (935). The main area shows a diagram with a source column 'customerid' and a target column 'OPER'. A red arrow points from the source column to the target column, and a blue box highlights the 'ER_RAN' node. A red arrow points from the 'ER_RAN' node to the 'Transformation' node in the legend on the right. The legend on the right shows the 'Transformation' node expanded, displaying properties such as Project Name (Project Tech Pubs), Map Name (erwinSalesIntegration), Map Spec Ver (1.01), JOB_XREF, Source Extra, and Source Colur (customerid).

You can expand the transformation node to view the transformation details that includes Business Rule, Extended Business Rule, Trans lookup Condition, Lookup On, and more relevant properties.

You can also run the lineage at the following levels:

- System
- Environment
- Column

For more information on performing lineage analysis in Metadata Manager, refer to the [Running Lineage Analysis](#) section.

Running Impact Analysis

After mapping source metadata with target metadata, you can run impact analysis on the technical assets that form the mappings. Impact analysis helps you understand upstream and downstream dependencies of technical assets. It helps you assess the impact of transformations and source or target-level changes.

This topic walks you through the steps to view impact analysis of a table. Similarly, you can view impact of a column, system, and environment.


To run impact analysis at table level, follow these steps:

1. Go to **Application Menu > Data Catalog > Metadata Manager > Explore**.
2. On the Explore tab, click an environment tile to see its details.
3. In the **Data Catalog** pane, click a table.
4. Click the **Impact Analysis** tab.

Impact analysis of the table appears.

It displays the asset hierarchy, sensitivity data indicator (SDI) classification, data quality analysis, and table's impact based on related assets in your metadata.

The screenshot shows the 'Impact Analysis' tab for the table 'dbo.Customers'. The interface includes a navigation bar with tabs: Columns, Properties, Extended Properties, Data Lineage, **Impact Analysis**, Mindmap, Associations, Workflow Log, Documents, Indexes, and Test Specification. Below the navigation bar, there are filters for Asset Type (TABLE), Environment (SQLTechPubs), System (SQLTechPubs), and Classification (Secret). A 'DQ Score' indicator is also present. The main content area displays a summary of impacts: 3 Systems, 3 Environments, 3 Tables, 19 Columns, 32 Other Impacts, 0 Transformation Rules, 0 Extract SQL, 0 Lookups, and 0 Linked To Business Assets. Each impact category has 'UPSTREAM' and 'DOWNSTREAM' arrows with associated counts.

Alternatively, click  to switch the **Overview Impact** option **ON** to exclude non-existent systems and environments from the impact analysis. When this option is switched off, the view includes systems and environments that do not exist in the Metadata

Running Impact Analysis

Manager.

The screenshot shows a dashboard with a 'DQ Score' of 0% in a circular gauge. To the right are 'LINEAGE' and 'EXPORT' buttons, and a settings gear icon. Below the gauge, it says 'Linked To 0 Business Assets'. A modal window titled 'Overview Impact' is open, featuring a toggle switch for 'Includes only Metadata Assets' which is currently turned on.

5. On the Tables card, click **Upstream**.

The upstream dependencies of the environment appear in a grid format.

The screenshot displays a navigation bar with four cards: 'Systems' (4 impacts), 'Environments' (4 impacts), 'Tables' (4 impacts), and 'Columns' (21 impacts). The 'Tables' card is selected and shows 'UPSTREAM' and 'DOWNSTREAM' buttons. Below the cards, there are filters for 'Has' (32 other impacts) and 'Linked To' (0 business assets). A tabbed interface shows 'Upstream (2)' selected. Below is a table of upstream dependencies:

#	System Name	Environment Name	Table Name	Project	Subject Area	Mapping
1	TABLEUAU	PRESENTATION LAYER	Account	Test		Data Integration
2	erwinDoc	erwinDOC	CustDetails	erwinDIS		Data Integration



Similarly, you can view downstream dependencies on the Downstream tab.

6. On the Upstream or Downstream tab, click an asset to view its lineage or impact analysis. For more information on running lineage analysis on assets, refer to the [Running](#)

Running Impact Analysis

[Lineage Analysis](#) topic.

Upstream (5)		Downstream (5)	
#	System Name	Environment Name	Project
1	SQL System	TechPubs	TestingBugs
2	SQLTechPubs		TestingBugs
3	SQL System		Flow Test
4	Oracle	TechPubs	erwinSalesIntegration

-  Lineage
-  Impact Analysis

Use the Other Impacts tile, and click one of the following to view them:

- Business rules
- Source Extract SQL
- Lookups

For example, the image below displays the In Lookups tab with lookup conditions that impacts the asset type. Also, you can switch between In Source Extract SQL and In Business Rules tabs to view relevant impacts.

Impacts 4

Systems

← UPSTREAM 2

→ DOWNSTREAM 2

Impacts 4

Environments

← UPSTREAM 2

→ DOWNSTREAM 2

Impacts 4

Tables

← UPSTREAM 2

→ DOWNSTREAM 2

Impacts 21

Columns

← UPSTREAM 7

→ DOWNSTREAM 14

Has

32

Other Impacts

TRANSFORMATION RULES 0

EXTRACT SQL 0

LOOKUPS 32

Linked To

0

Business Assets

In Transformation Rules (0)

In Source Extract SQL (0)

In Lookups (32)

Source Table	Source Column	Lookup Condition
dbo.Customers		SELECT CompanyName FROM dbo.Customers WHERE CompanyName = dbo.Customers.CompanyName
dbo.Customers		SELECT ContactName FROM dbo.Customers WHERE ContactName = dbo.Customers.ContactName
dbo.Customers		SELECT ContactTitle FROM dbo.Customers WHERE ContactTitle = dbo.Customers.ContactTitle
dbo.Customers		SELECT CustomerID FROM dbo.Customers WHERE CustomerID = dbo.Customers.CustomerID

Running Impact Analysis

You can also view the upstream and downstream dependencies of other impacted assets from selected table's perspective. For example, the image below displays upstream column dependencies from the table's perspective.

The screenshot displays the Impact Analysis interface. At the top, there are several navigation buttons: 'Impacts' (4) with 'UPSTREAM' and 'DOWNSTREAM' arrows, 'Systems' (2), 'Environments' (4), 'Tables' (4), 'Columns' (21), and 'Other Impacts' (32). Below these are 'Linked To Business Assets' (0) and 'Upstream (7) Downstream (14)' tabs. The main table shows the following data:

#	System Name	Environment Name	Table Name	Column Name	Project	Subject Area	Mapping
1	Salesforce	TechPubs	Account	Type	Project		SalesforceIntegration
2	Oracle	TechPubs	APPQOSSYS.WLM_CLASSIFIER_PLAN	CHKSUM	erwinDIS		erwinSalesIntegration
3	Oracle	TechPubs	APPQOSSYS.WLM_CLASSIFIER_PLAN	ACTIVE	erwinDIS		erwinSalesIntegration
4	Oracle	TechPubs	APPQOSSYS.WLM_CLASSIFIER_PLAN	TIMESTAMP	Project Tech Pubs		erwinSalesIntegration

Additionally, use the following options:

Lineage

Use this option to view lineage based on the asset type.

Export

Use this option to export the impact analysis in the XLSX format.

For more information on performing lineage and impact analysis in the Metadata Manager, refer to the [Running Impact](#) and [Lineage Analysis](#) section.

You can also [run impact analysis](#) in the Mapping Manager on:


- Any source/target table
- Any source/target column

Exporting Mapping Specifications to ETL Tools

Once the mappings are considered 'approved for coding', you can export the mappings as coding requirements to automatically generate ETL/ELT jobs. The ETL jobs can be generated for tools, such as Informatica PowerCenter, IBM DataStage, Microsoft SQL Server SSIS, and Talend.

1. Go to **Application Menu > Data Catalog > Mapping Manager**.
2. In the **Workspace Mappings** pane, click the required map.

The **Mapping Specification** grid appears.




#	Source System Name	Source Environment Name	Source Table Name	Source Column Name	Source Column Data Type	Source Column Length	Business Rule
1	erwinDIS	erwinDIS	dbo.ADS_ASSOCI	ID	bigint	8	ABS
2	erwinDIS	erwinDIS	dbo.ADS_ASSOCI	SOURCE_OBJECT_	bigint	8	ABS
3	erwinDIS	erwinDIS	dbo.ADS_ASSOCI	SOURCE_OBJECT_	bigint	8	ABS

3. Click .


The Export Window page appears.

Exporting Mapping Specifications to ETL Tools



4. Click the **ETL Engineering** tab.


Exporting Mapping Specifications to ETL Tools




5. Select the required ETL tool and click .

The Multi Mapping page appears.


Exporting Mapping Specifications to ETL Tools



6. Select the mapping and click .

The following notification appears.

Exporting Mapping Specifications to ETL Tools



7. Click the **Download File** hyperlink.

The mapping specification is exported.